



## SP500-Cotag

Access Control

### Switch-plate proximity reader

- 
- Compact proximity reader
  - Can be mounted in most single-gang back-boxes
  - Reading range of up to 30 cm with active card and up to 10 cm with passive card.

The SP500-Cotag is a compact proximity reader for SiPass access control system. It can be mounted in most single-gang back-boxes. It has a reading range of up to 30 cm.

## Technical data

---

<b>SP500-Cotag</b>	
Card technology	Cotag
Card read distance	Up to 30 cm with active card. Up to 10 cm with passive card.
Interface to controller	BC-Link, Clock&Data or Wiegand
Operating voltage	10.6 to 32 VDC
Current consumption	100 mA
Indicators	3 x LED (red/yellow/green) 1 x Buzzer
Environment	Indoor or outdoor use
Operating temperature	-30 to +50 °C
IP rating	IP55
Housing	ABS base houses fully encapsulated electronics, clip-on ABS front cover
Colour	White
Dimensions (W x H x D)	86 x 86 x 14 mm
Keypad	No
Approval	CE

## Details for ordering

---

Type	Part no	Designation	Weight
SP500-Cotag	S24246-F4704-A1	Switch-plate proximity reader	0.10 kg

Issued by  
Bewator AB  
SE-171 24 Solna  
Sweden

[www.buildingtechnologies.siemens.com](http://www.buildingtechnologies.siemens.com)

© 2008 Copyright by  
Bewator AB, a Siemens company  
Data and design subject to change without notice.  
Supply subject to availability.

---

Document no. **A6V10208962**  
Edition 04.2008