

# Nextiva S1970e

## Compact, DVD-Quality Ethernet Video Server

The Nextiva™ S1970e Ethernet video server is a single-port, DVD-quality encoder designed for digital video monitoring and surveillance over IP networks.

The S1970e can deliver 4CIF, 25 Frames Per Second (FPS) for single-camera applications requiring optimal image quality. With MPEG-4 SP video compression, dynamic bandwidth allocation, and dual streaming capabilities, the Nextiva S1970e helps optimise use of valuable network resources. And the S1970e is built for ease of use, enabling up to five authorised users to simultaneously monitor live video and configure other unit settings using Internet Explorer and a secure and intuitive Web browser interface.

### Easy to Configure and Manage

Nextiva Control Centre, an easy-to-use management portal, simplifies deployment and enables the Nextiva S1970e to be configured and administered from a single location and application. Nextiva HealthCheck™ continuously monitors the performance of the S1970e, with automated diagnostics and problem correction for greater uptime and lower service costs. The Nextiva S1970e can also be configured and managed using Verint® nDVR™, Loronix Video Manager™, or from a Web browser.

Built on accepted industry standards for easy interoperability with existing IT infrastructure and video equipment, the Nextiva S1970e is a comprehensive IP camera solution designed to deliver superior functionality, long-term investment protection, and value.

### Verint. Powering Actionable Intelligence.®

Verint Systems (NASDAQ: VRNT) is a leading global provider of analytic software-based solutions for communications interception, networked video, and business intelligence. Verint solutions transform voice, video, and text into actionable intelligence - timely, mission-critical insights for achieving strategic goals.

Since 1994, Verint has been committed to developing innovative solutions that help our customers achieve their most important objectives. Today, more than 1000 organisations in over 50 countries use Verint's actionable intelligence solutions to enhance security, boost operational efficiency, and fuel profitability.

#### KEY FEATURES

- ✓ DVD-quality, single-port encoder
- ✓ Dual streaming, MPEG-4 SP compression, and dynamic bandwidth allocation to optimise network use
- ✓ SSL-based authentication for enhanced security
- ✓ RS-422/485 serial port to support motorised domes and cameras
- ✓ Ethernet 10/100Base-T interface
- ✓ Standards based and firmware upgradeable for investment protection
- ✓ Automated configuration, health monitoring, and diagnostics with Nextiva

Nextiva Intelligent Edge Devices address security and performance challenges across a wide range of environments and applications.

The Nextiva S1970e features DVD-quality images and secure Web video streaming for single-camera applications.

Nextiva S1970e



**VERINT**  
POWERING ACTIONABLE INTELLIGENCE®

## Technical Specifications

<b>NETWORK</b>		<b>POWER</b>	
Interface	Ethernet 10/100Base-T	Supply Voltage	12V DC $\pm$ 10% (4.3W)
Connector	RJ-45 jack	Power Supply	Included
Protocols	Transport: RTP/IP, UDP/IP, TCP/IP, or multicast IP Others: DNS, NTP, HTTP, FTP, and DHCP client	<b>PHYSICAL</b>	
Security	SSL-based authentication	Dimensions	106 x 90 x 42 mm. (4.2 x 3.5 x 1.7 in )
<b>VIDEO</b>		Weight	260 g (9.2 oz)
Output	1 composite, 1 Vpp into 75 ohms (NTSC/PAL)	Environmental Humidity	0°C to 50°C (32°F to 122°F) 95% non-condensing at 50°C (122°F)
Dual Stream	4CIF, 25 FPS and CIF, 12.5 FPS programmable	<b>MANAGEMENT</b>	
Connector	BNC female	Configuration	Nextiva, nDVR, Loronix Video Manager, SConfigurator, or Internet Explorer 6.0
Compression	MPEG-4 SP	Firmware Upgrade	Flash memory for upgrade of video codec and application firmware over the network
Resolution	Scalable from 176x144 to 704x576 pixels PAL	<b>CERTIFICATION AND REGULATION</b>	
Frame Rate	1-25 FPS programmable (full motion)	USA	FCC part 15 (subpart B, class A)
Bandwidth	Configurable 30 kbps to 6 mbps	Canada	ICES-003/NMB-003
<b>ALARM</b>		Europe	CE marked, EN 55022:1998 class A, EN 55024
Alarm	Input: 1 dry contact input Output: 1 optically isolated contact (48V AC/DC at 100 mA max.)	<b>MODELS</b>	
Alarm Connector	5-position terminal block	S1970e-T	Compact, DVD-quality Ethernet video server with 1 bidirectional audio channel; power supply included
<b>AUDIO</b>		S1970e-T-XT	With 1 bi-directional audio channel and extended temperature range (-30 to +60°C); power supply included
Bi-directional Audio	Input: -46 to -3 dBV into 30 kOhm (line or microphone input) Output: -46 to -3 dBV into 16 ohms min.	<b>WARRANTY</b>	
Audio Connectors	1/8 in. (3.5 mm) stereo jacks	3-year limited warranty, covering parts and labour	
<b>SERIAL PORT</b>			
Electrical Levels	422/485 2/4 wires		
Connectors	5-position terminal strip		
Operating Mode	Transparent serial port supporting any asynchronous serial protocol		

Contact your Verint representative for specific configurations, ordering codes, and pricing information.

By providing this document, Verint Systems Inc. is not making any representations regarding the correctness or completeness of its contents and reserves the right to alter this document at any time without notice.

All marks referenced herein with the ® or TM symbol are registered trademarks or trademarks of Verint Systems Inc. or its subsidiaries. All rights reserved. All other marks are trademarks of their respective owners.

© 2006 Verint Systems Inc. All rights reserved.

Email: [marketing.emea@verint.com](mailto:marketing.emea@verint.com)

Phone: +44(0)1932 839500

Or on the web: [www.verint.com](http://www.verint.com)

241 Brooklands Road, Weybridge, Surrey, KT13 ORH, UK.

July 2006

**VERINT**  
POWERING ACTIONABLE INTELLIGENCE®