

## CE202D-N NETWORK INDOOR CAMERA DOME



- 1080p resolution
- Day/night camera with integral fixed lens
- H.264 high-profile, MPEG-4 and M-JPEG compression
- 0.2 lux low light capabilities @ 50 IRE
- Power-over-Ethernet (IEEE 802.3af) or 12 VDC
- Triple streaming video
- Surface mounting
- IP65

### Overview

Vicon's CE202D-N Camera Dome is designed for indoor security installations. This cost-effective fixed network camera includes an integral 3.7 mm megapixel fixed lens. The 1080p resolution delivers crisp clear images.

The CE202D-N provides triple-streaming video and supports H.264 compression technology, drastically reducing file sizes and conserving valuable network bandwidth. MPEG-4 and M-JPEG compressions are also provided. Privacy masking and motion detection features are provided.

Installation of the CE202D-N is made easy and cost effective with Power over Ethernet (IEEE 802.3af), which eliminates the need for power cables. The camera also accepts 12 VDC.

The day/night camera provides superior image quality around the clock. The camera dome provides manual pan and tilt adjustment for any angle of view.

### Model Descriptions

| Resolution | Lens         | Model Number |
|------------|--------------|--------------|
| 1080p      | 3.7 mm fixed | CE202D-N     |

|                                   |   |
|-----------------------------------|---|
| Model                             | CE202D-N  |
| Image Sensor:                     | 1/2.8-inch Sony Exmor CMOS; progressive scan  |
| Max Resolution:                   | 1080p   |
| Image Settings:                   | Adjustable bit rate. Flip and mirror. Configurable brightness, contrast, color, hue, sharpness. Auto Exposure (AE). Auto White Balance (AWB). Noise reduction (2DNR). Day/night. BLC (Backlight Compensation). Privacy Masks (8 windows). Motion detection (8 zones). |
| Shutter Speed:                    | 1/30 -1/20,000 sec; slow shutter control: 1/4, 1/8, 1/15 sec  |
| Day/Night Performance:            | Digital day/night   |
| Minimum Illumination:             | Color: 0.02 fc (0.2 lux); B/W: 0.02 fc (0.2 lux); @f/1.8, 50 IRE  |
| <b>Lenses</b>                     |   |
| Focal Length:                     | Megapixel 3.7 mm fixed  |
| Max. Aperture:                    | f/1.8   |
| Horizontal Field of View:         | 89.0°   |
| <b>Network Video Transmission</b> |   |
| Network:                          | 10Base-T, 100Base-TX, RJ-45   |
| Image Compression:                | H.264; MPEG-4; MJPEG  |
| Resolution:                       | Full HD (1920x1080), SXGA (1280x1024), HD (1280x720), D1 (720x480), VGA (640x480), CIF (352x240), QVGA (320x240)  |
| Protocol:                         | IPv4, IPv6, Manual, TCP, IP, HTTP, HTTPS, RTSP/RTP/RTCP, SMTP, DHCP, NTP, DDNS, UDP, FTP, Bonjour   |
| Frame Rate:                       | Full HD, 30 fps at all resolutions  |
| Streams:                          | Triple streaming  |
| Users:                            | Live viewing for up to 10 clients   |
| Web Browser:                      | Internet Explorer®, Safari®, Google Chrome®, Firefox®   |
| Security:                         | IP address filtering, HTTPS encrypted data transmission, SSL, password protection   |
| <b>Mechanical and Electrical</b>  |   |
| Construction:                     | Plastic base and clear plastic dome   |
| Camera Angle of Adjustment:       | Pan and tilt 90° adjustment manually  |
| Mounting:                         | Surface mount   |
| Dimensions:                       | 4.5 in. (115 mm) (Diam) x 2.2 in. (55 mm) (H), 2.2 in. (57 mm) (Dome Diam)  |
| Weight:                           | 0.6 lb (270 g)  |
| Input Power:                      | 12 VDC, PoE (IEEE 802.3af Class 0)  |
| Current:                          | 12 VDC: 375 mA  |
| Power Consumption:                | 4.5 W   |
| Storage:                          | Slot for Micro SD card (card not supplied)  |
| <b>Environmental</b>              |   |
| Operating Conditions:             | Temp: 14 to 104° F (-10 to 40° C); Humidity: 0 to 80%, non-condensing   |
| Approvals:                        | FCC Class A, CE; IP65   |
| Warranty:                         | 3 years   |

Controls and Connectors

|                    |   |
|--------------------|---|
| External Controls: | Reset Button: sets factory defaults.  |
| Connectors:        | Power: 12 VDC: jack for power supply; PoE/Network: RJ-45 CAT 5. Alarm cables.<br>Local Storage: Micro SD card slot. |

Dimensional Drawing  
Unit: mm

