

2U 26-Bay Rackmount Video Recording Appliance Integrated with Milestone XProtect® and Storage Accelerator

Video Processing and Customized to Scale Over Time

Benefit from scalable storage performance and video processing with the VSS-MS-262x-M appliance. This 2U, 2-socket platform brings you scalability and performance to adapt to a variety of the most demanding and process-intensive Milestone XProtect applications.

Storage Accelerator

The VSS-MS-262x-M comes equipped with a state-of-the-art Storage Accelerator, which allows you to fully utilize its 364TB of raw storage capacity without the need for live video drives. With the Storage Accelerator enabled, read/write speeds exceed that of four-hundred and fifty 15K SAS drives combined, ensuring disk bandwidth is never an issue. In addition, the Storage Accelerator's capacitor backup to non-volatile cache helps prevent data loss should a device lose power for added reliability.

System Reliability

System reliability and high availability are guaranteed with redundant 1100W power supplies and RAID 5/6 storage options, while a five-year, onsite, next business day, Keep Your Hard Drive warranty ensures peace of mind.

Keep Your Hard Drive

With Video Storage Solutions' Keep Your Hard Drive warranty, your sensitive data and hard drive never leave your control. It also helps you comply with current data privacy regulations and internal company policies by ensuring sensitive information on your hard drive is not compromised, mitigating the risk of expensive civil litigation if confidential customer data or intellectual property were to be exposed.





Back

KEY FEATURES

- · Up to 364TB of Raw Storage
- Intel® Xeon® Silver 4216 Scalable Processors
- · Operating System: Windows 10 Pro, Windows Server 2016
- iDRAC features include:
 - Remote Management
 - Disaster Recovery
 - Critical Resource Monitoring









NVME. SATA. & SAS



5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty



Redundant Power



RAID Options: 0, 1, 5, 6, 10



Storage Accelerator

FOR MORE INFORMATION

videoappliances.com sales@videoappliances.com +1.888.305.4993

TECH SUPPORT

support@videoappliances.com

Intel, the Intel logo, the Intel Inside logo and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.





2U 26-Bay Rackmount Video Recording Appliance Integrated with Milestone XProtect® and Storage Accelerator

PERFORMANCE	
Bandwidth	Up to 1600 Mbps
STORAGE ACCELERATOR FEATURES	
IOPS	135,000
Capacity	1.6TB
Response Time	30 μs
Endurance	8.76 Total Petabytes Written
SYSTEM	
Processor(s)	Dual Intel® Xeon® Silver 4216 (16 Cores, 32 Threads, 3.20GHz)
Processor Passmark	Dual Intel® Xeon® Silver 4216: 20,362
Maximum Storage	Up to 364TB
Hard Drives Supported	NVMe, SATA & SAS
Operating System	Windows 10 Pro, Windows Server 2016
Memory	Standard Configuration: 32GB (4x 8GB) Maximum Configuration: Up to 512GB RDIMM, 1TB LRDIMM (16x DDR4 DIMM Slots)
RAID	OS RAID 0, 1; Data RAID 0, 1, 5, 6, 10
RAID Controller	PERC H740P (8GB NV Cache)
Networking	(2) IGbE RJ45 Ports, (2) 10GbE SFP+ ports
Expansion Slots	(0) PCle slots (In default configuration)
USB(s)	Rear (2) USB 3.0, Front (2) USB 2.0, Internal (1) USB 3.0
Video Outputs	(I) VGA
Remote Management	iDRAC Express
Manufacturer	Video Storage Solutions
System Warranty	5-Year, On-site, Next Business Day, Keep Your Hard Drive Warranty
MECHANICAL	
Form Factor	2U Rackmount
Rack Support	Sliding Rack Rail with Cable Management Arm
Hard Drive Bays	(26) 3.5" Hot Swappable Bays & (2) M.2 SSD Slots
Power Supply(s)	(2) 1100W (100-240VAC) 80 Plus Platinum
Maximum Power Draw	1050W
Operating Temperature	(Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35° C]
Operating Humidity	5 ~ 90% (non-condensing)
Dimensions (WxDxH)	19" (482.6mm) x 33.26" (844.83mm) x 3.4" (86.36mm)
Max. Weight	88 lbs. (40 kg)