

5.8GHZ

## RX-5808

Plug & Play out of the box, the low profile desktop design is not susceptible to interference from 2.4GHz 802.11 b/g networks and data devices. Featuring 8 user selectable channels, this system is the ideal choice when multiple indoor wireless video links are required for any commercial, industrial or consumer application.

### ADVANTAGES

- 8 user selectable channels
- Low profile metal case desktop design with convenient slots for permanent mounting
- Stereo audio transmission capable
- Convenient front panel frequency selection, video gain adjustment, power indicator & switch
- Not susceptible to interference from 2.4GHz 802.11 b/g data devices
- Operating voltage from 8.0 to 32 Volts DC with 90% + efficient, low noise switching voltage regulators
- Ideal solution for portable, temporary and covert surveillance or monitoring applications
- One Year Limited Warranty

### SPECIFICATIONS

OPERATING FREQUENCY RANGE	5.725GHz – 5.875GHz; 8 User Selectable Channels
INDOOR RANGE	Up to 1,000 Feet line of sight
ANTENNA TYPE	Omnidirectional Rubber Duck – SMA Male
RECEIVER SENSITIVITY	-84 dBm
VIDEO FORMAT	NTSC or PAL
VIDEO CONNECTOR	BNC Female @ 75 OHMS 1 Volt P-P
AUDIO CONNECTOR	RCA Female Stereo Left & Right @ 600 OHMS 1 Volt P-P
TEMPERATURE RANGE	-22°F to +150°F
OPERATING VOLTAGE	8.0 – 32 VDC – Polarity Protected
CURRENT CONSUMPTION	170 mA – @ 12VDC – 90% + efficient
DIMENSIONS	7.4" x 4.2" x 1.2"
WEIGHT	441g or 15.5 oz
FCC / IC / CE APPROVED	Yes

### KIT INCLUDES

- DESKTOP RECEIVER
- RUBBER DUCK ANTENNA
- 12 VDC POWER SUPPLY
- OPERATING INSTRUCTIONS
- ONE YEAR LIMITED WARRANTY



Desktop Receiver



www.VideoTransmitters.com

US Office: 1711 Cudaback Avenue, Niagara Falls, NY USA 14303  
 Canadian Office: 407 Speers Road, Suite 204, Oakville, ON Canada L6K 3T5  
 Toll Free: 1.888.379.2666 Tel: 905.339.0366 Fax: 905.339.1776

© Copyright 2006  
Printed in Canada