900 MHz

The new wireless SPUD camera series sends real time, high resolution video in applications ranging from surveillance to remote monitoring. Half the size of a 9 Volt battery, the SPUD is ideal in scenarios where only a battery is possible.

Advantages

- Easy to use Includes Wireless SPUD Camera and Receiver
- Size: only 1.1" x 0.9" x 0.7"
- Ideal for Portable, Temporary and Covert Surveillance or monitoring applications
- · Includes universal wall or ceiling mounting bracket
- · Incredibly sharp high resolution color picture
- Perfect for the office, warehouse, nursery and more
- Outperforms 2.4 GHz for penetration through walls
- Outperforms 2.4 GHz for mobile or bodycam application
- One Year Limited Warranty



SPUD-975 Color Kit SPUD-940 B/W Kit



SPECIFICATION	
Radiated Power	50 mV/m @ 3m
Transmitter Frequency	916.5 MHz
Operating Distance Line of Sight	Up to 700 feet (300 feet indoors)
Antenna Type	Fixed Omni-Directional
Video Format	NTSC
SPUD-975 Color CMOS	3.7mm lens - Auto Iris - Min 3 Lux
SPUD-940 B/W CMOS	3.7mm lens - Auto Iris - Min 0.5 Lux
Resolution	380 Lines (H) x 350 Lines (V)
Temperature Range	-22° F to 140° F
Power Supply Included	9 to I4VDC – Polarity Protected
Current Consumption	65 mA @ 12 VDC
Dimensions	1.1" × 0.9" × 0.7"
FCC / Industry Canada Approved	YES

KIT INCLUDES One Wireless Color Camera One Wireless Video Receiver One Universal Mounting Bracket One AA Battery Pack Holder One set of RCA Video Cables Two 12 VDC Power Supply Operating Instructions



I 888 379-2666 www.VideoTransmitters.com

US Office: 2930 Pine Avenue, Niagara Falls NY, USA 14301 Canadian Office: 407 Speers Road, Suite 204, Oakville, ON Canada L6K-3T5 Tel: 905 339-0366 Fax: 905 339-1776