

The T-900 series is an incredibly small video transmitter that outperforms 2.4GHz video series for punching through walls. Ideal choice for building into custom mini camera housings, these tiny transmitters are perfectly suited for applications where only a battery is possible. Choose one of two fixed frequencies for applications ranging from surveillance to remote monitoring.

Advantages

- Easy to use – “Plug & Play”
- Ideal for portable, temporary and covert surveillance or monitoring applications
- Low current consumption for convenient battery operation.
- Custom configure your own wireless video camera
- Eliminates the need for cabling or trenching
- Outperforms 2.4 GHz for wall penetration
- Outperforms 2.4 GHz for mobile and bodycam applications
- One Year Limited Warranty



T-906 / T-916



T-906HP / T-916HP

SPECIFICATIONS	T-906 / T-916	T-906HP / T-916HP
Radiated Power	50 mV / m @ 3m	250 mW
Range (Line-of-Sight)	Up to 1,000 Feet	Up to 2,000 Feet
Fixed Frequencies	906MHz OR 916MHz – NOT Selectable	
Antenna Type – Fixed	Omni-Directional	
Video Format	NTSC or PAL	
Video Input	RCA Male @ 75 Ω – 1 Volt p-p	
Temperature Range	-22°F to 140°F	
Power Supply Not Included	9 to 14VDC – Polarity Protected	
Current Consumption	50 mA @ 12V	80 mA @ 12V
Dimensions	0.75" x 0.6" x 0.2"	1.5" x 0.6" x 0.2"
FCC / IC Approved	YES	N/A

Requires 900MHz receiver – not included

900 MHz

The T-900ahpm series is deceptively versatile for its compact size. Capable of transmitting wireless video through poured concrete walls (when most other transmitters cannot), this surprisingly small device draws less than 100mA of current. With a convenient terminal strip at its base, connecting and disconnecting power or video sources are made quick and easy. Choose one of two fixed frequencies for applications ranging from surveillance to remote monitoring.

Advantages

- Easy to use – “Plug & Play”
- Ideal for portable, temporary and covert surveillance or monitoring applications
- Easy connect Terminal Strip for Quick Setup
- Custom configure your own wireless video camera
- Low current consumption for convenient battery operation.
- Outperforms 2.4 GHz for wall penetration
- Outperforms 2.4 GHz for mobile and bodycam applications
- One Year Limited Warranty



**T-906AHPM /
T-916AHPM**

SPECIFICATIONS	T-906AHPM / T-916AHPM
Radiated Power	350 mW
Range (Line-of-Sight)	Up to 3,000 Feet
Fixed Frequencies	906MHz OR 916MHz – NOT Selectable
Antenna Type – Fixed	Omni-Directional
Video Format	NTSC (PAL Format Optional)
Video Input	Terminal Block @ 75 Ω – 1 Volt p-p
Audio Input	Terminal Block @ 600 Ω – 1 Volt p-p
Temperature Range	-22°F to 140°F
Power Supply Included	9 to 14VDC – Polarity Protected
Current Consumption	70 mA @ 9V, 100 mA @ 12V
Dimensions	2.5" x 1.1" x 0.2"
FCC / Industry Canada Approved	N/A

Requires 900MHz receiver – not included