

2.4GHZ

TC-2495

Ideal for short to long range transmission when running cable is not possible, economical or convenient. These transmitters are mounted in a metal case for improved EMI / RFI shielding and includes a rubber duck antenna to ensure a robust RF signal. With four user selectable frequencies, this system is perfect for applications ranging from surveillance to remote monitoring.

ADVANTAGES

- Eliminates the need for cabling or trenching
- Sends video from locations normally not possible, convenient or economical with cable
- Ideal for portable, temporary and covert surveillance or monitoring applications
- Four user selectable channels
- One Year Limited Warranty

SPECIFICATIONS

OPERATING FREQUENCY	2.4108GHz – 2.4728GHz; 4 User Selectable Channels
RADIATED POWER	900mW
RANGE (LINE-OF-SIGHT)	One Mile
ANTENNA TYPE	Omnidirectional Rubber Duck
VIDEO FORMAT	NTSC or PAL
VIDEO CONNECTOR	BNC Male @ 75 Ohms 1 Volt P-P
AUDIO CONNECTOR	BNC Female @ 600 Ohms 1 Volt P-P
TEMPERATURE RANGE	-22°F to +150°F
POWER SUPPLY INCLUDED	12 VDC Polarity Protected
CURRENT CONSUMPTION: TX	390mA
CURRENT CONSUMPTION: RX	350 mA @ 12 VDC
DIMENSIONS	2.30" x 5.25" x 1.25" each
WEIGHT	213g or 7.5 oz each
FCC / IC APPROVED	PART 90 AVAILABLE

KITS INCLUDE

- VIDEO TRANSMITTER
- VIDEO RECEIVER
- TWO RUBBER DUCK ANTENNAS
- TWO 12VDC POWER SUPPLIES
- ONE YEAR LIMITED WARRANTY



VIDEO COMM
TECHNOLOGIES

www.VideoTransmitters.com

US Office: 1711 Cudaback Avenue, Niagara Falls, NY USA 14303

Canadian Office: 407 Speers Road, Suite 204, Oakville, ON Canada L6K 3T5

Toll Free: 1.888.379.2666 Tel: 905.339.0366 Fax: 905.339.1776

© Copyright 2006
Printed in Canada