TC-916

The TC-916 wireless transmitter is ideal for punching video through walls or other objects when running cable is not possible or economical. Mounted in a metal case for improved EMI / RFI shielding and includes a Rubber Duck antenna to ensure a robust RF signal. Choose one of two fixed frequencies for applications ranging from surveillance to remote monitoring.

ADVANTAGES

900MHz

- Easy to use "Plug & Play"
- Transmitter Size: 2.5" x 1.5" x 0.6"
- Punches through concrete or cinder block walls
- Outperforms 2.4GHz for wall penetration, mobile and bodycam applications
- One Year Limited Warranty



SPECIFICATIONS

| FIXED FREQUENCY | 906MHz |
|-----------------------|---------------------------------|
| RADIATED POWER | 50 mV / m @ 3m |
| RANGE (LINE-OF-SIGHT) | Up to 1,000 Feet |
| ANTENNA TYPE | Omnidirectional Rubber Duck |
| VIDEO FORMAT | NTSC |
| VIDEO CONNECTOR | RCA Female @ 75 Ohms 1 Volt P–P |
| TEMPERATURE RANGE | -22°F to +140°F |
| POWER SUPPLY INCLUDED | 9 – 14 VDC Polarity Protected |
| CURRENT CONSUMPTION | 50 mA @ 12 VDC |
| DIMENSIONS | 2.5" x 1.5" x 0.6" |
| WEIGHT | 99g or 3.5 oz |
| FCC / IC APPROVED | YES |

KIT INCLUDES

- VIDEO TRANSMITTER
- 12 VDC POWER SUPPLY
- RUBBER DUCK ANTENNA
- ONE YEAR LIMITED WARRANTY
- REQUIRES 900MHz RECEIVER NOT INCLUDED





