

2.4GHZ

TX-2495

Ideal for short to long range transmission when running cable is not possible, economical or convenient. This transmitter is mounted in a metal case for improved EMI / RFI shielding and includes a rubber duck antenna to ensure a robust RF signal. With four user selectable frequencies, this transmitter is perfect for applications ranging from surveillance to remote monitoring.

ADVANTAGES

- Eliminates the need for cabling or trenching
- Sends video from locations normally not possible, convenient or economical with cable
- Ideal for portable, temporary and covert surveillance or monitoring applications
- Four user selectable channels
- One Year Limited Warranty

SPECIFICATIONS

| | |
|-----------------------|---|
| OPERATING FREQUENCY | 2.4108GHz – 2.4728GHz; 4 User Selectable Channels |
| RADIATED POWER | 900mW |
| RANGE (LINE-OF-SIGHT) | Depends on Optional Receiver and Antenna |
| ANTENNA TYPE | Omnidirectional Rubber Duck |
| VIDEO FORMAT | NTSC or PAL |
| VIDEO CONNECTOR | BNC Male @ 75 Ohms 1 Volt P-P |
| AUDIO CONNECTOR | RCA Female @ 600 Ohms 1 Volt P-P |
| TEMPERATURE RANGE | -22°F to +150°F |
| POWER SUPPLY INCLUDED | 12 VDC Polarity Protected |
| CURRENT CONSUMPTION | 400mA |
| DIMENSIONS | 2.30" x 5.25" x 1.25" |
| WEIGHT | 213g or 7.5 oz |
| FCC / IC APPROVED | PART 90 AVAILABLE |

KITS INCLUDE

- VIDEO TRANSMITTER
- RUBBER DUCK ANTENNA
- 12VDC POWER SUPPLY
- ONE YEAR LIMITED WARRANTY



VIDEO COMM
TECHNOLOGIES

www.VideoTransmitters.com

US Office: 1711 Cudaback Avenue, Niagara Falls, NY USA 14303
Canadian Office: 407 Speers Road, Suite 204, Oakville, ON Canada L6K 3T5
Toll Free: 1.888.379.2666 Tel: 905.339.0366 Fax: 905.339.1776

© Copyright 2006
Printed in Canada