

- Zoom lens controller
- Direct connection
- Low cost
- Easy wiring
- · Autopan function



The CBZ unit is for direct control of Pan & Tilt motors. The connection is made by means of a multipolar cable, which directly supplies the power for the concerned functions.

This unit allows the control of common ground or polarity inversion, motor-driven zoom lenses (zoom, focus, iris), with a power supply selectable between 6Vdc and 12Vdc (the latter is the default value). Available in 230Vac and 24Vac versions.

The low cost of this controller and its ease of use make it ideal for small CCTV control systems.







# TECHNICAL DATA



### **GENERAL**

Extruded aluminium body

Epoxypolyester powder painting, anthracite colour

Rubber side covers

Membrane keyboard

Supplied with instruction manual

#### MECHANICAL

Dimensions: 120x185x60mm (4.7x7.3x2.4in)

5 P&T control functions: UP, DOWN, LEFT, RIGHT, AUTO

6 lens control functions: ZOOM IN, ZOOM OUT, IRIS OPEN, IRIS CLOSE,

FOCUS NEAR, FOCUS FAR

### ELECTRICAL

Power consumption: 4W max Max switching power: 45W max

Power supply to the lens: 6Vdc or 12Vdc

#### **CBZ220**

Power supply: 230Vac, 50/60Hz

P&T control voltage: 230Vac, 50/60Hz

Protection fuses: F1 50mA F 250V; F2 (motors protection) 630mA T 250V

#### CBZ24

Power supply: 24Vac, 50/60Hz

P&T control voltage: 24Vac, 50/60Hz

Protection fuses: F1 500mA F 250V; F2 (motors protection) 1.6A T 250V

#### RELATED PRODUCTS

#### **CBZ220**

PTH910, PTH910SA, PTH310, IPTS720, IPT720, NXPTH210

#### CBZ24

PTH911, PTH911SA, PTH311, IPTS721, IPHS721, IPT721, NXPTH211

# ENVIRONMENT

Indoor

Operating Temperature: 0°C / +40°C (32°F / +104°F)

#### COMPLIANCE TO

CE according to EN 61000-6-3, EN 60065, EN 50130-4



Unit Weight: CBZ220 1.1kg / 2.4lb **CBZ24** 1kg / 2.2lb

Package Weight: CBZ220 1.3kg / 2.8lb CBZ24 1.2kg / 2.6lb

Package Dimensions (WxHxL): CBZ220 25x6.5x25cm / 9.84x2.55x9.8in CBZ24 25x6.5x25cm / 9.84x2.55x9.84in

Master Carton: **CBZ220** 20 units **CBZ24** 20 units

ITALY: info@videotec.com FRANCE: info@videotec-france.com U.K.: uksales@videotec.com