

## AS19LED-(W)

19" LED Monitor Plastic WHITE Case

### AS19LED-(W)

Panel Type	19" LED Monitor WHITE
Case Type	Plastic
Maximum Resolution	1280 (H) x 1024 (V)
Active Display Area	376.3 ( H ) × 301.06 ( V ) mm
Pixel Pitch	0.294 x 0.294 mm
Bezel Thickness	24mm
Contrast Ratio	10000:1
Brightness	300 cd/ m <sup>2</sup>
Response Time	5ms
Viewing Angle	170 / 160 (H/V)
Display Colours	16.7 M
Video Synchronization	Yes
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	Yes
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	4:3
VGA Auto Frequency correction	Yes
Number of Speakers	2
Sound Demodulation	Stereo, Audio
Mute	Yes
Work Humidity	10% - 90%
Work Temperature	0° - 40°C
Volume +/- Power On/Off	Yes

### IN/OUT INTERFACE

Video Interface	VGA, 2 x BNC In, 2 x BNC Out, BNC Loop through HDMI input x 1
Audio Interface	Audio x1
Power Interface	AC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	CE / FCC / ROHS
Stand Type	Desktop (Wall Rack Mount Option)
Colour	White
Packing Dimension	500 (W) x 570 (H) x 167 (D) mm
NET Weight	3.22 Kg
GROSS Weight	4.7 Kg



### POWER

Power Supply	AC 100-240V 50/60Hz
Voltage	DC 12V
Power Consumption	<15W

### OSD CONTROLS

Contrast, Brightness, Colour, Tint, Sharpness, Colour Temp., key lock, 3D Interlace, 3D Comb Filter, DNR

### OSD LANGUAGE

English, German, French, Italian, Spanish, Russian, Turkish, Polish & Japanese

### ACCESSORIES

Power Supply / Kettle Lead / VGA Cable / User Manual

