

## DS15LED

15" (4:3) LED Monitor

### DS15LED

Panel Type	15" (4:3) LED Monitor
Case Type	Plastic
Maximum Resolution	1024 (H) x 768 (V)
Active Display Area	304.128 (H) x 228.006 (V) mm
Pixel Pitch	0.297 (H) x 0.297 (V) mm
Bezel Thickness	18mm
Contrast Ratio	700:1
Brightness	350 cd/ m <sup>2</sup>
Response Time	8ms
Viewing Angle	U/D: 65° / 60°, L/ R: 70° / 70°
Display Colours	16.7M
Video Synchronization	TTL Positive or Negative
PC Compatible Frequency	30-60KHz(H) / 56-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	4 : 3
VGA Auto Frequency correction	Yes
Number of Speakers	Right x 1 Left x 1. 2.5W
Sound Demodulation	Stereo. Audio
Mute	Yes
Work Humidity	20 % - 70 %
Work Temperature	-10 to 50 °C
Volume +/- Power On/Off	Yes



### POWER

Power Supply	12VDC, 3amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	< 30W in 'ON' mode

### OSD CONTROLS

Contrast, Brightness, Clock, Phase, H-Position, V-Position, Language

### OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

### ACCESSORIES

Power Supply / Kettle Lead / VGA Cable / Audio Cable / User Manual

### IN/OUT INTERFACE

Video Interface	HDMI x1, VGA x 1 BNC x 2 In / BNC x 1 Out
Audio Interface	Audio In x1
Termination	75 Ohms (Automatic Termination)
Safety & EMC Certification	Energy Star / CE / FCC / ROHS
Vesa Standard Mount	100 x 100mm
Stand Type	Desktop
Colour	Black
Packing Dimension	410 (W) x 410 (H) x 142 (D) mm
NET Weight	2.9 Kg
GROSS Weight	3.85 Kg

