

#### DSMH21.5LED-WGF

Panel Type	21.5" (16:9 ) LED Monitor with Glass Front
Case Type	Metal
Maximum Resolution	1920 (H) x 1080 (V)
Active Display Area	476.64 ( H ) × 268.11 ( V ) mm
Pixel Pitch	0.24825 (H) x 0.24825 (V) mm
Bezel Thickness	Sides: 16mm, Top: 16mm, Bottom: 29mm
Contrast Ratio	1000 : 1
Brightness	250 cd/m <sup>2</sup>
Response Time	1.5 - 3.5ms
Viewing Angle	U/D: 80° / 80°, L/R: 85° / 85°
Display Colours	16.7 M
Video Synchronization	Yes
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V)
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Video Compatibility	Multi-Standard for NTSC / PAL
Aspect Ratio	16:9
VGA Auto Frequency correction	Yes
Number of Speakers	Right x 1 Left x 1. 2.5W
Sound Demodulation	Stereo. Audio
Mute	Yes
Work Humidity	20 % - 70 %
Work Temperature	-10 to 50 °C
Volume +/- Power On/Off	Yes

#### IN/OUT INTERFACE

Video Interface	HDMI x1, VGA x 1, BNC x 2 In/ BNC x 2 Out
Audio Interface	Audio In x 1, Audio L x 1, Audio R x 1
Power Interface	AC In x 1
Termination	75 Ohms (Automatic termination)
Safety & EMC Certification	CE / FCC / ROHS / WEEE
Vesa Standard Mount	100 x 100mm
Stand Type	Picture Frame
Colour	Black
Packing Dimension	610 (W) x 510 (H) x 170 (D) mm
NET Weight	5.5 Kg
GROSS Weight	7.1 Kg



#### POWER

Power Supply	12VDC, 3amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	< 35W in 'ON' mode

#### OSD CONTROLS

Contrast, Brightness, OSD Duration, H-Position, V-Position, Language, Picture Mode, Colour Temp, Scale, Saturation, Backlight, Sleep Timer, Sound, Memory Recall, 3D NR, MPEG NR, PIP, POP

#### OSD LANGUAGE

English, French, German, Spanish, Italian, Russian, Polish and Portuguese

#### ACCESSORIES

Power Supply / Kettle Lead / VGA Cable / Audio Cable / User Manual / Remote Control

