

## TA1011CTD, TA1013CTD, TA1611CTD Video Distribution Amplifiers

Twisted pair in 1 coax out and Twisted Pair video distribution



**TA1011CTD** 1 UTP in 1 coax out and 1 UTP out

ABS 108x76x27 mm 12 Vdc



**TA1013CTD** 1 UTP in 1 coax out and 3 UTP out

ABS 108x76x27 mm 12 Vdc



16 channels of **TA1011CTD** 1 UTP in 1 coax out and 1 UTP out

Metal 482x180x44 mm 1U

### Features:

All units utilise the TA1001R Video Receiver circuit

Two adjustments for colour gain and brightness on receiver

Full motion colour video signal up to 1200 meters from an active transmitter TA1001T or up to 800 meters with with a passive transmitter TP1001LH

BNC coax output to local monitor or DVR - up to 300 meters.

UTP out to remote location up to 800 meters with an active receiver at the remote end.

### SPECIFICATION

|                       |                               |
|-----------------------|-------------------------------|
| Video Output          | 1 Vp-p - 75 ohm BNC connector |
| Frequency Response    | dc to 5Mhz                    |
| Common Mode Rejection | 15Khz to 5Mhz 60dB            |
| DC voltage            | 12 Vdc                        |
| DC current            | 40 mA max. per channel        |

