



MCS-720

Two-way Wireless Indoor Siren

Demand for indoor sirens is growing, fueled by the special security needs of large complexes and multi-story buildings and by regulations prohibiting outdoor sirens. The MCS-720 two-way fully wireless indoor siren provides a flexible and cost-effective solution to these needs. Because it is fully supervised, the MCS-720 makes it possible to install the control panel where an intruder cannot see or reach it. With the siren producing all alerts, the control panel location remains secret.

Featuring an elegant, thin design, the MCS-720 indoor siren fits in unobtrusively with any décor. When activated, the siren sound is extremely strong, ensuring the alarm gets noticed.

- ▶ **Ideal for residential and light commercial applications** including homes and apartments, vacant vacation houses and small stores
- ▶ Differentiated alarm sounds for intrusion and fire
- ▶ Easy, cabling-free installation
- ▶ No external power supply required
- ▶ Fully enclosed electronics area

MCS-720 Two-way Wireless Indoor Siren

Key Features & Benefits

- **Ideal for a wide range of sites**
 - ▶ Modern, thin-profile design fits any décor
 - ▶ Ideal for use in large complexes and multi-story buildings - residential and light commercial

- **Highly reliable and cost-effective**
 - ▶ Two-way continuously supervised communication with the control panel
 - ▶ Loud arming and disarming notifications
 - ▶ 100dB piezo siren
 - ▶ Built-in high-power strobe light (white)
 - ▶ Distinguishes between fire and burglar alarms; emits a different alarm sound for each
 - ▶ Two diversity antennas
 - ▶ Double tamper protection – cover and wall tampers
 - ▶ Protected and fully enclosed electronics area

- **Easy to install and maintain**
 - ▶ Easily installed, with no need for cabling work
 - ▶ Internal antenna
 - ▶ Self-test (diagnostics) button
 - ▶ Wall mount
 - ▶ Low battery indicator

- **Compatible with newer versions of PowerMaxPro™ and PowerMaxComplete™**



MCS-720
Indoor Siren

MCS-720

Specifications

Power supply:	3.6v non rechargeable Lithium battery
Battery life expectancy:	3 years (with typical use)
Sound output:	100dB@1m
Operating frequency (MHz):	315, 433.92, 868.95, or other frequency as required in the country of use
Receiver and transmitter ID type:	24-bit
Flashing lights duration:	100ms ON, 900ms OFF
Dimensions (H x W x D):	161 x 161 x 50mm (6-7/16 x 6-7/16 x 1-3/4in)
Weight:	470g (16.5 oz.)
Color:	White
Operating temperature:	-10° - 60°C (14° - 140°F)
Compliance:	EN 50131-1 Grade 2 (Europe) SSF 1014:3 (Sweden) TO 14 A (Belgium) RSS210 (Canada) CFR47 part 15 (USA)

•Head Office (Israel) Tel (+972-3) 645 6789 •Visonic Iberica de Seguridad (Spain) Tel (+34-91) 659 3120
•Visonic Inc. (U.S.A) Tel (+860) 243 0833 •Visonic Deson Limited (Hong Kong) Tel (+852) 2157 7147
•Visonic Limited (U.K.) Tel (+44-870) 730 0800 •Visonic GmbH (Germany) Tel (+49) 211 600 6960
•Visonic Ltd. (Nordic) Tel (+47) 6758 0843 •Visonic Sp. z o.o. (Poland) Tel (+48-22) 639 3436
•Visonic Ltd. (South Africa) Tel (+27) 84 577 8668

For more information, visit: www.visonic.com

® Visonic and PowerMax are registered trademarks of Visonic Ltd. Other names are the property of their owners. Visonic reserves the right to change information or specifications without notice.

VISONIC LTD. MCS-720 DATA SHEET ENG C-800461 (Rev. 00)

Designed by Linor Ankri



Visonic®

For a secure way of life