

AP3001



Specification

Standard	IEEE802.3 IEEE802.3u IEEE802.3ab IEEE802.3at
Connector	Data in: RJ45 x 1 Data Pin out: 1, 2,3,4,5,6,7,8 Data and Power out: RJ45 x 1 Data Pin out: 1, 2,3,4,5,6,7,8 Power Pin out: 1,2,3,6
Network cable	10BASE-T: 2-pair UTP/STP Cat.3,4,5 cable EIA/TIA-568 100-Ω (100m) 100BASE-TX: 2-pair UTP/STP Cat.5 cable EIA/TIA-568 100- Ω (100m) Recommend Cat.5e cable above 1000Base-T: 4-pair UTP/STP Cat.5e cable
Certification	EMI: FCC Class B, CE Safety: UL, cUL, CE/EN60950-1
Power	Power Input :100~240 VAC, 50~60Hz, 0.72A Power Output :55V @ 0.6A Power Connector : AC Jack
General	LED Indicators: AC Power x 1 ,Feeding Power x 1
Environment	Operating Temperature:0 ~ 40℃ Storage Temperature: -40 ~ 70℃ Operating Humidity: 10 ~ 90%(non-condensing)
Mechanism	Enclosure : Plastic Dimensions(WxHxD): 65 x 36 x 140 mm