



FE9191



FE9391-EV

Fisheye Network Camera



H.265 • 12MP • 360° Panomorph View • PPTZ • 360° 20M IR •
Smart IR II • IP66 • IK10 • EN50155

VIVOTEK's FE9191 and FE9391-EV are the next generation of market-leading 12-Megapixel 360° panomorph network cameras, both featuring a detailed 12-Megapixel CMOS sensor which guarantees superb image quality. Utilizing the latest in panomorph lens technology for 180° panoramic view (wall mount) or 360° surround view (ceiling/wall/floor mount) with zero blind spots, these cameras are able to provide comprehensive coverage of open areas such as airports, shopping malls, parking lots, retail stores, offices and more.


The FE9191 and FE9391-EV (IP66, IK10 rated) are the successors to FE8191 and FE8391-V in the VIVOTEK 360° surround view family. Both new models are equipped with a removable IR-cut filter and WDR Enhancement technology, allowing the cameras to maintain optimal image quality around the clock for unparalleled visibility under high-contrast lighting environments. 3D Noise Reduction technology enables the cameras to capture clear, polished video under low-light conditions. The FE9191 and

FE9391-EV's use of the latest in panomorph lens technology has led to much improved image quality with a huge drop in edge distortion. The FE9391-EV is also updated with the latest in IR illumination, VIVOTEK's Smart IR II technology with Adaptive IR. Adaptive IR enables the FE9391-EV's IR illuminators to adjust to the scene together or individually to provide the best possible IR image, reducing glaring hotspots and/or underexposed dark spots.

The FE9191 and FE9391-EV will also be the first to include a new wave of advanced Video Content Analyses (VCA). Available in 4Q 2017, these will include better object detection in order to reduce false alarms. Through advanced Video Content Analyses functions including crowd detection features the FE9191 and FE9391-EV are the next steps in elevating surveillance cameras from image capturing devices to advanced notification instruments, allowing users to see more in smarter ways.

Key Features

- 12-Megapixel CMOS Sensor
- Real-time H.265, H.264 and MJPEG Compression (Triple Codec)
- 20 fps @ 2816x2816
- 1.29 mm Panomorph Lens for 180° Panoramic View and 360° Surround View
- Removable IR-cut Filter for Day & Night Function
- 360° 20M IR with Smart IR II (FE9391-EV)
- WDR Enhancement for Improved Visibility in Extremely Bright and Dark Environments
- 3D Noise Reduction for Low-light Conditions
- ePTZ for Data Efficiency
- Support Client Side Dewarping
- Pixel Calculator for Image Clarity Measurement
- 802.3at PoE Compliant
- Vandal-proof IK10-rated and Weather-proof IP66-rated Housing (FE9391-EV)
- Built-in MicroSD/SDHC/SDXC Card Slot for On-board Storage



With Smart IR



With Smart IR II (FE9391-EV)

Technical Specifications

| | | | |
|-------------------------------|--|--------------------------|--|
| Model | FE9191: 12MP 360° Panomorph Camera FE9391-EV: 12MP 360° Panomorph Camera, 360° 20M IR, IP66, IK10, EN50155 | Interface | Built-in microphone External microphone input External line output |
| System Information | | Effective Range | 5 meters |
| CPU | Multimedia SoC (System-on-Chip) | Network | |
| Flash | 256MB | Users | Live viewing for up to 10 clients |
| RAM | 1GB | Protocols | IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/ RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X, SSL/TLS, ARP, NTCIP, CIFS/SMB |
| Camera Features | | Interface | 10 Base-T/100 BaseTX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard. |
| Image Sensor | 1/1.7" Progressive CMOS in 4000x3000 | ONVIF | Supported, specification available at www.onvif.org |
| Maximum Resolution | 2816x2816 | Intelligent Video | |
| Lens Type | Fixed-focal | Video Motion Detection | Five-window video motion detection |
| Focal Length | f = 1.29 mm | Alarm and Event | |
| Aperture | F2.2 | Alarm Triggers | Motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection, audio detection |
| Field of View | 180° (horizontal) 180° (vertical) 180° (diagonal) | Alarm Events | Event notification using digital output, HTTP, SMTP, FTP, NAS server and MicroSD card File upload via HTTP, SMTP, FTP, NAS server and MicroSD card |
| Shutter Time | 1/5 sec. to 1/32,000 sec. | General | |
| WDR Technology | WDR Enhanced | Connectors | RJ-45 for Network/PoE connection Audio input *1 Audio output *1 DC 12V Power input Digital input *1 Digital output *1 |
| Day/Night | Removable IR-cut filter for day & night function | LED Indicator | System power and status indicator |
| Minimum Illumination | 0.18 Lux @ F2.2 (Color) <0.001 Lux @ F2.2 (B/W) | Power Input | FE9191: DC12V, PoE 802.3af Class 2 FE9391-EV: DC12V, PoE 802.3af Class 4 |
| Pan/Tilt/Zoom Functionalities | ePTZ: 48x digital zoom (4x on IE plug-in, 12x built-in) | Power Consumption | FE9191: Max. 6.49 W FE9391-EV: Max. 25 W |
| IR Illuminators | FE9391-EV: Built-in IR illuminators, effective up to 20 meters with Smart IR II | Dimensions | FE9191: Ø 139 x 39 mm FE9391-EV: Ø 160 x 61.7 mm |
| On-board Storage | Slot type: MicroSD/SDHC/SDXC card slot Seamless Recording | Weight | FE9191: 345 g FE9391-EV: 846 g |
| Video | | Casing | FE9391-EV: IP66, IK10 |
| Compression | H.265, H.264, MJPEG | Safety Certifications | FE9191: CE, LVD, VCCI, C-Tick, UL, FCC Class B FE9391-EV: CE, LVD, VCCI, C-Tick, UL, FCC Class A, EN50155 |
| Maximum Frame Rate | 20 fps @ 2816x2816 | Audio | |
| Maximum Streams | 4 Simultaneous Streams | Audio Capability | Two-way audio (full duplex) |
| S/N Ratio | 42.9 dB | Compression | G.711, G.726 |
| Dynamic Range | 61.8 dB | | |
| Video Streaming | Adjustable resolution, quality and bitrate, configurable video cropping for bandwidth saving, Smart Stream II | | |
| Image Settings | Adjustable image size, quality and bit rate, time stamp, text overlay, flip & mirror, scheduled profile settings, configurable brightness/contrast/saturation/sharpness, pixel calculator, 3D-Noise reduction, white balance, exposure control, gain, backlight compensation, privacy masks, defog, pixel calculator | | |

Technical Specifications


| | |
|----------------------------|---|
| Operating Temperature | FE9191: Starting Temperature: 0°C ~ 50°C (32°F ~ 122°F) Working Temperature: -10°C ~ 50°C (14°F ~ 122°F) |
| | FE9391-EV (DC12V): Starting Temperature: -25°C ~ 50°C (-13°F ~ 122°F) Working Temperature: -40°C ~ 50°C (-40°F ~ 122°F) |
| Humidity | 90% |
| | 36 months |
| Warranty | 36 months |
| System Requirements | |
| Operating System | Microsoft Windows 8/7 |
| Web Browser | Internet Explorer 10/11 |
| Other Players | VLC: 1.1.11 or above Quicktime: 7 or above |

Included Accessories


| | |
|--------|---|
| Others | Quick installation guide, warranty card, alignment sticker, desiccant bag, screw driver, screws pack, mounting bracket, I/O cable (Cable not included in North America) |
|--------|---|

Dimensions

• FE9191







• FE9391-EV



Compatible Accessories

Mounting Kits

| | | | |
|--|---|--|---|
|  <p>AM-520 Dome adapter</p> |  <p>AM-116/AM-117 Pendant pipe (20cm/40cm)</p> |  <p>AM-114/AM-118 Pendant head</p> |  <p>AM-514 Adapter ring (for FE9191)</p> |
|--|---|--|---|