



# IB9371-HT/EHT

## Bullet Network Camera

H.265 Compression · Smart Stream II · Bandwidth Saving · WDR Pro · SNV · IP66 · IK10 · Extreme Weather · P-iris · 30M IR


VIVOTEK's IB9371-HT and IB9371-EHT are two brand-new professional H.265 high-efficiency outdoor bullet network cameras, offering 30 fps @ 3-Megapixel with outstanding image quality. Employing H.265 technology enables the cameras to provide higher and more efficient image compression rates than previous H.264 systems. In addition, VIVOTEK's sophisticated Smart Stream II Technology enables the cameras to optimize resolution for a desired object or area and therefore to maximize efficiency of bandwidth usage. Combining both H.265 and Smart Stream II, the IB9371-HT and IB9371-EHT can reduce bandwidth and storage consumption up to 80%\* while maintaining image quality with the high standard.

As professional day/night cameras, the IB9371-HT and IB9371-EHT are also equipped with WDR Pro and SNV, empowering users to enjoy superb image-detail in any lighting condition. Additionally, IP66-rated housing ensures the ability of these advanced cameras to withstand rain and dust, thus guaranteeing smooth operation even under a multitude of harsh weather conditions. The cameras' IK10-rated housing can also provide protection against acts of vandalism and other impacts. Finally, a wide operating temperature range further enhances the performance and reliability of the IB9371-EHT in both extremely cold and warm weather, even while using PoE.

\* Depending on scenes

### Key Features

- H.265 Compression Technology
- 1/2.8" Progressive CMOS Sensor
- 30 fps @ 2048x1536
- Smart Stream II to Optimize Bandwidth Efficiency
- WDR Pro for Unparalleled Visibility in High Contrast Environments
- Built-in IR Illuminators, Effective up to 30 Meters
- Remote Focus for Easy Focus Adjustments
- Weather-proof IP66-rated and Vandal-proof IK10-rated Housing
- Extreme Weather Support with PoE
- SNV (Supreme Night Visibility) for Low Light Conditions
- Video Rotation for Corridor View
- P-iris Lens



Parking lot




Train station



City surveillance

## Technical Specifications

<b>Model</b>	IB9371-HT: Remote Focus IB9371-EHT: Remote Focus, Extreme Weather	<b>Alarm Triggers</b>	Video motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection, audio detection
<b>System Information</b>		<b>Alarm Events</b>	Event notification using digital output, HTTP, SMTP, FTP and NAS server, SD Card File upload via HTTP, SMTP, FTP, NAS server and SD card
<b>CPU</b>	Multimedia SoC (System-on-Chip)	<b>General</b>	
<b>Flash</b>	128MB	<b>Smart Focus System</b>	Remote Focus
<b>RAM</b>	512MB	<b>Connectors</b>	
<b>Camera Features</b>		RJ-45 cable connector for Network/PoE connection Audio input Audio output DC 12V power input Digital input*1 Digital output*1	
<b>Image Sensor</b>	1/2.8" Progressive CMOS	<b>LED Indicator</b>	System power and status indicator
<b>Maximum Resolution</b>	2048x1536 (3MP)	<b>Power Input</b>	12V DC IEEE 802.3at PoE
<b>Lens Type</b>	Vari-Focal	<b>Power Consumption</b>	
<b>Focal Length</b>	f = 3 ~ 9 mm	IB9371-HT: Max. 9 W (DC 12V) Max. 11 W (PoE) IB9371-EHT: Max. 20 W (DC 12V-Heater on) Max. 23.6W (PoE-Heater on)	
<b>Aperture</b>	F1.2 ~ F2.3	<b>Dimensions</b>	Ø 88 x 293 mm
<b>Auto-iris</b>	P-iris	<b>Weight</b>	IB9371-HT: 1182 g IB9371-EHT: 1193 g
<b>Field of View</b>	39° ~ 82° (Horizontal) 29° ~ 60° (Vertical) 49° ~ 108° (Diagonal)	<b>Casing</b>	Weather-proof IP66-rated housing Vandal-proof IK10-rated metal housing (Camera Only)
<b>Shutter Time</b>	1/5 sec. to 1/16,000 sec.	<b>Safety Certifications</b>	CE, LVD, FCC Class A, VCCI, C-Tick, UL
<b>WDR Technology</b>	WDR Pro	<b>Operating Temperature</b>	
<b>Day/Night</b>	Removable IR-cut filter for day & night function	IB9371-HT: Starting Temperature: -10°C ~ 50°C (14°F ~ 122°F) Working Temperature: -20°C ~ 50°C (-4°F ~ 122°F) IB9371-EHT: Starting Temperature: -40°C ~ 50°C (-40°F ~ 122°F) Working Temperature: -50°C ~ 50°C (-58°F ~ 122°F)	
<b>Minimum Illumination</b>	0.01 Lux @ F1.2 (Color) 0.001 Lux @ F1.2 (B/W)	<b>Humidity</b>	90%
<b>Pan/Tilt/Zoom Functionalities</b>	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built in)	<b>Warranty</b>	36 months
<b>IR Illuminators</b>	30 meters	<b>System Requirements</b>	
<b>On-board Storage</b>	Slot type: SD/SDHC/SDXC card slot Seamless Recording	<b>Operating System</b>	Microsoft Windows 8/7/Vista/XP/2000
<b>Video</b>		<b>Web Browser</b>	Mozilla Firefox 7~10 (streaming only) Internet Explorer 7/8/9/10/11
<b>Compression</b>	H265 & H264 & MJPEG	<b>Other Players</b>	VLC: 1.1.11 or above Quicktime: 7 or above
<b>Maximum Frame Rate</b>	30fps @ 2048x1536 30fps @ 1920x1080 In all compression modes	<b>Included Accessories</b>	
<b>Maximum Streams</b>	3 simultaneous streams	<b>CD</b>	User's manual, quick installation guide, Installation Wizard 2, ST7501 32-channel recording software
<b>S/N Ratio</b>	60 dB	<b>Others</b>	Quick installation guide, warranty card, sun shield, wall mount bracket, alignment sticker, desiccant bag, waterproof connector, screw pack
<b>Dynamic Range</b>	100 dB	<b>Dimensions</b>	
<b>Video Streaming</b>	Adjustable resolution, quality and bitrate Smart Stream II		
<b>Image Settings</b>	Time stamp, text overlay, flip & mirror Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks Scheduled profile settings, 3DNR, video rotation, defog		
<b>Audio</b>			
<b>Audio Capability</b>	Two-Way Audio (full duplex)		
<b>Compression</b>	G711, G726		
<b>Interface</b>	External microphone input Audio output		
<b>Network</b>			
<b>Users</b>	Live viewing for up to 10 clients		
<b>Protocols</b>	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, SSL, TLS		
<b>Interface</b>	10 Base-T/100 BaseTX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.		
<b>ONVIF</b>	Supported, specifications available at <a href="http://www.onvif.org">www.onvif.org</a>		
<b>Intelligent Video</b>			
<b>Video Motion Detection</b>	Five-window video motion detection		
<b>VCA*</b>	Line crossing detection, field detection, loitering detection		
<b>Alarm and Event</b>			

\* Available per project request.

## Compatible Accessories

### Mounting Kits



**AM-714**  
Junction Box

All specifications are subject to change without notice. Copyright © VIVOTEK INC. All rights reserved.

Ver. 6