

# OMNIKEY® 532I CL USB Reader

Contactless USB smart card reader

- ▶ **Versatile Applications** – Ideal for end-user environments with different contactless smart card technologies and tags in use
- ▶ **Fast Contactless Transmission** – Supports contactless smart cards up to 848 Kbps in fastest ISO 14443 A/B
- ▶ **Designed for User Convenience** – Housing design is optimized for advanced contactless applications
- ▶ **Readily compliant** – Supports HID® iCLASS® and MIFARE® as well as ISO 14443A/B and ISO 15693



## ACCESS quality.

Housed in a robust closed housing with a convenient card retainer, the OMNIKEY® 532I CL represents the ideal reader for contactless technology applications. Featuring a PC-linked reader that reads/writes to 13.56 MHz contactless smart cards in all three HF standards, the OMNIKEY 532I CL economically supports end-user environments where a variety of contactless cards and tags are used.

Utilizing contactless smart card technology for PC-linked applications, the OMNIKEY® 532I CL device allows users to experience the convenience, speed and security of contactless technology for applications, including logon to Windows®, networks, web sites and applications for the secure storage of user names, passwords and personal information.

- ▶ Supports three ISO standards for contactless cards (ISO 14443 A/B and 15693) and Microsoft WHQL
- ▶ Reader supports contactless smart cards with up to 848 Kbps in the fastest ISO 14443 transmission mode
- ▶ Standard application interfaces include PC/SC, Synchronous-API (on top of PC/SC), OCF (Open Card Framework) or CT-API

Contactless smart cards supported:

- ▶ HID: iCLASS®
- ▶ NXP: MIFARE®, DESFire®, SMART-MX and ICODE
- ▶ Texas Instruments: TagIT®
- ▶ ST Micro: x-ident, SR 176, SR 1X 4K
- ▶ Infineon: My-d (in secure mode UID only)
- ▶ Atmel: AT088RF020
- ▶ KSW MicroTech: KSW TempSens
- ▶ iCODE SLI, iCODE SL2 & LRI 64
- ▶ Contactless 2048 bit key generation in RSA mode (JCOP / SMART-MX)

For actual driver downloads please visit [www.hidglobal.com/omnikey](http://www.hidglobal.com/omnikey)

# Specifications

<b>Base Model Number</b>	OMNIKEY® 5321
<b>Dimensions</b>	3.78" x 3.07" x .031" (115 x 96.5 x 25.5 mm)
<b>Weight</b>	Approx. 5.64 oz / 160 g
<b>Power supply</b>	Bus powered
<b>Operating temperature</b>	32°-131° F (0° - 55° C)
<b>Operating humidity</b>	10-90% rH
<b>HOST INTERFACE</b>	
<b>Host Interface</b>	USB 2.0 (also compliant with USB 1.1)
<b>Transmission speed</b>	12 Mbps (USB 2.0 full speed)
<b>CONTACTLESS SMART CARD INTERFACE</b>	
<b>Protocols</b>	T=CL, MIFARE®, iCLASS® / ISO 14443 A with 848 Kbps transmission rate (depending on card) ISO 14443 B with 848 Kbps transmission rate (depending on card) ISO 15693 with 26 Kbps transmission rate (depending on card)
<b>Supported APIs</b>	PC/SC driver (ready for 2.01), Synchronous API (on top of PC/SC))
<b>PC/SC Driver Support</b>	Windows® 2000 / XP (32bit), 2003 Server, 2008 Server Windows® CE 5.0 / 6.0 / CE.NET (depending on hardware), Windows® XP 64bit (AMD64, EM64T, IA64), Windows® Vista (32bit / 64bit), Windows 7 (32bit/64bit) Linux® (in preparation), Mac® OS X 10.5 Leopard (in preparation)
<b>Status indicator</b>	Dual color LED (green=ready, red=busy)
<b>Reader Board</b>	Also available as PCB
<b>Color</b>	Dark grey
<b>Options</b>	<b>Customer Specific Logo:</b> Available upon request
<b>Composition</b>	ABS
<b>Connector cable</b>	70.9" (180 cm)
<b>Meantime between failure (MTBF)</b>	500,000 hours
<b>Compliance / Certification</b>	Microsoft® WHQL <sup>1</sup> , USB 2.0 (USB 1.1 compatible), GSA FIPS 201 approved product list (in preparation)
<b>Safety / Environmental</b>	CE, FCC, UL, RoHS, WEEE
<b>Warranty</b>	Two year manufacturer's warranty. (For drivers, see complete lifetime support policy.)

<sup>1</sup> = Windows® Hardware Quality Lab.



© 2009 HID Global Corporation. All rights reserved. HID, the HID logo, Omnikey and the Omnikey logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 08/2009

MKT-OMNIKEY\_5321\_CL\_DS\_EN Rev. 08/2009



**ACCESS** experience.

hidglobal.com

**HID Global Offices:**

**Corporate North America**  
15370 Barranca Pkwy  
Irvine, CA 92618  
U.S.A.  
Tel: 1 800 237 7769  
Tel: +1 949 598 1600  
Fax: +1 949 598 1690

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Tel: +852 3160 9800  
Fax: +852 3160 4809

**Latin America**  
Circunvalación Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Tel: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Haverhill Business Park  
Phoenix Road  
Haverhill, Suffolk  
CB9 7AE  
England  
Tel: +44 1440 714 850  
Fax: +44 1440 714 840