



# GET READY FOR THE AGE OF FACES

## FACIAL RECOGNITION TERMINAL

### Hikvision Facial Recognition Technology

The DS-K1T605 series is Hikvision's first facial recognition access control terminal embedded with the proprietary deep-learning algorithm. The capability to use captured pictures to build face models makes it stand out among competitors.

#### Main Features:

- Facial registration within 3 seconds
- Import JPG format face pictures with flash disk
- Batch downloading face pictures into terminal through software
- Dual-camera with IR function in one camera – detects faces from 1 meter away
- Detects live human faces and distinguishes them from pictures and videos
- Excellent performance under backlight, strong light, and dim light environments
- Recognizes faces within 1 second and less than 0.6-second interval between recognitions
- 99% success rate, reaching international standards for false acceptance rates (FAR) and false rejection rates (FAR)
- Supports authentication modes among face, fingerprint, card, password and multiple combination.

#### Other Highlights:

- Connects to external card/fingerprint reader to make two-way access control
- Calculates time attendance in software
- Connects to security systems to reduce risks and ensure safety
- Advanced access control functions such as anti-passback, linkage, and interlocking
- Optional 3400 mA high-capacity backup battery
- Touch screen user interface



## APPLICATION SCENARIOS



Factory



Hospital



Office

## KEY PARAMETERS

Model	DS-K1T605E	DS-K1T605EF	DS-K1T605MF-B
	DS-K1T605M	DS-K1T605MF	
LCD Screen	5-inch LCD touch screen; resolution: 800 × 480		
Camera	0.3 MP, live face detection		
Fingerprint Module	/	Optical	
Fingerprint Capacity	/	5000	
Fingerprint False Accept Rate (FAR)	/	≤0.001%	
Fingerprint False Rejection Rate (FRR)	/	≤0.01%	
Face Picture Capacity	2000		
Face Recognition Distance	0.3m to 1m		
Face Recognition Accuracy Rate	>99%		
Face Recognition Duration	≤0.6s		
Card Capacity	5000		
Event Capacity	100,000		
Communication Mode	TCP/IP, Wi-Fi, EHome protocol, RS485, Wiegand 26/34		
Card/Fingerprint Reading Mode	EM Card/Mifare Card	EM Card, Fingerprint/Mifare Card, Fingerprint	Mifare Card, Fingerprint
Interface	Alarm input, USB 2.0, door magnetic sensor, doorbell, exit button, alarm output, lock		



### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

Follow us on social media to get the latest product and solution information



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision\_Global



Hikvision  
Corporate Channel



hikvisionhq

www.hikvision.com