



HIKVISION

2017 Q1

QUARTERLY FEATURED PRODUCTS

PRODUCT SERIES

EasyIP 3.0 Series

Easy & Powerful Security for the Small-Medium Business

- Up to 4K ultra-HD, advanced H.265+ encoding
- Darkfighter ultra-low illumination technology
- Efficient VCA functions
- Easy to install, setup, and manage
- Budget-friendly and powerful



Turbo HD 3.0 Series

Supercharging Analog Systems to Hi-Def

- 5 MP Cameras & up to 1080p output over coax
- Advanced H.265+ encoding
- IR, privacy masking, Smart features and more
- Wide range of in- & outdoor camera types

TURBO HD 3.0



VMS (Blazer) Series

Powerful One-Piece Server & VMS Station

- A server, data storage, VMS station, and NVR in one device
- Advanced hardware and software design for high availability
- Budget-friendly and powerful
- Manages multiple sites and NVRs from one location



STAR PRODUCTS

PanoVu Cameras

Huge Panoramas. Incredible Zoom

- 8 & 16 MP Multi-Sensors with DarkFighter technology
- 180° & 360° Panoramas, with in-camera image stitching
- 23x Optical zoom; 16x digital zoom
- Smart tracking, Smart detection, & more

PanoVu



DarkFighter Cameras

Stunning Color Video in Near Darkness

- 1/1.8" Prog. scan CMOS sensor
- Color imaging at 0.002 Lux; B/W: 0.0002 Lux
- Full HD 1080p; 120 dB WDR; with up to 128 GB on-board storage
- Full smart feature-set
- IP67; EXIR; Motorized lens with smart focus

DARKFIGHTER



Thermal Cameras Series

Bringing the Invisible to Light

- Advanced thermal sensors
- Unaffected by changes in weather, light conditions
- Single- & dual-lens and handheld cameras
- Wide range of Smart features



Access Control + Intrusion Series

A Steady Guard at the Gate

- Video intercom system
- Fully integrated security solution
- Alarm triggering and remote access
- Wide range of options for any application



Network Video Recorder Series

Stable Video Data Storage & Management Station

- Super PoE up to 300 meters
- Patent industry designs to build a stable station
- Powerful decoding and storage capacity
- Low power consumption and light noise



96 M series NVR

Easily build a stable local surveillance center

- Up to 768Mbps bit rate input Max(Up to 16/32/64 camera input)
- Up to 192T storage capacity(8T x 24HDD), support hot swapping
- Redundant power supply
- Support RAID 0/1/5/6/10
- 20-ch 1080p decoding capacity
- Output resolution at up to 4K



PTZ CAMERA

SMART NETWORK PTZ

DS-2DF8436IX-AEL(W)

4MP 36X IR PTZ network camera



- H.265+/H.265/H.264+/H.264
- 4MP HD resolution, 36X Optical Zoom
- DarkFighter ultra-low light technology
- Smart features (smart tracking, etc)
- 200m IR distance
- Wiper for self-cleaning
- Vandal-proof (IK10)

DS-2DF8236IX-AEL(W)

DarkFighter series 2MP 36X IR PTZ network camera



DARKFIGHTER

- H.265+/H.265/H.264+/H.264
- ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 36X Optical Zoom
- Smart features (smart tracking, etc), optical defog
- 120dB WDR
- 200m IR distance
- Wiper for self-cleaning(-W)
- Vandal-proof (IK10)

DS-2DF8836IV-AELW

8MP 36X IR PTZ Network Camera



- 8MP ultra-HD resolution, 36X Optical Zoom
- Smart features (smart tracking, etc)
- 200m IR distance
- Wiper for self-cleaning
- Vandal-proof (IK10)

DS-2DF8236I-AEL(W)

DarkFighter Series 2MP 36X IR PTZ Network Camera



DARKFIGHTER

- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 36X Optical Zoom
- Smart features (smart tracking, etc), optical defog
- 120dB WDR
- 200m IR distance
- Wiper for self-cleaning(-W)
- Vandal-proof (IK10)

DS-2DF6236-AEL

DarkFighter Series 2MP 36X PTZ Network Camera



DARKFIGHTER

- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 36X Optical Zoom
- Smart features (smart tracking, etc)
- 120dB WDR
- Vandal-proof (IK10)

DS-2DF8223I-AEL(W)

DarkFighter Series 2MP 23X IR PTZ Network Camera



DARKFIGHTER

- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 23X Optical Zoom
- Smart features (smart tracking, etc)
- 120dB WDR
- 200m IR distance
- Wiper for self-cleaning(-W)
- Vandal-proof (IK10)

DS-2DF6223-AEL

DarkFighter Series 2MP 23X PTZ Network Camera



DARKFIGHTER

- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 23X Optical Zoom
- Smart features (smart tracking, etc)
- 120dB WDR
- Vandal-proof (IK10)

DS-2DF8336IV-AEL(W)

3MP 36X IR PTZ Network Camera



- 3MP(2048*1536) HD up to 60fps, 36X Optical Zoom
- Smart features (smart tracking, etc)
- 120dB WDR
- 200m IR distance
- Optional wiper(-W)
- Vandal-proof (IK10)

DS-2DF6336V-AEL

3MP 36X PTZ Network Camera



- 3MP(2048*1536) HD up to 60fps, 36X Optical Zoom
- Smart features (smart tracking, etc)
- 120dB WDR
- Vandal-proof (IK10)

DS-2DT6223-AELY

DarkFighter Series 2MP 23X Anti-corrosion PTZ Network Camera



DARKFIGHTER

- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 23X Optical Zoom
- Smart features (smart tracking, etc)
- 316L stainless steel housing
- 120dB WDR
- Vandal-proof (IK10)
- ISO C5-M, NEMA 4X certification

NETWORK PTZ

DS-2DE4A320/4A220IW-DE

3MP/2MP 20X Mini PTZ Dome Network Camera



- 3MP/2MP real-time, 20X Optical Zoom
- Pan 0° to 360°; Tilt -5° to 90°
- Up to 50m IR range, prevent IR reflection
- New-generation bubble, prevent blurs at any angle
- IP66; MIC: Customizable

DS-2DE4A204IW-DE

2MP 4X/20X Mini PTZ Dome Network Camera



DARKFIGHTER

- 2MP real-time, Pan 0° to 360°; Tilt -5° to 90°
- Up to 50m IR range, prevent IR reflection
- New-generation bubble, prevent blurs at any angle
- 4X (2.8 to 12mm) Optical Zoom
- DarkFighter
- IP66; MIC: Customizable

DS-2DY3320/3220-DE(4)

3MP/2MP 20X IR PTZ Bullet Network Camera



- 3MP/2MP real-time, 20X Optical Zoom
- -40°~30° tilt range, 360° endless pan range
- 3D intelligent positioning
- Up to 100m IR range
- Wall-mount/Stand-Mount

DS-2DE2204IW-DE3

2MP 4X mini PTZ network camera



- 2MP real-time
- 4X Optical Zoom
- 3D intelligent positioning
- Privacy mask
- PoE / 12VDC

DS-2DE3304W/3204-DE

3MP/2MP 4X Mini PTZ Network Camera



- 3MP/2MP real-time
- 4X Optical Zoom
- 3D intelligent positioning
- Privacy mask
- PoE/12VDC
- IP66 protection

DS-2DE7230/7220IW-AE

2MP 30X/20X IR PTZ network camera



- 1920*1080P Full HD, 30X/20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output
- Privacy mask
- Up to 150m IR distance
- 24VAC / High-PoE

PTZ CAMERA

DS-2DE7130/7120IW-AE

1.3MP 30X/20X IR PTZ network camera



- 1280*960P HD, 30X/20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output
- Privacy mask
- Up to 150m IR distance
- 24VAC / High-PoE

DS-2DE5230/5220W-AE(3)

2MP 30X/20X PTZ Dome Network Camera



- 1920*1080P Full HD, 30X/20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output
- Privacy mask
- 24VAC / High-PoE

DS-2DE5130/5120W-AE(3)

1.3MP 30X/20X PTZ network camera



- 1280*960P HD, 30X/20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output
- Privacy mask
- 24VAC / High-PoE

DS-2DE5220IW-AE

2MP 20X IR PTZ Network Camera



- 5-inch sized IR PTZ
- 2MP real-time, 20X Optical Zoom
- 3D DNR, DWDR, ICR
- Alarm input/output, privacy mask
- Up to 150m IR
- 24VAC/PoE+

DS-2DE5120I-AE

1.3MP 20X IR PTZ Network Camera



- 5-inch sized IR PTZ
- 1.3MP real-time, 20X Optical Zoom
- 3D DNR, DWDR, ICR
- Alarm input/output, privacy mask
- Up to 150m IR
- 24VAC/PoE+

DS-2DE4220IW-D

2MP 20X IR PTZ network camera



- 4-inch sized IR PTZ
- 2MP real-time, 20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output, privacy mask
- Up to 100m IR
- 12VDC power

DS-2DE4120I-D

1.3MP 20X IR PTZ network camera



- 4-inch sized IR PTZ
- 1.3MP real-time, 20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output, privacy mask
- Up to 100m IR
- 12VDC power

DS-2DE4220W/4120-AE(3)

2MP/1.3MP 20X PTZ Network Camera



- 4-inch bubble
- 2MP/ 1.3MP real-time, 20X Optical Zoom
- 3D DNR, D WDR, ICR
- Alarm input/output, privacy mask
- 24VAC/PoE+

TURBO HD PTZ

DS-2AE5223TI/5123TI-A

1080P/720P 23X IR PTZ Analog Camera



- 1080P/720P video output
- 23X optical zoom
- Up the coxial function
- Privacy masking
- Up to 150m IR distance

DS-2AE4223TI/4123TI-D

1080P/720P 23X PTZ IR Analog Camera



- 1080P/720P video output
- 23X optical zoom
- Up the coxial function
- Privacy masking
- Up to 100m IR distance
- 12VDC

DS-2AE7230TI-A

1080P 30X PTZ IR Analog Camera



- 1080P video output
- 30X optical zoom
- Up the coxial function
- Privacy masking
- Up to 150m IR distance

DS-2AE7123TI-A

720P 23X PTZ IR Analog Camera



- 720P video output
- 23X optical zoom
- Up the coxial function
- Privacy masking
- Up to 150m IR distance

DS-2AE5230T-A(3)

1080P 30X PTZ Dome Analog Camera



- 1080P video output
- 30X optical zoom
- Up the coxial function
- Privacy masking

DS-2AE5123T-A(3)

720P 23X PTZ Dome Analog Camera



- 720P video output
- 23X optical zoom
- Up the coxial function
- Privacy masking

PTZ CAMERA

PanoVu NETWORK CAMERA

DS-2DP1636Z-D

16MP 360° panoramic + 2MP 23x PTZ network camera

PanoVu



Panoramic features

- 8 x 1/1.9" CMOS sensor, 2-ch 4096×1800 realtime videp output
- Horizontal angle of view: 360°, Vertical angle of view: 78°
- DarkFighter ultra-low light technology

PTZ features

- 1/1.9" CMOS sensor, 1920×1080 resolution@30fps
- 23X optical zoom, 16X digital zoom
- smart tracking, smart detection
- DarkFighter ultra-low light technology

DS-2DP0818Z-D

8MP 180° panoramic + 2MP 23x PTZ network camera

PanoVu



Panoramic features

- 8 x 1/1.9" CMOS sensor, 1-ch 4096×1800 realtime videp output
- Horizontal angle of view: 180°, Vertical angle of view: 78°
- DarkFighter ultra-low light technology

PTZ features

- 1/1.9" CMOS sensor, 1920×1080 resolution@30fps
- 23X optical zoom, 16X digital zoom
- smart tracking, smart detection
- DarkFighter ultra-low light technology

DS-2DP1636-D

16MP 360° panoramic network camera

PanoVu



- 8 x 1/1.9" CMOS sensor, 2-ch 4096×1800 realtime videp output
- Horizontal angle of view: 360°, Vertical angle of view: 78°
- DarkFighter ultra-low light technology

DS-2CD6986F-H

8MP 180° panoramic network camera

PanoVu



- 4 x 1/1.9" CMOS sensors, 1-ch 4096×1800 realtime video output
- 180° horizontal panoramic view
- DarkFighter ultra-low light technology

PTZ POSITIONING SYSTEM

DS-2DY5223IW-AE

DarkFighter 2MP 23X Pan-Tilt Positioning Network Camera

DARKFIGHTER



- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 23X optical Zoom
- -90°~90° tilt range, 360° endless pan range
- 3D intelligent positioning
- 120dB WDR
- Up to 150m IR distance

DS-2DY9185-A(I2)

DarkFighter 2MP 23X Pan-Tilt Positioning Network Camera

DARKFIGHTER



- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 23X optical Zoom
- -90°~40° tilt range, 360° endless pan range
- 120dB WDR
- Up to 200m IR distance(optional)

DS-2DY9188-A(I2)(I8)

DarkFighter 2MP 36X Pan-Tilt Positioning Network Camera

DARKFIGHTER



- Ultra-low illumination technology
- 1/1.9" HD CMOS sensor
- 1920*1080P Full HD, 36X optical Zoom
- -90°~40° tilt range, 360° endless pan range
- 120dB WDR
- Up to 200m IR distance(optional)
- Up to 800m laser IR distance(optional)

DS-2DY9187-A(I8)

2MP 32X Pan-Tilt Positioning Network Camera



- 1920*1080P Full HD, 32X optical Zoom
- -90°~40° tilt range, 360° endless pan range
- 120dB WDR
- Up to 800m laser IR distance

NETWORK CAMERA

EasyIP 3.0 NETWORK CAMERA

DS-2CD2085FWD-I

8MP EXIR Mini Bullet network camera

H.265+



- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67;
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2055FWD-I

5MP EXIR Mini Bullet network camera

H.265+



- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2035FWD-I

3MP EXIR Mini Bullet network camera

H.265+



- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2025FWD-I

2MP EXIR Mini Bullet network camera

H.265+



- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2185FWD-I(S)

8MP EXIR Dome network camera

H.265+



- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67; IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2155FWD-I(S)

5MP EXIR Dome network camera

H.265+



- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67; IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2135FWD-I(S)

3MP EXIR Dome network camera

H.265+



- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67; IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2125FWD-I(S)

2MP EXIR Dome network camera

H.265+



- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67; IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2385FWD-I

8MP EXIR Turret network camera

H.265+



- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67;
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2355FWD-I

5MP EXIR Turret network camera

H.265+



- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2335FWD-I

3MP EXIR Turret network camera

H.265+



- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2325FWD-I

2MP EXIR Turret network camera

H.265+



- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T85FWD-I(5/8)

8MP EXIR Bullet network camera

H.265+



- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67;
- 3 streams;
- IS: up to 50 m; I8: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T55FWD-I(5/8)

5MP EXIR Bullet network camera

H.265+



- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- IS: up to 50 m; I8: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T35FWD-I(5/8)

3MP EXIR Bullet network camera

H.265+



- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- IS: up to 50 m; I8: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T25FWD-I(5/8)

2MP EXIR Bullet network camera

H.265+



- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- IS: up to 50 m; I8: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

NETWORK CAMERA

DS-2CD2685FWD-IZ(S)

8MP Vari-focal EXIR Bullet network camera



H.265+



- 4K HD;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2655FWD-IZ(S)

5MP Vari-focal EXIR Bullet network camera



H.265+



- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2635FWD-IZ(S)

3MP Vari-focal EXIR Bullet network camera



H.265+



- 3MP high resolution; H.265+/H.265/H.264+/H.2643 streams;
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2625FWD-IZ(S)

2MP Vari-focal EXIR Bullet network camera



H.265+



- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2785FWD-IZ(S)

8MP Vari-focal EXIR Dome network camera



H.265+



- 4K HD;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2755FWD-IZ(S)

5MP Vari-focal EXIR Dome network camera



H.265+



- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2735FWD-IZ(S)

3MP Vari-focal EXIR Dome network camera



H.265+



- 3MP high resolution; H.265+/H.265/H.264+/H.2643 streams;
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2725FWD-IZ(S)

2MP Vari-focal EXIR Dome network camera



H.265+



- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67, IK10
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H85FWD-IZ(S)

8MP Vari-focal EXIR Turret network camera



H.265+



- 4K HD;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H55FWD-IZ(S)

5MP Vari-focal EXIR Turret network camera



H.265+



- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H35FWD-IZ(S)

3MP Vari-focal EXIR Turret network camera



H.265+



- 3MP high resolution; H.265+/H.265/H.264+/H.2643 streams;
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H25FWD-IZ(S)

2MP Vari-focal EXIR Turret network camera



H.265+



- 2MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2955FWD-IZ(S)

5MP EXIR Fisheye network camera



H.265+



- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 1.05 mm @ F2.2, horizontal field of view: 180°, vertical field of view: 180°
- 120dB WDR
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2935FWD-IZ(S)

3MP EXIR Fisheye network camera



H.265+



- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion & line crossing & object removal & unattended baggage & face detection
- 1.16 mm @ F2.2, horizontal field of view: 180°, vertical field of view: 180°
- 120dB WDR
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

NETWORK CAMERA

EasyIP 2.0 NETWORK CAMERA

DS-2CD2022/42WD-I(W)(S)

2MP/4MP WDR IR Mini Bullet Network Camera



- 2MP/4MP real-time resolution
- Intrusion & line crossing detection
- 120dB WDR
- On-board storage(optional)
- Up to 30m IR range
- DC12V & PoE
- Metallic housing, IP67
- Hik-connect cloud mobile surveillance

DS-2CD2122/42WD-I(W)(S)

2MP/4MP WDR IR Fixed Dome Network Camera



- 2MP/4MP real-time resolution
- 120dB WDR
- 3-axis adjustment
- On-board storage(optional)
- Up to 30m IR range
- DC12V & PoE
- Vandal-proof metallic housing, IP67
- Cloud P2P mobile surveillance

DS-2CD2T22/42WD-I5(I8)

2MP/4MP WDR EXIR Bullet Network Camera



- 2MP/4MP real-time resolution
- 120dB WDR
- Up to 50m/80m IR range
- DC12V & PoE
- IP67
- Hik-connect cloud mobile surveillance

DS-2CD2322/42WD-I

2MP/4MP WDR EXIR Turret Network Camera



- 2MP/4MP real-time resolution
- 120dB WDR
- Up to 30m IR range
- DC12V & PoE
- Plastic housing, Vandal-proof, IP67
- Hik-connect cloud mobile surveillance

DS-2CD2422/42FWD-IW

2MP/4MP WDR IR Cube Network Camera



- 2MP/4MP real-time resolution
- On-board storage(optional)
- PIR detection
- Up to 10m IR range
- 120dB WDR
- DC12V & PoE
- Built-in Speaker, Mic, WIFI
- Hik-connect cloud mobile surveillance

DS-2CD2522/42FWD-I(W)(S)

2MP/4MP WDR Mini Dome Network Camera



- 2MP/4MP real-time resolution
- 120dB WDR
- 3-axis adjustment
- On-board storage
- Up to 10m IR range
- DC12V & PoE
- IK8 protection, IP67
- Hik-connect cloud mobile surveillance

DS-2CD2F22/42FWD-I(W)(S)

4MP WDR IR Mini PT Network Camera



- 2MP/4MP real-time resolution
- Intrusion & line crossing detection
- 120dB WDR
- Pan & tilt rotation, easy-to-adjust
- On-board storage
- Up to 10m IR range
- Built-in Wi-Fi (optional)
- Hik-connect cloud mobile surveillance

DS-2CD2942F-I(W)(S)

4MP 180° Panoramic Network Camera



- 4MP high resolution
- 180° horizontal panoramic view
- ePTZ control
- Compact design
- IR, WIFI, Audio & alarm optional

DS-2CD2622/42FWD-I(Z)(S)

2MP/4MP WDR Vari-focal IR Bullet Network Camera



- 2MP/4MP real-time resolution
- 2.8-12mm motorized(-Z) VF lens
- 120dB WDR
- On-board storage
- Up to 30m IR range
- DC12V & PoE
- Metallic housing, IP67
- Hik-connect cloud mobile surveillance

DS-2CD2722/42FWD-I(Z)(S)

2MP/4MP WDR Vari-focal IR Dome Network Camera



- 2MP/4MP real-time resolution
- 2.8-12mm motorized(-Z) VF lens
- 120dB WDR
- On-board storage
- Up to 30m IR range
- Metallic housing, IP67
- Hik-connect cloud mobile surveillance

4-LINE DarkFighter LITE NETWORK CAMERA

DS-2CD4B26FWD-IZ(S)

DarkFighter Lite Series 2MP Bullet Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Color:0.002Lux/F1.2, B/W:0.0002Lux/F1.2
- Full HD1080P
- 120dB WDR
- Up to 128GB on-board storage
- Up to 120m IR range
- IP67

DS-2CD4B16FWD-IZ(S)

DarkFighter Lite Series 1.3MP Bullet Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/3" progressive scan CMOS sensor
- Color:0.005Lux/F1.2, B/W:0.0005Lux/F1.2
- Full HD1080P
- 120dB WDR
- Up to 128GB on-board storage
- Up to 120m IR range
- IP67

DS-2CD4C36FWD-(AP)

DarkFighter series 3MP Box network camera

DARKFIGHTER



- H.265+/H.264+/H.265/H.264
- DarkFighter ultra-low light technology
- 1/2.8" progressive scan CMOS sensor
- 3MP high resolution
- 120dB WDR
- Intrusion & line crossing & object removal & unattended baggage & face detection&Region Entrance/Left&Scene Change
- Up to 128GB on-board storage

DS-2CD4C26FWD-(AP)

DarkFighter series 2MP Box network camera

DARKFIGHTER



- H.265+/H.264+/H.265/H.264
- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p
- 120dB WDR
- Intrusion & line crossing & object removal & unattended baggage & face detection&Region Entrance/Left&Scene Change
- Up to 128GB on-board storage

NETWORK CAMERA

DS-2CD4D26FWD-IZ(S)

DarkFighter Lite Series 2MP Dome Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Color:0.002Lux/F1.2, B/W:0.0002Lux/F1.2
- Full HD1080P
- 120dB WDR
- Up to 128GB on-board storage
- EXIR, prevent IR reflection
- IP66

DS-2CD4D16FWD-IZ(S)

DarkFighter Lite Series 1.3MP Dome Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/3" progressive scan CMOS sensor
- Color:0.005Lux/F1.2, B/W:0.0005Lux/F1.2
- Full HD1080P
- 120dB WDR
- Up to 128GB on-board storage
- EXIR, prevent IR reflection
- IP66

4-LINE SMART NETWORK CAMERA

DS-2CD4A24FWD-IZ(H)(S)

2MP 20X Zoom Bullet Network Camera



- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 4.7-94mm 20X optical zoom Smart Focus
- 120dB WDR
- Full smart feature-set
- Up to 128GB on-board storage
- Up to 120m IR range
- IP67

DS-2CD4026FWD(-AP)

DarkFighter Series 2MP Box Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Auto back focus
- P-Iris optional

DS-2CD4126FWD-IZ

DarkFighter Series 2MP Indoor Dome Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4A26FWD-IZ(H)(S)

DarkFighter Series 2MP Bullet Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD4526FWD-IZ(H)(M)

DarkFighter Series 2MP Dome Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 40m IR
- IP66
- HDMI interface optional

DS-2CD4626FWD-IZ(H)(S)

DarkFighter Series 2MP Bullet Network Camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 70m IR range
- IP66, IK10

DS-2CD4025FWD(-AP)

LightFighter Series 2MP Indoor Box Network Camera

LIGHTFIGHTER



- LightFighter 140dB triple exposure WDR
- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- Full smart feature-set
- Auto back focus
- P-Iris optional

DS-2CD4125FWD-IZ

LightFighter Series 2MP Indoor Dome Network Camera

LIGHTFIGHTER



- LightFighter 140dB triple exposure WDR
- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4A25FWD-IZ(H)(S)

LightFighter Series 2MP Bullet Network Camera

LIGHTFIGHTER



- LightFighter 140dB triple exposure WDR
- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD4526FWD-IZ(H)(M)

LightFighter Series 2MP Dome Network Camera

LIGHTFIGHTER



- LightFighter 140dB triple exposure WDR
- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 40m IR
- IP66

DS-2CD4626FWD-IZ(H)(S)

LightFighter Series 2MP Bullet Network Camera

LIGHTFIGHTER



- LightFighter 140dB triple exposure WDR
- 1/2.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 70m IR range
- IP66, IK10

DS-2CD4035FWD(-AP)

3MP Indoor Box Network Camera



- 1/2.8" progressive scan CMOS sensor
- 3MP@45fps resolution
- 120dB WDR
- Full smart feature-set
- Auto back focus
- P-Iris optional
- Up to 128GB on-board storage

DS-2CD4135FWD-IZ

3MP Indoor IR Dome Network Camera



- 1/2.8" progressive scan CMOS sensor
- 3MP@45fps resolution
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4A35FWD-IZ(H)(S)

3MP IR Bullet Network Camera



- 1/2.8" progressive scan CMOS sensor
- 3MP@45fps resolution
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

NETWORK CAMERA

DS-2CD4565F-IZ(H)
6MP IR Dome Network Camera



- 1/1.8" progressive scan CMOS sensor
- 6MP high resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 40m IR
- IP66

DS-2CD4665F-IZ(H)(S)
6MP IR Bullet Network Camera



- 1/1.8" progressive scan CMOS sensor
- 6MP high resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 70m IR range
- IP66, IK10

DS-2CD4065F(-AP)
6MP Indoor Box Network Camera



- 1/1.8" progressive scan CMOS sensor
- 6MP high resolution
- Full smart feature-set
- Auto back focus
- P-Iris optional
- Up to 128GB on-board storage

DS-2CD4165FWD-IZ
6MP Indoor IR Dome Network Camera



- 1/1.8" progressive scan CMOS sensor
- 6MP high resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4A65F-IZ(H)(S)
6MP IR Bullet Network Camera



- 1/1.8" progressive scan CMOS sensor
- 6MP high resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD4085F(-AP)
8MP Indoor Box Network Camera



- 1/1.7" progressive scan CMOS sensor
- 4K(4096 × 2160) ultra-HD resolution
- Full smart feature-set
- Auto back focus
- P-Iris optional
- Up to 128GB on-board storage

DS-2CD4185FWD-IZ
6MP Indoor IR Dome Network Camera



- 1/1.7" progressive scan CMOS sensor
- 4K(4096 × 2160) ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4A85F-IZ(H)(S)
8MP IR Bullet Network Camera



- 1/1.7" progressive scan CMOS sensor
- 4K(4096 × 2160) ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD4585F-IZ(H)
8MP IR Dome Network Camera



- 1/1.7" progressive scan CMOS sensor
- 4K(4096 × 2160) ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 40m IR
- IP66

DS-2CD4685F-IZ(H)(S)
8MP IR Bullet Network Camera



- 1/1.7" progressive scan CMOS sensor
- 4K(4096 × 2160) ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 70m IR range
- IP66, IK10

DS-2CD40C5F(-AP)
12MP Indoor Box Network Camera



- 1/1.7" progressive scan CMOS sensor
- Up to 12MP ultra-HD resolution
- Full smart feature-set
- Auto back focus
- P-Iris optional
- Up to 128GB on-board storage

DS-2CD41C5F-IZ
12MP Indoor IR Dome Network Camera



- 1/1.7" progressive scan CMOS sensor
- Up to 12MP ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 30m IR range

DS-2CD4AC5F-IZ(H)(S)
12MP IR Bullet Network Camera



- 1/1.7" progressive scan CMOS sensor
- Up to 12MP ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD45C5F-IZ(H)
12MP IR Dome Network Camera



- 1/1.7" progressive scan CMOS sensor
- Up to 12MP ultra-HD resolution
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 40m IR
- IP66

6-LINE NETWORK CAMERA

DS-2CD63C2F-I(V)(S)
12MP Panoramic IR Network Camera



- 360° panoramic view
- Up to 4000x3072@20fps resolution
- Up to 1600x1200 ePTZ control
- Heat mapping analytic
- Support on-board hardware de-warping
- Support software de-warping
- IP66 & Vandal-proof (-V)
- Up to 15m IR

DS-2CD6362F-I(V)(S)
6MP Panoramic IR Network Camera



- 360° panoramic view
- Up to 3072x2048 resolution
- ePTZ control
- 120dB WDR
- Support on-board hardware de-warping
- Support software de-warping
- IP66 & Vandal-proof (-V)
- Up to 15m IR

NETWORK CAMERA

DS-2CD6332F-I(V)(S)

3MP Panoramic IR Network Camera



- 360° panoramic view
- Up to 2048x1536 resolution
- ePTZ control
- 120dB WDR
- Support on-board hardware de-warping
- Support software de-warping
- IP66 & Vandal-proof (-V)
- Up to 15m IR

DS-2CD6426FWD-50

DarkFighter Series 2MP Mini Bullet Covert Network Camera



- Ultra-low illumination technology
- 1/1.8" progressive CMOS sensor
- 2MP real-time resolution
- 120dB WDR
- Full Smart Feature-set
- Up to 128GB on-board storage
- Mini bullet part support IP66

DS-2CD6424FWD-10/20/30

2MP Covert Network Camera



- 2MP real-time resolution
- 120dB WDR
- Up to 128GB on-board storage
- Pinhole lens (-10/20)
- Fixed tube lens (-30)

DS-2CD6424FWD-40/E1(E2)

2MP Covert Network Camera



- 2MP real-time resolution
- 120dB WDR
- Up to 128GB on-board storage
- Mini ball lens (-40/E1)
- Embedded lens (-40/E2)

MOBILE NETWORK CAMERA

DS-2XM6122FWD-I(M)

2MP Vehicle Mini Dome network camera



- Special design for vehicle-mounted
- 2MP realtime resolution
- 3-axis adjustment
- M12 ethernet interface(optional)
- 120dB WDR
- IP66, IK8
- EN50155, EN50121 certification
- Build-in microphone
- Multiple smart events supported

DS-2CD6520ET-I(O)

2MP Outer-vehicle Mini Dome Network Camera



- Special design for vehicle-mounted
- 2MP real time resolution
- 3-axis adjustment
- M12 ethernet interface(optional)
- Up to 30m IR range
- IP68, IK10
- EN50155, EN50121 certification

DS-2CD6510-I(O)

1.3MP Outer-vehicle Mini Dome Network Camera



- Special design for vehicle-mounted
- 1.3MP real time resolution
- 3-axis adjustment
- M12 ethernet interface(optional)
- Up to 30m IR range
- IP68, IK10
- EN50155, EN50121 certification

DS-2CD6520DT-I(O)

2MP Inner-vehicle Mini Dome Network Camera



- Special design for vehicle-mounted
- 2MP realtime resolution
- 3-axis adjustment
- M12 ethernet interface(optional)
- IP54, IK8
- EN50155, EN50121 certification

DS-2CD6510DT-I(O)

1.3MP Inner-vehicle Mini Dome Network Camera



- Special design for vehicle-mounted
- 1.3MP real time resolution
- 3-axis adjustment
- M12 ethernet interface(optional)
- IP54, IK8
- EN50155, EN50121 certification

DS-2XM6612FWD-I (1.3MP)

DS-2XM6622FWD-I (2.0MP)
Mobile Network Camera



- HD720p or Full HD1080p video
- 120dB WDR
- Smart IR, up to 3m IR range
- Up to 128GB on-board storage
- Built-in Microphone

Explosion-Proof & Anti-Corrsion NETWORK CAMERA

DS-2XE6222F-IS

2MP Explosion-Proof Dome network camera



- H.265+/H.264+/H.265/H.264
- 2MP realtime resolution
- 120dB WDR
- ATEX, IECEx, IP68
- 316L Anti-Corrosion Standard: WF-2, NEMA 4X, C5-M
- Support on-board storage, up to 128GB
- AC 100V to 240V/PoE

DS-2XE6242F-IS

4MP Explosion-Proof Bullet network camera



- H.265+/H.264+/H.265/H.264
- 4MP high resolution
- 120dB WDR
- 316L Anti-Corrosion Standard: WF-2, NEMA 4X, C5-M
- Support on-board storage, up to 128GB
- AC 100V to 240V/PoE

DS-2DF6223-CX(W)

DarkFighter series 2MP Anti-corrsion PTZ network camera



- 2MP 1/1.8" progressive scan CMOS
- 23x optical zoom
- 120dB WDR
- Explosion-Proof: II 2 G Ex d IIC T6 Gb, Ta -40°
- C to +60°C; II 2 D Ex tb IIIC T80° C Db
- IP68 standard

DS-2CD6626DS-IZ(HJS)


DarkFighter Series 2MP Anti-corrsion Dome Network Camera



- Ultra-low illumination technology
- 316L stainless steel housing
- 1/1.8" progressive scan CMOS sensor
- 2.8-12mm motorized VF lens
- 120dB WDR
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification

DS-2CD6626BS-R

DarkFighter Series 2MP Anti-corrsion Bullet Network Camera



- Ultra-low illumination technology
- 316L stainless steel housing
- 1/1.8" progressive scan CMOS sensor
- 120dB WDR
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification

DS-2CD6626B/E-HIR5/IRA

DarkFighter Series 2MP Anti-corrsion IR Bullet Network Camera



- Ultra-low illumination technology
- 316L stainless steel housing
- 1/1.8" progressive scan CMOS sensor
- 120dB WDR
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification
- IR5: 3.8-16mm VF lens, up to 50m IR range
- IRA: 11-40mm VF lens, up to 100 IR range

NETWORK CAMERA

DS-2CD6626B-IZHS

DarkFighter series 2MP Anti-corrosion IR Bullet network camera

DARKFIGHTER



- DarkFighter ultra-low light technology
- 316L stainless steel housing
- 1/1.8" progressive scan CMOS sensor
- 120dB WDR
- Motorized lens with Smart Focus
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification

DS-2CD6652B-IZHS

DarkFighter series 2MP Anti-corrosion IR Bullet network camera

DARKFIGHTER



- 5MP 2592 × 1944@60 fps
- 316L stainless steel housing
- 120dB WDR
- Motorized lens with Smart Focus
- Full Smart Feature-set
- ISO C5-M, NEMA 4X certification

DS-2XC6122FWD-IS

DarkFighter series 2MP Anti-corrosion Dome network camera

DARKFIGHTER



- H.265+/H.264+/H.265/H.264
- 2MP realtime resolution
- 120dB WDR
- Anti-Corrosion Standard: WF-2, NEMA 4X, C5-M
- IP67
- Support on-board storage, up to 128GB

DS-2XC6142FWD-IS

DarkFighter series 2MP Anti-corrosion Dome network camera

DARKFIGHTER



- H.265+/H.264+/H.265/H.264
- 4MP realtime resolution
- 120dB WDR
- Anti-Corrosion Standard: WF-2, NEMA 4X, C5-M
- IP67
- Support on-board storage, up to 128GB

ANPR NETWORK CAMERA

DS-2CD4026FWD/P-IR5 (3.8-16mm) /IRA(11-40mm)

2MP Low Light Smart Box LPR Camera with housing



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Up to 128GB on-board storage
- Up to 50m/100m IR range

DS-2CD4026FWD/P-(H)(N)IRA (11-40mm)

2MP Low Light Smart Box LPR Camera with housing



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Up to 128GB on-board storage
- Up to 30m light range

DS-2CD4026FWD/P-L (3.8-16mm)(11-40mm)(7-33mm)

2MP Low Light Smart Box LPR Camera with housing



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Up to 128GB on-board storage
- Up to 30m light range

DS-2CD4A26FWD-IZ(S)(H)/P (2.8-12mm)/(8-32mm)(-WG)

2MP Low Light Smart Bullet LPR Camera



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range
- IP67

DS-2CD4A26FWD-LZS/P (2.8-12mm)

2MP Low Light Smart Bullet LPR Camera



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- Up to 50m IR range

DS-2CD4626FWD-IZ(HS)/P (2.8-12mm)

2MP Low Light Smart Bullet LPR Camera



- DarkFighter ultra-low light technology
- License Plate Recognition
- 1/1.8" progressive scan CMOS sensor
- Full HD1080p, up to 60fps
- 120dB WDR
- Full smart feature-set
- Motorized lens with Smart Focus
- Up to 128GB on-board storage
- IP67, IK10

THERMAL CAMERA

DS-2TD2136-10/15/25 DS-2TD2136T-10/15/25

Thermal Network single-lens
Bullet Camera



- Thermal: 384×288
- 10mm (36°)/ 15mm (24°)/25mm (15°) thermal lens optional
- Support line crossing and intrusion detection
- Support temperature exception alarm
- Support fire detection
- -T: -20 C ~ 550 C (-4°F to 1,022°F) temperature measuring range, Max(±2 C , ±2%) temperature accuracy(only DS-2TD2136T support)
- IP66

DS-2TD2166-15/25/35 DS-2TD2166T-15/25/35

Thermal Network single-lens
Bullet Camera



- Thermal: 640×512
- 15mm (39°)/ 25mm (24°)/35mm (17°) thermal lens optional
- Support line crossing and intrusion detection
- Support temperature exception alarm
- Support fire detection
- -T: -20 C ~ 550 C (-4°F to 1,022°F) temperature measuring range, Max(±2 C , ±2%) temperature accuracy(only DS-2TD2166T support)
- IP66

DS-2TD2336-50/75/100

Thermal Network single-lens
Bullet Camera



- Thermal: 384×288
- 50mm (7.47°)/ 75mm (4.98°)/100mm (3.73°) thermal lens optional
- Support line crossing and intrusion detection
- Support temperature exception alarm
- Support fire detection
- IP66

DS-2TD2366-50/75/100

Thermal Network single-lens
Bullet Camera



- Thermal: 640×512
- 50mm (12.4°)/ 75mm (8.3°)/100mm (6.2°) thermal lens optional
- Support line crossing and intrusion detection
- Support temperature exception alarm
- Support fire detection
- IP66

DS-2TD6135-50/75B2L DS-2TD6166-50/75B2L

Observable Thermal + Optical
Bi-spectrum Network PTZ
Camera



- Thermal: 384×288/640×512, Visible: 1920×1080
- Visible: 8-250mm lens, 32x optical zoom, 16x digital zoom
- Thermal: 50mm (6135: 11°, 6166: 12.4°)/ 75mm (6135: 7.3°, 6166: 8.3°) thermal lens optional
- 360°endless pan range, +40°~90° tilt range
- Support line crossing and intrusion detection with smart tracking linkage
- Support temperature exception alarm
- Support fire detection
- up to 500m IR
- IP66

DS-2TD6135T-25/50A2L DS-2TD6166T-25/50A2L

Thermometric Thermal +
Optical Bi-spectrum Network
PTZ Camera



- Thermal: 384×288/640×512, Visible: 1920×1080
- Visible: 4.5-135mm lens, 30x optical zoom, 16x digital zoom
- Thermal: 25mm (6135: 21°, 6166: 24°)/ 50mm (6135: 11°, 6166: 12.4°) thermal lens optional
- 360°endless pan range, +40°~90° tilt range
- -20 C ~ 550 C (-4°F to 1,022°F) temperature Range, Max(±2 C , ±2%) temperature accuracy
- Support line crossing and intrusion detection with smart tracking linkage
- Support fire detection
- up to 150m IR
- IP66

DS-2TD8135 series DS-2TD8166 series

Observable Thermal + Optical
Bi-spectrum Network PTZ
Camera



- Thermal: 384×288/640×512, Visible: 1920×1080
- Thermal lens: 75mm / 100mm /150mm optional
- Visible lens:10-320mm / 6.7-330mm / 12.5-750mm optional
- 360°endless pan range, +45°~45° tilt range
- 0.01°/s to 12°/s pan speed, 0.01°/s to 8°/s tilt speed
- Support line crossing and intrusion detection with smart tracking linkage
- Support temperature exception alarm
- Support fire detection
- up to 3000m laser
- IP66

DS-2TD4035D-25/50

Thermal + Optical Bi-spectrum
Network Speed Dome



- Thermal: 384×288, Visible: 1920×1080
- Visible: 4.3-129mm lens, 30x optical zoom, 16x digital zoom
- Thermal: 25mm (21.7°)/ 50mm (11°) thermal lens optional
- 360°endless pan range, -15°~ 90° tilt range
- Support line crossing and intrusion, which can be linked to auto tracking
- Support temperature exception alarm
- Support fire detection
- up to 150m IR
- IP66

DS-2TD2235D-25/50

Thermal + Optical Bi-spectrum
Network Bullet
Camera



- Thermal: 384×288, Visible: 1920×1080
- Visible: DarkFighter Ultra low light
- Thermal: 25mm (21.7°)/ 50mm (11°) thermal lens optional
- Support line crossing and intrusion
- Support temperature exception alarm
- Support fire detection
- up to 120m IR
- IP66

DS-2TP03-15VM/W

Handheld Thermometric
Thermal Camera



- Thermal: 384×288 17μm, Visible: 8MP
- 15mm (25°)thermal lens, 7.5mm/30mm/50mm lens optional
- 3.6" 320 x 240 touch screen
- -20 C ~ 650 C (-4°F to 1202°F) temperature measuring range
- Max(±2 C , ±2%) temperature accuracy
- Optical detail on thermal image,
- 64G Micro SD/SDHC/SDXC Card
- >4 hours operating time, battery capacity display
- IP66

DS-2TS03-25UM/W DS-2TS03-35UM/W

Handheld Observational
Thermal Camera



- Thermal: 384×288 17μm
- 25mm (15°) or 35mm(10°)thermal lens optional
- 0.39" OLED, 1024×768
- 64G Micro SD/SDHC/SDXC Card
- Laser positioning, Smart ranging.
- Hot spot tracking
- Support Wi-Fi
- Support Hik-Connect
- >5 hours operating time, battery capacity display
- IP67
- 2m fall down protection

TURBO HD ANALOG CAMERA

TURBO HD 3MP WDR EXIR CAMERA

DS-2CE16F7T-IT
Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56F7T-ITM
Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56F7T-VPIT
Outdoor Vandalproof EXIR Dome



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE16F7T-IT1/3/5
Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 20/40/80m IR distance
- IP66 weatherproof

DS-2CE56F7T-IT1/3
Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 20/40m IR distance
- IP66 weatherproof

DS-2CE16F7T-IT3Z
Outdoor EXIR Motorized Vari-focal Bullet



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance & IP66 weatherproof

DS-2CE16F7T-AIT3Z
Outdoor EXIR Motorized Vari-focal Bullet



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance & IP66 weatherproof
- Dual voltage: 12 VDC / 24 VAC

DS-2CE56F7T-IT3Z
Outdoor EXIR Motorized Vari-focal Eyeball



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66 weatherproof

DS-2CE56F7T-ITZ
Indoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance

DS-2CE56F7T-AITZ
Indoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance
- Dual voltage: 12 VDC / 24 VAC

DS-2CE56F7T-VPIT3Z
Outdoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66 weatherproof

DS-2CE56F7T-AVPIT3Z
Outdoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66 weatherproof
- Dual voltage: 12 VDC / 24 VAC

TURBO HD 3MP EXIR CAMERA

DS-2CE16F1T-IT
Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True Day/Night & Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56F1T-ITM
Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True Day/Night & Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE16F1T-IT1/3/5
Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True Day/Night & Smart IR
- Advanced EXIR technology
- 20/40/80m IR distance
- IP66 weatherproof

DS-2CE56F1T-IT1/3
Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True Day/Night & Smart IR
- Advanced EXIR technology
- 20/40m IR distance
- IP66 weatherproof

TURBO HD ANALOG CAMERA

TURBO HD 5MP EXIR CAMERA

DS-2CE16H1T-IT
Outdoor EXIR Bullet



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56H1T-ITM
Outdoor EXIR Eyeball



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE16H1T-IT1/3/5
Outdoor EXIR Bullet



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- Up to 20/40/80m IR distance
- IP66 weatherproof

DS-2CE56H1T-IT1/3
Outdoor EXIR Eyeball



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- Up to 20/40m IR distance
- IP66 weatherproof

DS-2CE16H1T-(A)IT3Z
Outdoor EXIR Motorized Vari-focal Bullet



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance & IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56H1T-IT3Z
Outdoor EXIR Motorized Vari-focal Eyeball



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66 weatherproof

DS-2CE56H1T-(A)ITZ
Indoor EXIR Motorized Vari-focal Dome



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56H1T-(A)VPIT3Z
Outdoor EXIR Motorized Vari-focal Dome



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- True Day/Night, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CC12D9T-IT3
HD1080P Starlight+ POC Bullet



- Built-in POC(Power over Coax)
- True Day/Night,
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 40m IR distance
- IP66 weatherproof

DS-2CC52D9T-IT3
HD1080P Starlight+ POC Eyeball



- Built-in POC(Power over Coax)
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 40m IR distance
- IP66 weatherproof

DS-2CC12D9T-AIT3ZE
HD1080P Starlight+ POC Vari-focal Bullet



- Built-in POC(Power over Coax)
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized auto focus Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC

DS-2CC52D9T-AVPIT3ZE
HD1080P Starlight+ POC Vari-focal Dome



- Built-in POC(Power over Coax)
- True Day/Night, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized auto focus Lens
- 40m IR distance
- Vandal proof & IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC

TURBO HD HD1080P WDR EXIR CAMERA

DS-2CC52D9T-AITZE
HD1080P Starlight+ POC Vari-focal Dome



- Built-in POC(Power over Coax)
- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized auto focus Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC

DS-2CE16D7T-IT
Outdoor EXIR Bullet



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56D7T-ITM
Outdoor EXIR Eyeball



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56D7T-VPIT
Outdoor Vandalproof EXIR Dome



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66 weatherproof

TURBO HD ANALOG CAMERA

DS-2CE16D7T-IT1/3/5
Outdoor EXIR Bullet



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 20/40/80m IR distance
- IP66 weatherproof

DS-2CE56D7T-IT1/3
Outdoor EXIR Eyeball



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 20/40m IR distance
- IP66 weatherproof

DS-2CE16D7T-(A)IT3Z
Outdoor EXIR Motorized Vari-focal Bullet



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56D7T-IT3Z
Outdoor EXIR Motorized Vari-focal Eyeball



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66 weatherproof

TURBO HD1080P CAMERA

DS-2CE56D7T-(A)ITZ
Indoor EXIR Motorized Vari-focal Dome



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56D7T-(A)VPIT3Z
Outdoor EXIR Motorized Vari-focal Dome



- True Day/Night
- True WDR, Smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56D0T-IRMM
Indoor IR Dome



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE56D0T-IRP
Indoor IR Eyeball



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE16D0T-IR(P)
Outdoor IR Bullet



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE56D0T-IR
Outdoor IR Eyeball



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE56D0T-IRM
Outdoor IR Eyeball



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE16D0T-IT1/3/5
Outdoor EXIR Bullet



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20/40/80m IR distance with EXIR
- IP66 weatherproof

DS-2CE56D0T-IT1/3
Outdoor EXIR Eyeball



- 3-axis adjustment
- True Day/Night
- DNR, Smart IR
- Up to 20/40m IR distance with EXIR
- IP66 weatherproof

DS-2CE56D1T-IRMM
HD1080P Indoor IR Dome



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC
- 3-axis adjustment

DS-2CE56D1T-VPIR
HD1080P Vandal-proof IR Dome



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC
- Vandal proof

DS-2CE16D1T-IR
HD1080P IR Bullet Camera



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC
- IP66 weatherproof

TURBO HD ANALOG CAMERA

DS-2CE56D1T-IRP
HD1080P Indoor IR Turret



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC

DS-2CE56D1T-IR
HD1080P Outdoor IR Turret



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC
- IP66 weatherproof

DS-2CE56D1T-IRM
HD1080P Outdoor IR Turret



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC
- IP66 weatherproof

DS-2CE16D1T-IT1/3/5
HD1080P EXIR Bullet Camera



- True day/night
- DNR, smart IR
- 20/40/80m IR distance
- OSD menu controlled via UTC
- IP66 weatherproof

DS-2CE56D1T-IT1/3
HD1080P EXIR Turret Camera



- True day/night
- DNR, smart IR
- 20/40m IR distance
- OSD menu controlled via UTC
- IP66 weatherproof

DS-2CE56D1T-AVFIR
HD1080P Indoor Vari-focal IR Dome



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 30m IR distance
- OSD menu controlled via UTC
- Dual voltage: 12 VDC / 24 VAC

DS-2CE56D1T-VFIR
HD1080P Indoor Vari-focal IR Dome



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 30m IR distance
- OSD menu controlled via UTC

DS-2CE56D1T-VP3IR3
HD1080P Outdoor Vandal-proof IR Dome



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 40m IR distance
- OSD menu controlled via UTC
- Vandal proof, IP66

DS-2CE56D1T-AV3IR3
HD1080P Outdoor Vandal-proof IR Dome



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 40m IR distance
- OSD menu controlled via UTC
- Vandal proof, IP66
- Dual voltage: 12 VDC / 24 VAC

DS-2CE56D1T-VF3IR3
HD1080P Outdoor Vari-focal IR Turret



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 40m IR distance
- OSD menu controlled via UTC
- IP66 weatherproof

DS-2CE16D1T-VF3IR3
HD1080P Outdoor Vari-focal IR Bullet



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 40m IR distance
- OSD menu controlled via UTC
- IP66 weatherproof

DS-2CE16D1T-AV3IR3
HD1080P Outdoor Vari-focal IR Bullet



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 40m IR distance
- OSD menu controlled via UTC
- IP66 weatherproof
- Dual voltage: 12 VDC / 24 VAC

DS-2CC12D9T(-A)
HD1080P Box Camera



- True day/night
- 3D DNR, smart IR
- True WDR, up to 120dB
- OSD menu controlled via UTC
- Alarm input & output (DS-2CC12D9T-A)
- Dual voltage: 12 VDC / 24 VAC

DS-2CE16D9T-AIRAZH
HD1080P Outdoor Vari-focal Bullet Camera



- Turbo HD output, up to 1080P resolution
- 5 - 50mm motorized vari-focal lens
- True Day/Night
- Auto Focus, EXIR Technology
- OSD menu, 3D DNR, Smart IR
- True WDR, up to 120dB
- Up to 120m IR distance
- Built-in heater, IP66 weatherproof
- UTC function, 24V AC/ 12V DC

DS-2CE16D5T-IR
HD1080P Bullet Camera



- HD1080P video output
- Adopt HDTVI Technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 20m IR distance
- IP66 weatherproof
- True wide dynamic range
- Up the coax(via coaxial cable)

DS-2CE56D5T-IRM
HD1080P Turret Camera



- HD1080P Video Output
- Adopt HDTVI Technology
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- 20m IR distance
- IP66 weatherproof
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)

TURBO HD ANALOG CAMERA

DS-2CE56D5T-IR

HD1080P Turret Camera



- HD1080P Video Output
- Adopt HDTVI Technology
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- 20m IR distance
- IP66 weatherproof
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)

DS-2CE16D5T-IT1

HD1080P EXIR Bullet Camera



- HD1080P Video Output
- Supports HDTVI Technology
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- 20m IR distance
- IP66 weatherproof
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)

DS-2CE16D5T-IT3

HD1080P EXIR Bullet Camera



- HD1080P Video Output
- Supports HDTVI Technology
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- 40m IR distance
- IP66 weatherproof
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)

DS-2CE16D5T-IT5

HD1080P EXIR Bullet Camera



- HD1080P Video Output
- Supports HDTVI Technology
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- 80m IR distance
- IP66 weatherproof
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)

DS-2CE56D5T-IT1

HD1080P EXIR Turret Camera



- HD1080P Video Output
- Supports HDTVI Technology
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- 20m IR distance
- IP66 weatherproof
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)

DS-2CE56D5T-IT3

HD1080P EXIR Turret Camera



- HD1080P Video Output
- Supports HDTVI Technology
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- 40m IR distance
- IP66 weatherproof
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)

DS-2CE56D5T-VP1R3

HD1080P Outdoor Vandal Proof Camera



- HD1080P Video Output
- Supports HDTVI Technology
- True Day/Night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, Smart IR
- Up to 40m IR distance
- IP66 weatherproof & Vandal Proof
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)

DS-2CE56D5T-AV1R3

HD1080P Outdoor Vandal Proof Camera



- HD1080P Video Output
- Supports HDTVI Technology
- True Day/Night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, Smart IR
- Up to 40m IR distance
- IP66 weatherproof & Vandal Proof
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)
- Dual Voltage(12 VDC/24 VAC)

DS-2CE56D5T-VF1R

HD1080P Indoor Vari-focal IR Camera



- HD1080P Video Output
- Supports HDTVI Technology
- True Day/Night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, Smart IR
- Up to 30m IR distance
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)

DS-2CE56D5T-AV1F1R

HD1080P Indoor Vari-focal IR Camera



- HD1080P Video Output
- Supports HDTVI Technology
- True Day/Night
- 2 - 12mm Motorized vari-focal lens
- OSD menu, 3D DNR, Smart IR
- Up to 30m IR distance
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)
- Dual Voltage(12 VDC/24 VAC)

DS-2CE56D5T-VF1T3

HD1080P Outdoor Vari-focal EXIR Turret Camera



- HD1080P Video Output
- Supports HDTVI Technology
- True Day/Night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, Smart IR
- Up to 50m IR distance
- IP66 weatherproof
- True Wide Dynamic Range
- Up the Coax(via coaxial cable)

DS-2CE16D5T-VF1T3

HD1080P Outdoor Vari-focal EXIR Bullet Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 50m IR distance
- IP66 weatherproof
- True wide dynamic range
- Up the coax(via coaxial cable)

DS-2CE16D5T-AV1F1T3

HD1080P Outdoor Vari-focal EXIR Bullet Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 50m IR distance & IP66 weatherproof
- True wide dynamic range
- Up the coax(via coaxial cable)
- Dual voltage(12 VDC/24 VAC)

DS-2CE16D1T-(A)1R3Z

Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True Day/Night
- DNR, Smart IR
- OSD menu controlled via UTC
- 2.8 - 12mm Motorized vari-focal lens
- Up to 40m IR distance
- IP66 weatherproof
- Dual voltage: 12 VDC/ 24 VAC

DS-2CE56D1T-1R3Z

Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True Day/Night
- DNR, Smart IR
- OSD menu controlled via UTC
- 2.8 - 12mm Motorized vari-focal lens
- Up to 40m IR distance
- IP66 weatherproof

DS-2CE56D1T-(A)1RZ

Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True Day/Night
- DNR, Smart IR
- OSD menu controlled via UTC
- 2.8 - 12mm Motorized vari-focal lens
- Up to 40m IR distance
- IP66 weatherproof

TURBO HD ANALOG CAMERA

DS-2CE56D1T-(A)VPIR3Z Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True Day/Night
- DNR, Smart IR
- OSD menu controlled via UTC
- 2.8 - 12mm Motorized vari-focal lens
- Up to 40m IR distance
- IP66 weatherproof & Vandal Proof
- Dual voltage: 12 VDC / 24 VAC

DS-2CE16D5T-AIR3ZH Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- OSD menu
- 2.8 - 12mm Motorized vari-focal lens
- Up to 40m IR distance
- IP66 weatherproof
- Built-in Heater

DS-2CE56D5T-IR3Z Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- OSD menu
- 2.8 - 12mm Motorized vari-focal lens
- Up to 40m IR distance
- IP66 weatherproof

DS-2CE56D5T-AIRZ Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- OSD menu
- 2 - 12mm Motorized vari-focal lens
- Up to 30m IR distance

TURBO HD720P LOW LIGHT

DS-2CE56D5T-AVPIR3Z(H) Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True Day/Night
- True WDR, 3D DNR, Smart IR
- OSD menu
- 2.8 - 12mm Motorized vari-focal lens
- Up to 40m IR distance
- IP66 weatherproof & Vandal Proof
- Built-in Heater (DS-2CE56D5T-AVPIR3ZH)

DS-2CE16C5T-IT1/3 HD720P EXIR Low Light Bullet Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 40m IR distance
- IP66 weatherproof
- Low illumination
- Up the coax(via coaxial cable)

DS-2CE16C5T-IT5 HD720P EXIR Low Light Bullet Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 80m IR distance
- IP66 weatherproof
- Low illumination
- Up the Coax(via coaxial cable)

DS-2CE56C5T-IT1 HD720P EXIR Low Light Turret Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 20m IR distance
- IP66 weatherproof
- Low illumination
- Up the coax(via coaxial cable)

DS-2CE56C5T-IT3 HD720P EXIR Low Light Turret Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 40m IR distance
- IP66 weatherproof
- Low illumination
- Up the coax(via coaxial cable)

DS-2CE56C5T-VPIR3 HD720P Outdoor Vandal-proof Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- 8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 40m IR distance
- IP66 weatherproof & vandal proof
- Low illumination
- Up the coax(via coaxial cable)

DS-2CE56C5T-AVPIR3 HD720P Outdoor Vandal-proof Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- 8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 40m IR distance
- IP66 weatherproof & vandal proof
- Low illumination, up the coax(via coaxial cable)
- Dual voltage(12 VDC/24 VAC)

DS-2CE56C5T-VFIR HD720P Indoor Vari-focal IR Dome Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 30m IR distance
- Low illumination
- Up the coax(via coaxial cable)

DS-2CE56C5T-AVFIR HD720P Indoor Vari-focal IR Dome Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 30m IR distance
- Low illumination, up the coax(via coaxial cable)
- Dual voltage(12 VDC/24 VAC)

DS-2CE56C5T-VFIT3 HD720P Outdoor Vari-focal EXIR Turret Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 50m IR distance
- Low illumination
- Up the coax(via coaxial cable)

DS-2CE16C5T-VFIR3 HD720P Outdoor Vari-focal IR Bullet Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 40m IR distance
- Low illumination
- Up the coax(via coaxial cable)

DS-2CE16C5T-AVFIR3 HD720P Outdoor Vari-focal IR Bullet Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- 2.8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 40m IR distance
- Low illumination, Up the Coax(via coaxial cable)
- Dual voltage(12 VDC/24 VAC)

TURBO HD ANALOG CAMERA

TURBO HD720P

DS-2CE16C2T-IR

HD720P Bullet Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- DNR, smart IR
- 20m IR distance
- IP66 weatherproof

DS-2CE16C2T-IRP

HD720P Bullet Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- DNR, smart IR
- 20m IR distance
- IP66 weatherproof

DS-2CE56C2T-IRM

HD720P Turret Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- DNR, smart IR
- 20m IR distance
- IP66 weatherproof

DS-2CE56C2T-IR

HD720P Turret Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- DNR, smart IR
- 20m IR distance
- IP66 weatherproof

DS-2CE16C2T-IT1/3

HD720P EXIR Bullet Camera



- HD720P video output
- Supports HDTVI technology
- True day/night, smart IR
- 20/40m IR distance
- IP66 weatherproof

DS-2CE16C2T-IT5

HD720P EXIR Bullet Camera



- HD720P video output
- Supports HDTVI technology
- True day/night, smart IR
- 80m IR distance
- IP66 weatherproof

DS-2CE56C2T-IT1/3

HD720P EXIR Turret Camera



- HD720P video output
- Supports HDTVI technology
- True day/night, smart IR
- 20/40m IR distance
- IP66 weatherproof

DS-2CE56C0T-IRMM

Indoor IR Dome



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE56C0T-IRP

Indoor IR Eyeball



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance

DS-2CE16C0T-IR(P)

Outdoor IR Bullet



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE56C0T-IR(M)

Outdoor IR Eyeball



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20m IR distance
- IP66 weatherproof

DS-2CE16C0T-IT1/3/5

Outdoor EXIR Bullet



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20/40/80m IR distance with EXIR
- IP66 weatherproof

DS-2CE56C0T-IT1/3

Outdoor EXIR Eyeball



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True Day/Night
- DNR, Smart IR
- Up to 20/40m IR distance with EXIR
- IP66 weatherproof

NVR

NVR

DS-96128/256NI-I16 DS-96128/256NI-I24

Embedded H.265+ 4K Super NVR



- 576/768Mbps Bit Rate input Max(up to 128/256 IP cameras Input)
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264+/H.264 video formats
- 20-ch 1080P decoding capability
- HDMI output at up to 4K resolution
- Up to 16/24 SATA interfaces, up to 8 TB for each HDD, 4 Gigabit optical interfaces
- Redundant power supply to ensure system stability
- HDD hot swapping with RAID 0/1/5/6/10
- One LCD screen optional , mini SAS optional

DS-7700NI-H4/8P DS-7700NI-H4/16P

X86 open platform for software developers and integrators, PoE port



- Intel Celeron Processor(2M Cache, 2.00GHz)
- 300 Mbps Bit Rate input Max
- HDMI output resolution at up to 4MP, VGA output resolution at up to 2MP
- 4 hot-swappable SATA
- 4GB memory
- 2 USB 2.0 & 1 USB 3.0
- Alarm in/out : 16/4
- 1 RJ-45 10/100/1000 Mbps self-adaptive interface
- 8P/16P models support 8/16 independent 100M PoE network interfaces

DS-9664NI-I16 DS-9632NI-I16 DS-9616NI-I16

Embedded H.265+ 4K 3U NVR



- 256/320 Mbps Bit Rate Input Max(up to 16/32/64-ch IP cameras input)
- Third-party network cameras supported
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264+/MPEG4 video formats
- 2-ch HDMI and 2-ch VGA outputs interfaces provided, HDMI1 output at up to 4K resolution
- 16 SATA, HDD hot swapping , 1 eSATA, 2 USB2.0, 1 USB3.0
- Support RAID0,1,5,6,10
- *Hot spare working mode

DS-7608NI-I2(/8P) DS-7616NI-I2(/16P)

Embedded H.265+ 4K 1U PoE NVR



- 160/256 Mbps Bit Rate Input Max(up to 8/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264+/H.264/MPEG4 video formats
- HDMI output resolution at up to 4K
- 2 SATA, 1 x USB 2.0, 1 x USB 3.0
- 8P/16P series support 8/16 independent PoE network Interfaces
- 4-ch 4K decoding or 16-ch 1080P decoding

DS-96128/256NI-I16/H DS-96128/256NI-/24/H

Embedded H.265+S 4K Super NVR



- 768MbpsBit Rate input Max(up to 128/256 IP cameras Input)
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264+/H.264 video formats
- 64-ch 1080P decoding capability
- HDMI output at up to 4K resolution,
- Up to 16/24 SATA interfaces , up to 8 TB for each HDD, Gigabit optical interfaces
- Redundant power supply to ensure system stability
- HDD hot swapping with RAID 0/1/5/6/10
- One LCD screen optional , mini SAS optional

DS-7600NI-H2/4P DS-7600NI-H2/8P

X86 open platform for software developers and integrators, PoE port



- Intel Celeron Processor(2M Cache, 2.00GHz)
- 300 Mbps Bit Rate input Max
- HDMI output resolution at up to 4MP , VGA output resolution at up to 2MP
- 2 hot-swappable SATA
- 4GB memory
- 2 USB 2.0 & 1 USB 3.0
- Alarm in/out : 16/4
- 1 RJ-45 10/100/1000 Mbps self-adaptive interface
- 4P/8P models support 4/8 independent 100M PoE network interfaces

DS-9664NI-I8 DS-9632NI-I8 DS-9616NI-I8

Embedded H.265+ 4K 2U NVR



- 320 Mbps Bit Rate Input Max(up to 16/32/64-ch IP cameras input)
- Third-party network cameras supported
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264+/MPEG4 video formats
- 2-ch HDMI and 2-ch VGA outputs interfaces provided, HDMI1 output at up to 4K resolution
- 8 SATA, HDD hot swapping, 1 eSATA, 2 USB2.0, 1 USB3.0
- Support RAID0,1,5,6,10
- *Hot spare working mode

DS-7732NI-K4(/16P) DS-7716NI-K4(/16P)

Embedded entry level H265+ 4K NVR, 1.5U PoE



- 160/256Mbps Bit Rate input Max(up to 32/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 8MP resolution recording
- Support H.265+/H.265/H.264+/H.264/MPEG4 video formats
- HDMI output resolution at up to 4K
- 4 SATA, 2 x USB 2.0, 1 x USB 3.0
- /16P series support 16 independent PoE network interfaces

DS-9600NI-H8

X86 open platform for software developers and integrators



- Intel Xeon Processor(8M Cache, 3.20GHz)
- 768 Mbps Bit Rate input Max
- 2 HDMI, output resolution at up to 8MP, VGA output resolution at up to 2MP
- 8 hot-swappable SATA & 1 eSATA interface
- 8GB memory
- 2 USB 2.0 & 2 USB 3.0
- Alarm in/out : 16/4(8 optional)
- 2 RJ-45 10/100/1000 Mbps self-adaptive interfaces

DS-9000AI-S16-D

NVR+X86 , compatible with third-party VMS and worked as a workstation, Redundant power supply



- 576Mbps Bit Rate input Max(up to 128-ch IP cameras input)
- Up to 20-ch decoding capacity at 1080p resolution
- Redundant power supply
- Support RAID 0/1/5/6/10
- Server board: Intel Processor ;Ubuntu Linux installed by default , Microsoft windows is optional; up to 64GB DDR memory, 128 GB system disk; 4 x RJ45, 2 x USB2.0, 2 x USB3.0
- Storage board : Up to 16 SATA ,hot swapping, 1 x eSATA , 4 x RJ45, 2 x USB 3.0, 2 x USB2.0

DS-7732NI-I4(/16P) DS-7716NI-I4(/16P)

Embedded H.265+ 4K 1.5U PoE NVR



- 160/256Mbps Bit Rate Input Max(up to 16/32-ch IP video)
- Third-party network cameras supported
- Up to 12MP resolution recording
- Support H.265+/H.265/H.264+/H.264/MPEG4 video formats
- HDMI output resolution at up to 4K
- 4 SATA, 1 eSATA, 2 x USB 2.0, 1 x USB 3.0
- /16P series support 16 independent PoE network interfaces
- *4-ch 4K decoding or 16-ch 1080P decoding

DS-7608NI-K2(/8P) DS-7616NI-K2(/16P)

Embedded entry level H265+ 4K NVR, 1U PoE



- 160/256Mbps Bit Rate input Max(up to 8/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 8MP resolution recording
- Support H.265+/H.265/H.264+/H.264/MPEG4 video formats
- HDMI output resolution at up to 4K
- 2 SATA, 1 x USB 2.0, 1 x USB 3.0
- 8P/16P series support 8/16 independent PoE network interfaces

NVR & TURBO HD DVR

DS-7604NI-K1(/4P)

Embedded entry level H265+ 4K NVR, 1U PoE



- 40Mbps Bit Rate input Max(up to 4-ch IP cameras input)
- Third-party network cameras supported
- Up to 8MP resolution recording
- Support H.265+/H.265/H.264+/H.264/MPEG4 video formats
- HDMI output resolution at up to 4K
- 1 SATA, 2 USB 2.0
- 4P series support 4 independent PoE network interfaces

DS-7732NI-E4(/16P)

DS-7716NI-E4(/16P)
Embedded 1.5U PoE NVR



- 160 Mbps Bit Rate input Max(up to 16/32-ch IP cameras input)
- Third-party network cameras supported
- Up to 6MP resolution recording
- Support H.264+/H.264/MPEG4 video formats
- HDMI and VGA output at up to 2M Resolution
- 4 SATA, 2 USB 2.0, 1 USB 3.0
- /16P series support 16 independent PoE network interfaces

DS-7608NI-E2(/8P)

DS-7616NI-E2(/16P)
Embedded 1U PoE NVR



- 80/160Mbps bit rate input max(up to 8/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 6MP resolution recording
- Support H.264+/H.264/MPEG4 video formats
- HDMI and VGA output resolution at up to 2M
- 2 SATA, 1 x USB 2.0, 1 x USB 3.0
- 8P/16P series support 8/16 independent PoE network interfaces

DS-7604NI-E1(/4P)

DS-7608NI-E1
DS-7616NI-E1
Embedded 1U PoE NVR



- 40/80/160Mbps bit rate input max(up to 4/8/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 6MP resolution recording
- Support H.264+/H.264/MPEG4 video formats
- HDMI and VGA output at up to 2M resolution
- 1 SATA, 1 USB 2.0, 1 USB 3.0
- /4P series support 4 independent PoE network interfaces

DS-7104NI-SN(/P)

DS-7108NI-SN(/P)
DS-7116NI-SN(/P)
Embedded Mini 1U NVR



- 25/50/100Mbps bit rate input max(up to 4/8/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 2MP resolution recording
- HDMI and VGA output at up to 2M resolution
- 1 SATA, 2 USB 2.0
- P models support 4/8/16 independent PoE network interfaces

DS-7108NI-E1/V/W

DS-7108NI-E1/V/W/500G
DS-7108NI-E1/V/W/1T
Embedded Mini Wi-Fi Router NVR



- 50Mbps bit rate input max(up to 8-ch IP cameras input)
- Third-party network cameras supported
- Up to 6MP resolution recording
- HDMI and VGA output at up to 1920x1080P resolution
- 1 SATA, 1 USB 3.0
- 802.11 b/g/n and a built-in dual WiFi antenna for a strong wireless network signal
- Automatic detection and connection of IP cameras without any manual operation

DS-7600NI-E1/A

DS-7600NI-E1/A/500G
DS-7600NI-E1/A/1T
Embedded All-in-One NVR



- 80Mbps bit rate input max(up to 8-ch IP cameras input)
- Third-party network cameras supported
- 22" LCD monitor up to 1080P resolution & NVR all in one
- Optional display of HDMI/VGA/internal NVR video sources
- Up to 6MP resolution recording
- 1 SATA, 2 USB 2.0
- Up to 1920x1080P display resolution
- Support advertising files import from USB port and preview

DS-7604NI-E1/GW

DS-7608/16NI-E2/GW
Embedded 1U 4G/3G NVR



- 25/50/100Mbps bit rate input max(up to 4/8/16-ch IP cameras input)
- Third-party network cameras supported
- Up to 8MP resolution recording
- HDMI and VGA output at up to 1920x1080P resolution
- 1 SATA(DS-7604NI-E1 series)/2 SATA(DS-7608/16NI-E2 series), 1 USB 3.0
- Built-in 4G/3G modular to support wireless function
- */GLF series support FDD-LTE 4G network
- */GW series support WCDMA UMTS/HSDPA/HSUPA 3G network"

TURBO HD DVRs

DS-7204/08HUHI-F1/S

5MP 1U Turbo HD DVR



- 4/8-ch video & 4-ch audio input
- HDTV/analog/AHD/IP camera quadruple hybrid
- 12fps recording at 5MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920x1080P resolution(DS-7204HUHI-F1/S), support CVBS output
- 4K UHD output (DS-7208HUHI-F1/S)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208HUHI-F1/S)

DS-7204/08/16HUHI-F2/S

5MP 1U Turbo HD DVR



- 4/8/16-ch video & 4-ch audio input
- HDTV/analog/AHD/IP camera quadruple hybrid
- 12fps recording at 5MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920x1080P resolution(DS-7204HUHI-F2/S), support CVBS output
- 4K UHD output (DS-7208/16HUHI-F2/S)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208/16HUHI-F2/S)

DS-7104/08/16HGHI-F1

720P Mini 1U Turbo HD DVR



- 4/8/16-ch HD TVI/AHD/analog cameras video&audio input
- HD-TVI/AHD/analog hybrid
- HD-TVI and analog cameras self-adaptive access
- Up to full channel@720P resolution real-time recording
- HDMI and VGA output at up to 1920x1080P resolution
- Long transmission distance over coax cable
- 1SATA, 2 USB 2.0

DS-7104/08/16HQHI-F1/N

1080P Mini 1U Turbo HD DVR



- 4/8/16-ch HD TVI/analog/AHD cameras video&audio input
- HD-TVI/analog/AHD/IP camera hybrid
- H.264+ video compression
- Full channel@720P resolution real-time and 1080P non real-time recording
- HDMI and VGA output at up to 1920x1080P resolution
- Long transmission distance over coax cable
- 1 SATA, 2 USB 2.0

TURBO HD DVR

DS-7204/08/16HGHI-F1
DS-7208/16HGHI-F2
720P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/AHD/analog cameras video&audio input
- HD-TVI/analog/AHD/IP camera quadruple hybrid
- HD-TVI and analog cameras self-adaptive access
- Up to full channel@720P resolution real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1SATA(DS-7204/08/16HGHI-F1)/2 SATA(DS-7208/16HGHI-F2), 2 USB2.0

DS-7204/08/16HQHI-F1/N
1080P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/analog/AHD cameras video&audio input
- HD-TVI/analog/AHD/IP camera hybrid
- H.264+ video compression
- Full channel@720P resolution real-time and 1080P non real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 2 USB 2.0

DS-7208/16HQHI-F2/N
1080P 1U Turbo HD DVR



- 8/16-ch HD TVI/analog/AHD cameras video&audio input
- HD-TVI/analog/AHD/IP camera hybrid
- H.264+ video compression
- Full channel@720P resolution real-time and 1080P non real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA, 2 USB 2.0

DS-7204/08HUHI-F1/N
3MP 1U Turbo HD DVR



- 4/8-ch video & 1-ch audio input
- HDTV/analog/AHD/IP camera quadruple hybrid
- 15fps recording at 3MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7204HUHI-F1/N), support CVBS output
- 4K UHD output (DS-7208HUHI-F1/N)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208HUHI-F1/N)

DS-7204/08HUHI-F2/N
3MP 1U Turbo HD DVR



- 4/8/16-ch video & 1-ch audio input
- HDTV/analog/AHD/IP camera quadruple hybrid
- 15fps recording at 3MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7204HUHI-F2/N), support CVBS output
- 4K UHD output (DS-7208/16HUHI-F2/N)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208HUHI-F2/N)

DS-7204/08/16HGHI-SH
1080P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/analog cameras video&audio input
- HD-TVI/analog/IP camera triple hybrid
- HD-TVI and analog cameras self-adaptive access
- Full channel@720P resolution real-time and 1080P no-real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA(DS-7216HGHI-SH)/1 SATA(7204/08HGHI-SH), 2 USB2.0

DS-7204/08/16HQHI-SH
Full 1080P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/analog cameras video&audio input
- HD-TVI/analog/IP camera triple hybrid
- HD-TVI and analog cameras self-adaptive access
- Full channel@1080P resolution real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA(DS-7208/16HQHI-SH)/1 SATA(7204HQHI-SH), 2 USB2.0

DS-7304/08/16HQHI-F4/N
1080P 1.5U Turbo HD DVR



- 4/8/16-ch video & 4-ch audio input
- HDTV/analog/AHD/IP camera quadruple hybrid
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7304/08HQHI-F4/N), support CVBS output
- 4K UHD output (DS-7316HQHI-F4/N)
- Long transmission distance over coax cable
- 4 SATA, 1 eSATA, 3 USB2.0, gigabit NIC



DS-7304/08/16/24/32HGHI-SH
1080P 1.5U Turbo HD DVR



- 4/8/16/24/32-ch HD TVI/analog cameras video&audio input
- HD-TVI/analog/IP camera triple hybrid
- HD-TVI and analog cameras self-adaptive access
- Full channel@720P resolution real-time and 1080P no-real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Gigabit network interfaces
- 4 SATA, 1 eSATA, 3 USB2.0

DS-7304/08/16HUHI-F4/N
3MP 1.5U Turbo HD DVR



- 4/8/16-ch HD-TVI/analog cameras video & audio input
- HDTV/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 6/10/18-ch 8MP ONVIF conformant IP cameras input
- 4K (3840 × 2160) UHD output
- Long transmission distance over coax cable
- Supports POS triggered recording and POS information overlay
- Dual Gigabit network interfaces
- 4 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0



DS-8104/08/16HQHI-F8/N
1080P 2U Turbo HD DVR



- 4/8/16-ch video & audio input
- HDTV/analog/AHD/IP camera quadruple hybrid
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-8104/08HQHI-F8/N), support CVBS output
- 4K UHD output (DS-8116HQHI-F8/N)
- Long transmission distance over coax cable
- 8 SATA, 1 eSATA, 3 USB2.0, gigabit NIC



DS-8104/08/16/24/32HGHI-SH
1080P 2U Turbo HD DVR



- 4/8/16/24/32-ch HD TVI/analog cameras video&audio input
- HD-TVI/analog/IP camera triple hybrid
- HD-TVI and analog cameras self-adaptive access
- Full channel@720P resolution real-time and 1080P no-real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Dual Gigabit network interfaces
- 8 SATA, 1 eSATA, 3 USB2.0

TURBO HD DVR & KEYBOARD

HYBRID DVR

DS-8104/08/16HUHI-F8/N

3MP 2U Turbo HD DVR



- 4/8/16-ch HD-TVI/analog cameras video & audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 6/10/18-ch 8MP ONVIF conformant IP cameras input
- 4K (3840 × 2160) UHD output
- Long transmission distance over coax cable
- Supports POS triggered recording and POS information overlay
- Dual Gigabit network interfaces
- 8 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-9004/08/16HUHI-F8/N

3MP 2U Turbo HD DVR



- 4/8/16-ch HD-TVI/analog cameras video & audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 10/18/32-ch 8MP ONVIF conformant IP cameras input
- 4K (3840 × 2160) UHD output
- Long transmission distance over coax cable
- Supports POS triggered recording and POS information overlay
- Dual Gigabit network interfaces
- 8 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-9004/08/16HFI-ST(-RT)

Full 4CIF 2U Hybrid DVR



- Up to 8/16/32-ch [Analog video + IP video] input
- H.264 & dual-stream video compression
- Full channel@4CIF real-time analog video recording
- Up to 5MP resolution IP video recording
- Third-party network cameras supported
- HDMI and VGA output at up to 1920×1080P resolution
- 8 SATA, 1 eSATA, 3 USB2.0
- * -RT series support RAID0, 1, 5, 10

DS-7604HUHI-F1/N & DS-7608/16HUHI-F2/N

3MP 1U Turbo HD DVR



- Up to 8/16/32-ch [Analog video + IP video] input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 8MP resolution IP video recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 2 USB 2.0[DS-7604HUHI-F1/N]
- 2 SATA, 1 USB 2.0 & 1 USB 3.0[DS-7608/16HUHI-F2/N]

DS-7604/08/16HI-ST

Full 4CIF 1U Hybrid DVR



- Up to 8/16/32-ch [Analog video + IP video] input
- H.264 & dual-stream video compression
- Full channel@4CIF real-time analog video recording
- Up to 5MP resolution IP video recording
- Third-party network cameras supported
- HDMI output at up to 1920×1080P resolution
- 1 SATA[DS-7604HI-ST]/2 SATA[DS-7608/16HI-ST], 2 USB2.0

DS-8104/08/16HFHI-ST(-SL)

Full 1080P/720P 2U HD-SDI DVR



- 4/8/16-ch HD-SDI video&audio input
- H.264 & dual-stream video compression
- Full channel@1920×1080P resolution real-time recording[-ST series]
- Full channel@1280×720P resolution real-time recording[-SL series]
- HDMI and VGA output at up to 1920×1080P resolution
- Dual Gigabit network interfaces
- HDD quota and group management
- 8 SATA, 1 eSATA, 3 USB2.0

KEYBOARD

DS-7304/08/16HFHI-ST(-SL)

Full 1080P/720P 1.5U HD-SDI DVR



- 4/8/16-ch HD-SDI video&audio input
- H.264 & dual-stream video compression
- Full channel@1920×1080P resolution real-time recording[-ST series]
- Full channel@1280×720P resolution real-time recording[-SL series]
- HDMI and VGA output at up to 1920×1080P resolution
- Gigabit network interfaces
- HDD quota and group management
- 4 SATA, 1 eSATA, 3 USB2.0

DS-1600KI

Network Keyboard



- 10.1" capacitive touchscreen with 1024×600 resolution
- Touchscreen and joystick detachable
- Live view
- Wifi connection
- PoE power supply
- External video play via USB interface
- HDMI, DVI output
- Emergency event recording and picture capturing
- Video wall control: window division, screen splicing, cross-window video roaming

DS-1100KI

Network Keyboard



- 7" TFT touch screen with 800×480 resolution
- Live view and video playback
- Video wall control
- 4-axis joystick
- Macro command operation
- Up to 255 analog domes by RS-485 connection
- Compatible with Hikvision IP cameras, DVR/NVR, decoder, matrix

DS-1005KI

USB Keyboard



- USB HID protocol
- Power supply and communication by USB port directly;
- PTZ control: set and call the preset, patrol and pattern
- DVR/NVR menu control
- Compatible with client software and platform software;

DS-1200KI

Network Keyboard



- 128×64 LED dot matrix screen
- PTZ and TV wall control
- 4-axis joystick
- System upgrade and import / export of configuration files by USB-flash disk
- Network access and configuration by Web browser support

DS-1006KI

RS-485 Keyboard



- 128×64 LED dot matrix screen
- PTZ and TV wall control
- 4-axis joystick
- System upgrade and import / export of configuration files by USB-flash disk
- RS-485 serial port

ENCODER & MOBILE RECORDER

ENCODERS

DS-6708/16HQHI-SATA

HD1080P Encoder



- 8/16-ch video input, 4-ch audio input
- HD-TVI and analog cameras self-adaptive access
- H.264 & dual-stream video compression
- Full channel@1920x1080P resolution real-time recording
- Multiple network protocols
- 2 SATA interfaces, up to 6 TB for each disk
- 8/16-ch alarm in, 4-ch alarm output

DS-6701/04/08/16HFI/HWI(-SATA)

Full 4CIF/960H Encoder



- 1/4/8/16-ch video&audio input
- H.264/MPEG4/MPEG2/MJPEG & dual-stream video encoding
- Full channel@ 4CIF resolution for DS-6700HFI (-SATA) and full channel@WD1(PAL:960x576,NTSC:960x480) resolution for DS-6700HWI (-SATA)
- Multiple network protocols
- One independent PoE network interfaces for DS-6701/6704HFI/HWI models
- Multiple PTZ protocols
- 1 SATA (DS-6701/04/08/16HFI/HWI-SATA)

DS-6600HFI-JX

ATCA Standard Encoder



- Up to 64-ch video&audio input
- H.264/MPEG4/MPEG2/MJPEG & dual-stream video encoding
- 16 slots available for audio/video output modules (DS-6604HFI-B)
- Each DS-6604HFI-B module provides 4-ch audio/video inputs
- Full channel@4CIF resolution real-time recording
- Standard rack-mounted chassis structure (6U 19")
- Pluggable modular design provides high flexibility

NETWORK STORAGE

DS-A81024D

Network Storage System



- High-performance & easily-extensible hardware platform
- Highly reliable system design, double controller
- Support 180 -Ch(2M) record and play in IP-SAN mode,296 -Ch(2M) record and play in CVR mode
- Disk detection, repair and RAID optimization
- Low power design
- Massive storage space, 4U chassis with 14 HDDs and cascade extension support

DS-A82024D

Network Storage System



- High-performance & easily-extensible hardware platform
- Highly reliable system design, double controller
- Support 256 -Ch(2M) record and play in IP-SAN mode,448 -Ch(2M) record and play in CVR mode
- Disk detection, repair and RAID optimization
- Low power design
- Massive storage space, 4U chassis with 14 HDDs and cascade extension support

DS-A81016S

Network Storage System



- High performance with 64-bit RISC processor
- Up to 16 HDD, each disk up to 4TB capacity and cascade extension support
- Support 180 -Ch(2M) record and play in IP-SAN mode,296 -Ch(2M) record and play in CVR mode
- iSCSI/NFS/CIFS/FTP/HTTP/AFP protocols
- RAID 0, 1, 3, 5, 10, 50 and HDD hot swap supported
- Modularization and redundant power design for highest reliability

MOBILE RECORDERS

DS-A80624S

Network Storage System



- High performance with 64-bit RISC processor
- Up to 24 HDD, each disk up to 4TB capacity and cascade extension support
- Support 120 -Ch(2M) record and play in IP-SAN mode,192 -Ch(2M) record and play in CVR mode
- iSCSI/NFS/CIFS/FTP/HTTP/AFP protocols
- RAID 0, 1, 3, 5, 10, 50 and HDD hot swap supported
- Modularization and redundant power design for highest reliability

DS-MP3516-RS/GW

On-board Network Recorder



- 16 channels video/audio input
- Support up to 6 x 2.5-inch HDDs/SSDs
- 1-ch CVBS output, 1-ch VGA output
- Support Wi-Fi connection
- Support 3G connection *only for GW model
- 2 x Ethernet ports with M12 plug
- Built-in G-sensor
- Wide power range protection
- Super capacitor for power-off protection
- Patented anti-vibration design

DS-M5504HNI

4-Channel Mobile NVR



- Supports 4 channels of 1080P IP video input
- 4-channel POE interface
- Pluggable disk box with vibration damping technology
- 2x pluggable 2.5-inch HDDs / SSDs
- 1x SD/SDHC card slot
- Pluggable 3G/4G/Wi-Fi module (optional)
- Standard 1DIN dimensions
- EN50155 certification

DS-M5504HMI-SD

4-Channel Mobile DVR



- Supports 4 channels of WD1 video input
- 2x SD / SDHC / SDXC card slot
- Pluggable 3G/4G/Wi-Fi module (optional)
- Standard 1DIN dimensions
- EN50155 certification

DS-M5504HMI

4-Channel Mobile DVR



- Supports 4 channels of WD1 video input
- Pluggable disk box with vibration damping technology
- 1x 2.5-inch HDD/SSD
- Pluggable 3G/4G/Wi-Fi module (optional)
- Standard 1DIN dimensions
- EN50155 certification

DS-MP7504

HD-TVI Mobile DVR



- Supports 4 channels of 720P video input
- 4-ch POE interface
- Pluggable disk box with vibration damping technology
- 2x pluggable 2.5-inch HDDs / SSDs
- Pluggable 3G/4G model (optional)
- Built-in Wi-Fi/GPS (optional)
- Built-in G-sensor
- EN50155 certification

MONITOR & NETWORK SWITCH

MONITOR

DS-D5019QE
19" LCD Monitor



- LED backlit with 1366×768 resolution
- View angle: 90°(H)/65°(V)
- Inputs: VGA
- 3D comb filter, 3D de-interlace, 3D noise reduction
- High reliable components for 7×24 working

DS-D5019QE-B
19" LCD Monitor



- LED backlit with 1366×768 resolution
- View angle: 90°(H)/65°(V)
- Inputs: VGA, HDMI
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5022FC
22" LCD Monitor



- LED backlit technology with full HD 1920×1080
- Wide View angle: 170°(H)/160°(V)
- Multiply inputs: HDMI, VGA, BNC, audio in
- 3D comb filter, 3D de-interlace, 3D noise reduction
- High reliable components for 7×24 working

DS-D5022QE-B
22" LCD Monitor



- LED backlit technology with full HD 1920×1080
- Wide View angle: 170°(H)/160°(V)
- Inputs: VGA, HDMI
- 3D comb filter, 3D de-interlace, 3D noise reduction
- High reliable components for 7×24 working

DS-D5032FC
32" LCD Monitor



- LED backlit with 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, S-Video, CVBS(BNC×1), audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5043FC
43" LCD Monitor



- LED backlit with 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, CVBS(BNC×1), audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5032FL
32" LCD Monitor



- LED backlit with 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, BNC, USB, audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- Image freeze
- High reliable components for 7×24 working

DS-D5042FL
42" LCD Monitor



- LED backlit with 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, BNC, USB, audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- Image freeze
- High reliable components for 7×24 working

DS-D5055FL
55" LCD Monitor



- LED backlit with 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, BNC, USB, YPbPr, S-Video, audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- Image freeze
- High reliable components for 7×24 working

DS-D5055UL
55" LCD Monitor



- LED backlit with 3840×2160 UHD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI×2, VGA, DVI, DP, audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5084UL
84" LCD Monitor



- LED backlit with 3840×2160 UHD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI×2, VGA, DP×2, USB, audio in
- Build-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

NETWORK SWITCH & DECODER

NETWORK SWITCH

DS-3D2208P

Full Managed L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 2×Gigabit combo ports
- 150Watts PoE budget
- QoS and flow control
- 32Gbps switching bandwidth
- VLAN support and tagging
- Spanning Tree Protocol(STP)
- Network Management: SNMP, Telnet, RMON, CLI
- Network Security: IEEE 802.1x, IP ACL, MAC ACL, VLAN ACL, and static/dynamic ARP prevention

DS-3D2228P

Full Managed L2 PoE Switch



- 24×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 4×Gigabit combo ports
- 370Watts PoE budget
- QoS and flow control
- 32Gbps switching bandwidth
- VLAN support and tagging
- Spanning Tree Protocol(STP)
- Network Management: SNMP, Telnet, RMON, CLI
- Network Security: IEEE 802.1x, IP ACL, MAC ACL, VLAN ACL, and static/dynamic ARP prevention

DS-3E0105P-E

Unmanaged L2 PoE Switch



- 4×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 1×10/100Mbps uplink port
- 58Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E0109P-E

Unmanaged L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 1×10/100Mbps uplink port
- 123Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E0318P-E

Unmanaged L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 1×10/100Mbps uplink port
- 123Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E0326P-E

Unmanaged L2 PoE Switch



- 24×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 2×1000M combo port
- 370Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E1310P-E

Managed L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 2×1000Mbps combo uplink port
- 123Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug & play installation
- Web-managed: VLAN, Port Mirroring, SNMP, etc.

DS-3E1318P-E

Managed L2 PoE Switch



- 16×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 2×1000M combo uplink port
- 230Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Web-managed: VLAN, Port Mirroring, SNMP, etc.

DS-3E1326P-E

Managed L2 PoE Switch



- 24×10/100Mbps PoE ports, each port support 802.3af/802.3at self-adaption
- 2×1000M combo port
- 370Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Web-managed: VLAN, Port Mirroring, SNMP, etc.

DECODER

DS-D6400HDI-T Series

High Definition Decoder



- Max. 8-ch 8MP or 32-ch 1080P decoding
- PC signal input via VGA/DVI input interface(except DS-6401HDI-T)
- Decoding output via DVI and BNC interface(DS-6401HDI HDMI/VGA/BNC output)
- 1/4/6/8/9/12/16 division
- H.264/MPEG4 /MPEG2/MJPEG format
- Max. 4×4 video wall control
- Window division, large screen splicing, cross-window video roaming

DS-D6901UDI

Ultra High Definition Decoder



- 2-ch 12MP or 16-ch 1080P decoding
- Decoding output via HDMI, VGA and BNC interface
- 4K resolution output via HDMI interface
- 1/4/6/8/9/12/16 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Two-way audio

DS-D6904UDI

Ultra High Definition Decoder



- 4-ch 12MP or 32-ch 1080P decoding
- Decoding output via HDMI and BNC interface
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for even interface)
- 1/4/6/8/9/12/16/25 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Build-in 16 port 100M switch
- Two-way audio

VMS & ACCESSORIES

DS-D6908UDI

Ultra High Definition Decoder



- 8-ch 12MP or 64-ch 1080P decoding
- Decoding output via HDMI and BNC interface
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for even interface)
- 1/4/6/8/9/12/16/25/36 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Build-in 16 port 100M switch
- Two-way audio

DS-D6910UDI

Ultra High Definition Decoder



- 10-ch 12MP or 80-ch 1080P decoding
- Decoding output via HDMI and BNC interface
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for even interface)
- 1/4/6/8/9/12/16/25/36 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Build-in 16 port 100M switch
- Two-way audio

DS-D6912UDI

Ultra High Definition Decoder



- 12-ch 12MP or 96-ch 1080P decoding
- Decoding output via HDMI and BNC interface
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for even interface)
- 1/4/6/8/9/12/16/25/36 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Build-in 16 port 100M switch
- Two-way audio

DS-D6916UDI

Ultra High Definition Decoder



- 16-ch 12MP or 128-ch 1080P decoding
- Decoding output via HDMI and BNC interface
- Up to 4K (3840 × 2160@30Hz) via HDMI output interfaces (only for even interface)
- 1/4/6/8/9/12/16/25/36 division
- H.265/H.264+/H.264/MPEG4 /MPEG2/MJPEG format
- Build-in 16 port 100M switch
- Two-way audio

iVMS

iVMS 5200 Pro

iVMS-5200 Professional Software



- Centralized equipment and user management
- Support ANPR and ANPR based parking management
- Support business intelligence & POS integration
- Support RSM to control 5 CMS for large system **(New)**
- Maximum connected devices per CMS: 1024
- 3rd party surveillance integration via ONVIF protocol and SDK
- Mobile transportation management module

Blazer Pro 256/128

VMS All-in-One Server



- Ready to use, preinstalled with Hikvision Professional VMS software and Windows 8.1;
- Up to 256 channels access and recording , recording bandwidth up to 640 Mbps;
- Support for 2×2 screen displays, an economical solution for small monitoring centers;
- HDD hot swap with RAID0, RAID1, RAID5, RAID10, N+1 equipment hot spare to ensure data reliability;
- Active directory integration for user management;
- 3 years of software technical support with SSP.

PORTABLE CAMERA

Blazer Express

A Simple iVMS Station With Enormous Potential



- Easy and user friendly UI design for easy basic operation and daily monitoring operation
- Alarm information, real-time video, and the physical location are all displayed on one screen
- Interactive Live View E-map for system awareness and easy visual identification of events
- ANPR function makes entrance/exit management and identification of VIP or black list vehicles quick and convenient
- Point-of-sale integration displays transaction data and video on the same screen for effective customer

DS-6102 HLI/GW

Portable Video Recorder



- H.264 Video Compression
- 3.5 inch IPS Touch Screen
- 5MP HD Camera
- Up to HD1080p Video Recording
- Up to 32GB Micro SD card recording
- Built-in 3G and GPS module

DS-MH6171

Portable PTZ Dome



- 2 MP Full HD1080p high resolution
- 30X optical zoom, 12X digital zoom
- H.264+ optimized codec to reduce storage
- Dual SD card slots, up to 128 GB for each card
- Supports Wi-Fi, 3G, 4G wireless connection
- Interchangeable Lithium battery, up to 6-hour operating time
- Alarm I/O, RS232, RS485 interfaces
- Supports Bluetooth connection
- IP66 weather-proof protection
- Up to 195 feet (60m) IR range
- Powerful magnetic base for vehicle-roof mounting
- iVMS-4500 client for remote operation

ACCESS CONTROL

INTRUSION ALARM & VIDEO INTERCOM

ACCESS CONTROL

DS-K1802M/E
Card Reader



- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard

DS-K1802MK/EK
Card Reader



- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard
- With keypad

DS-K1F810-F
Fingerprint Card
Issuer



- 500 dpi high-definition
- Support the function of PnP(plug and play)
- Optical fingerprint sensor designed with scratch-resistant material
- USB 2.0 communication standard for data transmission

DS-K1F180-D8E
Card Issuer



- Plug-and-play USB with no-driver technology
- Supports various card types (Mifare card and EM card)
- Supports on-line upgrade

DS-K1107E/EK
DS-K1107E/EK



- Support EM card,
- With keypad (DS-K1107EK)
- Supports RS485 and Wiegand (W26/W34) protocol,
- IP65 Standard

DS-K1107M/MK
Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1107MK)
- Supports RS485 and Wiegand (W26/W34) protocol,
- IP65 Standard

DS-K1200EF/MF
Fingerprint Card
Reader



- Support fingerprint Mifare 1/EMcard
- Supports RS485 protocol,
- IP65 Standard
- 9500 Fingerprints Capacity

DS-K2M060
Secure Module



- Provide secure door control as well as I/O expansion via encrypted communication when combined with other Hikvision terminal.
- Support RS485 protocol

DS-K1T803F
Fingerprint Access
Control Terminal



- Support Access Control and Time Attendance Function
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.4-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation

DS-K1T803MF/EF
Fingerprint Access
Control Terminal



- Support Access Control and Time Attendance Function
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.4-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation
- Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc

DS-K1A801F
Fingerprint Time
Attendance Terminal



- Support Time Attendance Function, Forming Reports Automatically
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.8-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation(Adding Person & Card & Fingerprints Locally)

DS-K1A801MF/EF
Fingerprint Time
Attendance Terminal



- Support Time Attendance Function, Forming Reports Automatically
- Optical Fingerprint Module, 3,000 Fingerprints Capacity
- 2.8-inch LCD Screen
- Support Wi-Fi & TCP-IP
- Stand-alone Operation(Adding Person & Card & Fingerprints Locally)
- Multiple Authentication: Card(EM or Mifare-1 Card), Fingerprint, etc

DS-K2801
Single-door Access
Controller



- Accessible Card Reader: 2 Wiegand readers
- Input interface: 1 Door Magnetic, 1 Door Switch, 1 Case Input
- Output interface: 1 Door Switch Relay, 1 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 10,000 cards information and 50,000 access control events

DS-K2802
Double-door Access
Controller



- Accessible Card Reader: 4 Wiegand readers
- Input interface: 2 Door Magnetic, 2 Door Switch, 2 Case Input
- Output interface: 2 Door Switch Relay, 2 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 10,000 cards information and 50,000 access control events

DS-K2804
Four-door Access
Controller



- Accessible Card Reader: 4 Wiegand readers
- Input interface: 4 Door Magnetic, 4 Door Switch, 4 Case Input
- Output interface: 4 Door Switch Relay, 4 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 10,000 cards information and 50,000 access control events

DS-K1T801M/E
Time & Attendance
and Access Control
Terminal



- 12 Keys Keyboard and doorbell
- Built-in Mifare/EM Card reading module
- Max. 3000 card number settings
- Supports door-open button

ACCESS CONTROL

INTRUSION ALARM & VIDEO INTERCOM

DS-K1T802M/E

Time & Attendance and Access Control Terminal



- 128×64 Dot Matrix STN Screen
- 12 Keys Keyboard and doorbell
- Built-in Mifare/EM Card reading module
- Supports door-open button
- Storage with 3,000 cards information and 10,000 access control events

DS-K1801MK/EK

Card Reader



- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard
- With keypad

DS-K1801M/E

Card Reader



- Support Mifare 1/EM card
- PC+ABS material shell
- Supports Wiegand protocol
- IP65 Standard

DS-K1F100-D8E

Card Enrollment Station



- Plug-and-play USB with no-driver technology
- Supports various card types (Mifare card, CPU, PSAM, and EM card)
- Supports on-line upgrade

DS-K2601

Single door Access Controller



- Accessible Card Reader: 2 Wiegand readers & 2 RS485 readers
- Input interface: 4 Alarm Input, 1 Door Magnetic, 1 Door Switch, 2 Case Input, 1 Tamper-proof
- Output interface: 1 Door Switch Relay, 1 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 100,000 cards information and 300,000 access control events

DS-K2602

Double-door Access Controller



- Accessible Card Reader: 4 Wiegand readers & 4 RS485 readers
- Input interface: 4 Alarm Input, 2 Door Magnetic, 2 Door Switch, 4 Case Input, 1 Tamper-proof
- Output interface: 2 Door Switch Relay, 2 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 100,000 cards information and 300,000 access control events

DS-K2604

Four door Access Controller



- Accessible Card Reader: 4 Wiegand readers & 8 RS485 readers
- Input interface: 4 Alarm Input, 4 Door Magnetic, 4 Door Switch, 8 Case Input, 1 Tamper-proof
- Output interface: 4 Door Switch Relay, 4 Alarm Relay
- Uplink Communication Interface: TCP/IP Network Interface and RS-485 Interface
- Storage with 100,000 cards information and 300,000 access control events

DS-K1T105M/E(-C)

Standalone Access Control Terminal



- 2.8 inch LCD -TFT Screen
- 16 Keys Keyboard and doorbell
- Built-in Mifare/EM Card reading module
- 2 Megapixels camera(Optional)
- Supports WiFi function
- Storage with 100,000 cards information and 300,000 access control events

DS-K1T200MF/EF(-C)

Standalone Access Control Terminal



- 2.8 inch LCD -TFT Screen
- 16 Keys Keyboard and doorbell
- Built-in Mifare/EM Card reading module
- 2 Megapixels camera(Optional)
- Supports WiFi function
- Storage with 100,000 cards information and 300,000 access control events

DS-K1101M(K)

Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1101MK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 120 Gang Box Only

DS-K1102M(K)

Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1102MK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 86 & 120 Gang Box

DS-K1102E(K)

Card Reader



- Support EM card,
- With keypad (DS-K1102EK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 86 & 120 Gang Box

DS-K1104M(K)

Vandal Proof Card Reader



- Support Mifare 1 card,
- With keypad (DS-K1104MK)
- Supports RS485 and Wiegand (W26/W34) protocol, Tamper-proof,
- Applied for 86 & 120 Gang Box
- Vandal Proof

DS-K1F800-F

Fingerprint Card Issuer



- 500 dpi high-definition
- Support the function of PnP(plug and play)
- Optical fingerprint sensor designed with scratch-resistant material
- USB 2.0 communication standard for data transmission

IC S50

Mifare 1 Non-contacting IC Card



- Working frequency: 13.56 MHz
- Anti-conflict
- Long time data storage for 10 years
- Triple accreditation(ISO/IEC DIS9798-2)

DS-K4T100

Electric Bolt



- Support Thrust of 800Kg;
- Polished and Brushed Stainless Steel
- Working Current: 900mA(Startup Current) , 100mA(Standby)
- DC12V

ACCESS CONTROL

INTRUSION ALARM & VIDEO INTERCOM

DS-K4H250S
Magnetic Lock



- Single -door Control
- Supports static linear thrust of 300kg
- Working Current: DC12V(500 mA) / 24VAC(250 mA)

DS-K4H250D
Magnetic Lock



- Double-door Control
- Supports static linear thrust of 2x300kg
- Working Current: 12V/500mA × 2 24V/250mA × 2

DS-K4T100-U1/2
Accessories of Electric Bolt



- Aluminum alloy material
- Suitable for fully frameless glass door
- The door opens both sides at the angle of 180°

DS-K4H250-LZ/U
Accessories of Magnetic Lock



- Adopts aldural material with the surface sandblast
- The shell is hard anodizing electroplating operated

DS-K7P01/02
Exit Button



- Aluminum alloy panel with sandblast, metal button
- Already passed 500 thousand times aging test
- NO/NC/COM Contact
- 3A@36VDC Max

DS-K7P03/04
Exit Button



- Infrared Sensor
- Panel: aluminum panel
- Already passed 1 million times aging test
- NO/NC/COM Contact
- 1A@30VDC, 0.5A@125VAC

DS-K7P05/06
Exit Button



- Infrared Sensor
- Brushed stainless steel panel, metal button
- Already passed 500 thousand times aging test
- NO/NC/COM Contact
- 3A@36VDC Max

DS-K7PEB
Emergency Break Glass



- Suitable for exit door and emergency door
- Fireproof material, sandblast finished
- NO/NC/COM Contact
- 3A@36VDC Max

INTRUSION ALARM

DS-19A08-F/Kx(G)
8 Zone Network Security Control Panel



- PTSN, 10/100Mbps Ethernet
- LED screen (DS-19A08-F/K1)
- LCD screen (DS-19A08-F/K2)
- 1 relay output
- 14.3 VDC

DS-19S08-04F/Kx(Gx)
8 Zone Video Security Control Panel



- 4-ch 960H analog video input
- PTZ control
- LED screen (DS-19S08-04F/K1)
- LCD screen (DS-19S08-04F/K2)
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-19S08N-04F/Kx(Gx)
8 Zone Video Security Control Panel



- Support 4-ch IPC video input, Max 25 Mbps
- PTZ Control
- LED screen (DS-19S08N-04F/K1)
- LCD screen (DS-19S08N-04F/K2)
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-19A00-BN
8/16 Zone Video Control Panel



- PTSN, 10/100Mbps Ethernet
- 4 relay output, 220 VAC

DS-19S00-04S(Gx)
8/16 Zone Video Security Control Panel



- 4-ch 960H analog video input
- PTZ Control
- 1-ch VGA output, 1-ch HDMI output
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-19S00N-04S(Gx)
8/16 Zone Video Security Control Panel



- Support 4-ch IPC video input, support dual-stream
- PTZ Control
- 1-ch VGA output, 1-ch HDMI output
- 1 SATA interface
- 1 relay output, 14.3 VDC

DS-1T21FZ
Dual-technology Detector



- CLOAK WISETM arithmetic
- Tempering-proof bracket
- Sealing optical system
- The IR and microwave working distance is 15m X 15m

DS-1T070R
Shock Detector



- The zinc-aluminum alloy enclosure is antistatic and anti-interference
- The sensitivity is adjustable
- Ceramics sensor, with high temperature & humidity adaptation and corrosion resistance
- Function of low battery and tampering alarm

ACCESS CONTROL

INTRUSION ALARM & VIDEO INTERCOM

VIDEO INTERCOM

DS-19K00-B(X)
LED Alarm Keypad



- Supports remote control via wireless network(the keypad with model of RF)
- Prompts alarm with the indicators and audio alert
- Operates on the security control panel through programming
- LED display, RS485 interface

DS-19K00-BL
LCD Alarm Keypad



- Supports remote control via wireless network(the keypad with model of RF)
- Prompts alarm with the indicators and audio alert
- Operates on the security control panel through programming
- LCD display, RS485 interface

DS-19M00-R0
Trigger Extension Module



- RS-485 trigger extension module
- 8 DIP address
- 4/8-ch trigger Output

DS-KB8112-IM
vandal-proof villa door station



- HD video surveillance with WDR wide angle and high performance CMOS, up to 720P @ 30 fps
- Support Web remote access and OSD display
- Support ISAPI and ONVIF
- IK 9 and IP 66
- Access control function
- Motion detection

DS-KAD606-N
Distributor



- Built-in 24 VDC voltage-stabilized switching mode power supply
- 8 interfaces of RJ-45, including six adaptive 10/100 Mbps LAN interfaces

DS-KB2411-IM
Door Station



- Pinhole Camera with 720*576 @ 25 fps
- Video Intercom Communication
- Support Two Door Stations Cascading in Intercom System
- Unlocking Controlling
- Self-adaptive IR Supplement

DS-KH2200
Indoor Station



- 7-inch LCD Screen
- Video Intercom Communication
- Support Three Indoor Stations Cascading in Intercom System
- Remote Unlocking
- Monitoring Door Station and External Analog Camera

DS-KD8102-V
Plastic Door Station



- 3.5-inch Colorful TFT LCD, display resolution: 480 * 320
- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M/1000M Self-adaptive Ethernet
- 8-ch alarm input, 4-ch alarm output
- IR detection
- Visible Light Supplement

DS-KD8002-VM
Metal Door Station



- 3.5-inch Colorful TFT LCD, display resolution: 480 * 320
- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M/1000M Self-adaptive Ethernet
- 8-ch alarm input, 4-ch alarm output
- Visible Light Supplement

DS-KV81/2/402-IM
Metal Villa Door Station



- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M Self-adaptive Ethernet
- 4-ch alarm input, 1-ch alarm output
- IP 65 and IR Supplement
- 1/2/4-ch Indoor station access

DS-KV8102-IP/VP
Plastic Villa Door Station



- Camera resolution: HD720P, 25fps(P)/30fps(N)
- 10M/100M Self-adaptive Ethernet
- 4-ch alarm input, 1-ch alarm output
- IP 65
- 1-ch Indoor station access
- Visible Light Supplement(-VP), IR Supplement(-IP)

DS-KH8300/DS-KH8301-WT
Indoor Station



- 7-inch Colorful TFT LCD, display resolution: 1024 * 600
- 10M/100M Self-adaptive Ethernet
- Camera resolution: 640 * 480, Mechanical Switch, Wi-Fi 802.11b/g/n, support SD card (DS-KH8301-WT)
- 8-ch alarm input
- Power Over Network Cable/ 12 VDC

DS-KH6310(-W)
Indoor Station



- 7-inch Colorful TFT LCD, display resolution: 800 * 480
- 10M/100M Self-adaptive Ethernet
- Wi-Fi 802.11b/g/n (-W)
- 8-ch alarm input
- Power Over Network Cable/ 12 VDC

DS-KAD606/612
Distributor



- Built-in voltage-stabilized power
- Suitable for indoor monitor station and villa door station
- 8 x 100Mbps ports(6-ch network cable powering and 2-ch cascading LAN interfaces) (DS-KAD606)
- 16 x 100Mbps ports(12-ch network cable powering and 4-ch cascading LAN interfaces) (DS-KAD612)

DS-KM8301
Master Station



- 7-Inch Colorful TFT LCD, display resolution: 1024 * 600
- Capacitive Touch Screen, Touch Key, Physical Key
- 10M/100M/1000M Self-Adaptive Ethernet
- SIP services
- 2 RS-485, 4 On-Off Input, 2 On-Off Output, 2 Relay Output,

DS-KAW50-1
Power Supply



- Power supply for Door station and Villa Door Station
- Output: 12 VDC, 4.2A

DS-KAW50-1N

Power Supply



- Input Voltage: 100-240VAC
- Output Voltage: 12VDC
- Output Current: 4.17A
- Output Power: 50W
- Short circuit protection, over load protection, and over power voltage protection

DS-KAB01


Protective Shield



- Stainless steel material
- Convenient design available for villa door station wall mounting
- Avoid of being directly exposed to the sun
- Rain shield and mounted box are separated.

DS-KAB02

Protective Shield



- Stainless steel material
- Convenient design available for villa door station wall mounting
- Avoid of being directly exposed to the sun

COMPRESSION CARDS

DS-4304HFHI-E

HD1080P Compression Card



- 4-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@1920×1080P resolution real-time recording
- HDMI output at up to 1920×1080P resolution
- PCI-Ex1 2.0 standard
- OSD, LOGO and mask area settings

DS-4308/16HWI-E

Full 960H Compression Card



- 8/16-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@WD1(PAL:960×576,NTSC:960×480) resolution
- real-time recording
- PCI-Ex1 2.0 standard
- OSD, LOGO and MASK overlay

DS-4304/08/16HFVI-E

Full 4CIF Compression Card



- 4/8/16-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@4CIF resolution real-time recording
- PCI-Ex1 2.0 standard
- OSD, LOGO and MASK overlay



2017 Q1

QUARTELY FEATURED PRODUCTS

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
Tel: +27 (0) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision
Corporate Channel

Follow us on social media to get the latest product and solution information

www.hikvision.com