



2018 Q1
QUARTELY FEATURED PRODUCTS

Distributed by



HIKVISION®

Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com


Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com

Follow us on social media to get the latest product and solution information



www.hikvision.com

HIKVISION®

2018 Q1
QUARTERLY FEATURED PRODUCTS

PRODUCT SERIES

DEEPER INTELLIGENCE,
DEEPER SURVEILLANCE.

DeepinView & DeepinMind Series

- Deep Learning algorithm
- High performance GPUs
- Facial recognition, object detection, people counting, vehicle structured data, and human body search
- Continuous improvement of accuracy supported by huge amount of training data



EASY & POWERFUL SECURITY
FOR THE SMALL-MEDIUM BUSINESS

EasyIP 3.0/2.0 Plus Series

- Up to 4K ultra-HD, advanced H.265+ encoding
- Powered by DarkFighter ultra-low illumination technology
- Efficient VCA functions
- Easy to install, setup, and manage
- Budget-friendly and powerful
- Super PoE up to 300 meters
- Low power consumption and light noise



SUPERCHARGING ANALOG SYSTEMS
TO HI-DEF

Turbo HD 4.0 Series

- 5 MP Cameras & up to 1080p output over coax
- Advanced H.265+ encoding
- IR, privacy masking, Smart features and more
- Wide range of in- & outdoor camera types



PRODUCT SERIES

BRINGING THE INVISIBLE
TO LIGHT

Thermal Cameras Series

- Advanced thermal sensors
- Unaffected by changes in weather, light conditions
- Single- & dual-lens and handheld cameras
- Wide range of Smart features



POWERFUL ONE-PIECE SERVER
& VMS STATION

VMS (Blazer) Series

- A server, data storage, VMS station, and NVR in one device
- Advanced hardware and software design for high availability
- Budget-friendly and powerful
- Manages multiple sites and NVRs from one location



A STEADY GUARD AT THE GATE

Access Control + Security Alarm Series

- Video intercom system
- Fully integrated security solution
- Alarm triggering and remote access
- Wide range of options for any application



STAR PRODUCTS

HUGE PANORAMAS. INCREDIBLE ZOOM.

PanoVu Cameras

- Up to 24MP multiple sensors with DarkFighter technology
- 180° & 360° panoramic views with in-camera image stitching
- 50x optical zoom
- Smart tracking, smart detection, & more



PanoVu

DarkFighterX



IN BRIGHT COLORS, ALL DAY, ALL NIGHT.

DarkFighterX Cameras

- Only one lens for two kinds of light
- One sensor for IR light, one for visible light
- Bi-Spectral fusion technology: fuse IR and visible light to get a colorful and bright image
- Up to 25x optical zoom
- H.265+

EASILY BUILD A STABLE LOCAL SURVEILLANCE CENTER

96 M series NVR

- Up to 768Mbps bit rate input Max(Up to 16/32/64 camera input)
- Up to 192T storage capacity(8T x 24HDD),support hot swapping
- Redundant power supply
- Support RAID 0/1/5/6/10
- 20-ch 1080p decoding capacity
- Output resolution at up to 4K



CONTENTS

05	PTZ DOME CAMERAS
08	NETWORK CAMERA
14	THERMAL CAMERA
17	NVR
19	TURBO HD ANALOG CAMERA
27	TURBO HD DVR
29	NETWORK STORAGE
30	MONITOR
31	NETWORK SWITCH
33	ENCODER
33	MOBILE RECORDER
33	VMS
34	OTHER
35	ACCESS CONTROL
39	VIDEO INTERCOM
41	SECURITY ALARM

PTZ DOME CAMERA

Pro Series

DS-2DF8225IH-AEL(W)

DarkFighterX 2MP 25× IR Network Speed Dome



- 2MP 2× 1/2.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 25× Optical Zoom, 16× Digital Zoom
- Digital WDR, 3D DNR, HLC, BLC
- Up to 200 m IR distance
- H.265+/H.265

DS-2DF8836IX-AEL(W)

8MP 36× Network IR Speed Dome



- 8MP 2/3" progressive scan CMOS
- DarkFighter DarkFighter ultra-low light technology
- 36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, smart IR
- Up to 200 m IR distance
- H.265+/H.265
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF8825/8425IX-AEL(W)

4MP/8MP 25× Network IR Speed Dome



- 4MP/8MP 2/3" progressive scan CMOS
- DarkFighter DarkFighter ultra-low light technology
- 25× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, smart IR
- Up to 200 m IR distance
- H.265+/H.265
- Rapid focus
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF8436IX-AEL(W)

4MP 36× Network IR Speed Dome



- 4MP 1/1.9" progressive scan CMOS
- DarkFighter ultra-low light technology
- 36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, smart IR
- Up to 200 m IR distance
- H.265+/H.265
- Rapid focus
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF8236IX-AEL(W)

2MP 36× Network IR Speed Dome



- 2MP 1/1.9" progressive scan CMOS
- DarkFighter ultra-low light technology
- 36× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, smart IR
- Up to 200 m IR distance
- H.265+/H.265
- Rapid focus
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF8225IX-AEL(W)

2MP 25× Network IR Speed Dome



- 2MP 1/1.9" progressive scan CMOS
- DarkFighter ultra-low light technology
- 25× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, smart IR
- Up to 200 m IR distance
- H.265+/H.265
- Rapid focus
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF8250IX-AEL(W)

2MP 50× Network IR Speed Dome



- 2MP 1/2.8" progressive scan CMOS
- 50× Optical Zoom, 16× Digital Zoom
- 120dB WDR, 3D DNR, HLC, BLC
- Optical Image Stabilization
- Up to 500 m IR distance
- H.265+/H.265
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF8836/8436IX-AEL(W)

4MP/8MP 36× Network Laser Speed Dome



- 4MP/8MP 2/3" progressive scan CMOS
- DarkFighter ultra-low light technology
- 36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, smart IR
- Up to 500 m laser distance
- H.265+/H.265
- Rapid focus (8436)
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF8236IX-AEL(W)

2MP 36× Network Laser Speed Dome



- 2MP 1/1.9" progressive scan CMOS
- DarkFighter DarkFighter ultra-low light technology
- 36× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, smart IR
- Up to 500 m laser distance
- H.265+/H.265
- Rapid focus
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF8250IX-AEL(W)

2MP 50× Network Laser Speed Dome



- 2MP 1/2.8" progressive scan CMOS
- 50× Optical Zoom, 16× Digital Zoom
- 120dB WDR, 3D DNR, HLC, BLC
- Optical Image Stabilization
- Up to 800 m laser distance
- H.265+/H.265
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF7232/7225IX-AEL(W)

2MP 25×/32× Network IR Speed Dome



- 2MP 1/2.8" progressive scan CMOS
- 25×/32× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, smart IR
- Up to 150 m IR distance
- H.265+/H.265
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF6A825/36X-AEL

8MP 25×/36× Network Speed Dome



- 8MP 2/3" progressive scan CMOS
- DarkFighter ultra-low light technology
- 25×/36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, BLC, Defog, EIS
- H.265+/H.265
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF6A425/36X-AEL

4MP 25×/36× Network Speed Dome



- 4MP 1/1.9" progressive scan CMOS
- DarkFighter ultra-low light technology
- Rapid focus
- 25×/36× optical zoom, 16× digital zoom
- Digital WDR, 3D DNR, HLC, BLC, Defog, EIS
- H.265+/H.265
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF6A225/36X-AEL

2MP 25×/36× Network Speed Dome



- 2MP 1/1.9" progressive scan CMOS
- DarkFighter ultra-low light technology
- Rapid focus
- 25×/36× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, BLC, Defog, EIS
- H.265+/H.265
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF6225X-AEL

2MP 25× Network Speed Dome



- 2MP 1/1.9" progressive scan CMOS
- DarkFighter ultra-low light technology
- 25× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, Optical Defog
- H.265+/H.265
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

DS-2DF5225/5232X-AEL(3)

2MP 25×/32× Network Speed Dome



- 2MP 1/2.8" progressive scan CMOS
- 120dB WDR, 3D DNR, HLC
- H.265+/H.265
- Deep-learning-based target classification algorithm for auto-tracking 2.0 and perimeter protection

PTZ DOME CAMERA

HIKVISION

DS-2DY9250IAX-A

2MP 50× Network Laser Positioning System



- 2MP 1/2.8" progressive scan CMOS
- 50× optical zoom, 16× digital zoom
- Optical image stabilization (OIS)
- 120 dB WDR, 3D DNR, HLC, BLC
- Support up to 1000 m laser distance
- Up to 256 GB on-board storage
- H.265+/H.265
- IP66

DS-2DY9236IX-A

2MP 36× Network IR Positioning System



- 2MP 1/1.9" progressive scan CMOS
- DarkFighter ultra-low light technology
- 36× optical zoom, 16× digital zoom
- 120dB WDR, 3D DNR, HLC, BLC, smart IR
- Support up to 200 m IR distance
- Up to 256 GB on-board storage
- H.265+/H.265
- IP66

DS-2DY7236IW-A

2MP 36× Network IR Positioning System



- 2MP 1/1.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 36× optical zoom, 16× digital zoom
- 120 dB WDR, 3D DNR, HLC, BLC
- Support up to 150 m IR distance
- Up to 256 GB on-board storage
- H.265+/H.265
- IP66

DS-2DY9250X-A

2MP 50× Network Positioning System



- 2MP 1/2.8" progressive scan CMOS
- 50× optical zoom, 16× digital zoom
- 120 dB WDR, 3D DNR, HLC, BLC
- Up to 256 GB on-board storage
- H.265+/H.265
- IP66

DS-2DY9236X-A

2MP 36× Network Positioning System



- 2MP 1/1.9" progressive scan CMOS
- 36× optical zoom, 16× digital zoom
- 120 dB WDR, 3D DNR, HLC, BLC
- Up to 256 GB on-board storage
- H.265+/H.265
- IP66

DS-2DY7236W-A

2MP 36× Network Positioning System



- 2MP 1/1.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 36× optical zoom, 16× digital zoom
- 120 dB WDR, 3D DNR, HLC, BLC
- Up to 256 GB on-board storage
- H.265+/H.265
- IP66

DS-2DP1636ZIX-D/236(5mm)

PanoVu Series 360° Panoramic + PTZ Camera



- **Panoramic Camera**
- 8× 1/1.8" progressive scan CMOS
- Up to 2× 8MP resolution @30fps
- FOV: horizontal 360°, vertical: 80°
- DarkFighter ultra-low light technology
- **Tracking PTZ Camera**
- 2MP 1/1.8" progressive scan CMOS
- Pan and tilt range: 360° (Pan), -15° to 90° (Tilt)
- DarkFighter ultra-low light technology
- 36× Optical Zoom, 16× Digital Zoom
- IR distance: 200m

DS-2DP0818ZIX-D/236(5mm)

PanoVu Series 180° Panoramic + PTZ Camera



- **Panoramic Camera**
- Four 1/1.8" progressive scan CMOS
- Up to 8MP resolution @30fps
- FOV: horizontal 180°, vertical: 80°
- DarkFighter ultra-low light technology
- **Tracking PTZ Camera**
- 1/1.8" progressive scan CMOS
- Up to 2MP resolution @30fps
- 360° (Pan), -15° to 90° (Tilt)
- DarkFighter ultra-low light technology
- 36× Optical Zoom, 16× Digital Zoom
- IR distance: 200m

DS-2DP1636ZX-D/236(5mm)

PanoVu Series 360° Panoramic + PTZ Camera



- **Panoramic Camera**
- Eight 1/1.8" progressive scan CMOS
- Up to 2× 8MP resolution @30fps
- Horizontal field of view: 180°, vertical field of view: 80°
- DarkFighter ultra-low light technology
- **Tracking PTZ Camera**
- 1/1.8" progressive scan CMOS
- Up to 1920×1080 resolution @30fps
- Pan and tilt range: 360° (Pan), -15° to 90° (Tilt)
- DarkFighter ultra-low light technology
- 36× Optical Zoom, 16× Digital Zoom

DS-2DP0818ZX-D/236(5mm)

PanoVu Series 180° Panoramic + PTZ Camera



- **Panoramic Camera**
- Four 1/1.8" progressive scan CMOS
- Up to 8MP resolution @30fps
- Horizontal field of view: 180°, vertical field of view: 80°
- DarkFighter ultra-low light technology
- **Tracking PTZ Camera**
- 1/1.8" progressive scan CMOS
- Up to 2MP resolution @30fps
- Pan and tilt range: 360° (Pan), -15° to 90° (Tilt)
- DarkFighter ultra-low light technology
- 36× Optical Zoom, 16× Digital Zoom

DS-2DP1636-D

PanoVu series 360° Panoramic Camera



- 8 x 1/1.9" CMOS sensor, 2-ch
- 8MP realtime video output
- Horizontal angle of view: 360°, Vertical angle of view: 78°
- DarkFighter DarkFighter ultra-low light technology

iDS-2PT9122IX-DE/S (5-50mm) (4mm)

DeepInview Series 2MP + 2MP 10× Network PTZ Camera



- 8 x 1/1.9" CMOS sensor, 2-ch
- 8MP realtime video output
- Horizontal angle of view: 360°, Vertical angle of view: 78°
- DarkFighter DarkFighter ultra-low light technology

EasyIP 3.0 Series

DS-2DE7530IW-AE

5MP 30× Network IR Speed Dome



- 5MP 1/1.9" progressive scan CMOS
- DarkFighter ultra-low light technology
- 30× optical zoom, 16× digital zoom
- Defog, EIS, 3D DNR, BLC, HLC, Digital WDR
- IR distance up to 150 m
- H.265+/H.265

DS-2DE7420/7430IW-AE

4MP 20×/30× Network IR Speed Dome



- 4MP 1/1.9" progressive scan CMOS
- DarkFighter ultra-low light technology
- 20×/30× optical zoom, 16× digital zoom
- Defog, EIS, 3D DNR, BLC, HLC, digital WDR
- IR distance up to 150 m
- H.265+/H.265

DS-2DE7320/7330IW-AE

3MP 20×/30× Network IR Speed Dome



- 3MP 1/2.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 30×/20× optical zoom, 16× digital zoom
- 120dB WDR, HLC, BLC, 3D DNR, Defog, EIS, regional exposure, regional focus
- Up to 150 m IR distance
- H.265+/H.265

DS-2DE5225IW

2MP 25× Network IR Speed Dome



- 2MP 1/2.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 25× optical zoom, 16× digital zoom
- WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus
- H.265+/H.265

PTZ DOME CAMERA

DS-2DE4A320IW-DE
3MP 20x Network IR PTZ Camera



- 3MP 1/2.8" progressive scan CMOS
- 20× Optical Zoom, 16× Digital Zoom
- WDR, 3D DNR, HLC, smart IR
- Up to 50 m IR distance
- H.265

DS-2DE4A215/225IW-DE
2MP 15x/25x Network IR PTZ Camera



- 2MP 1/2.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 15×/25× optical zoom, 16× digital zoom
- 120 dB WDR, 3D DNR, HLC, BLC, smart IR
- Up to 50 m IR distance
- H.265+/H.265

DS-2DE4A204IW-DE
2MP 4x Network IR PTZ Camera



- 2MP 1/1.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 4× optical zoom, 16× digital zoom
- Digital Defog, EIS, 3D DNR, BLC, HLC, WDR
- Up to 50 m IR distance
- H.265+/H.265

DS-2DE5320/5330W-AE(3)
3MP 20×/30× Network Speed Dome



- 3MP 1/2.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 20×/30× optical zoom, 16× digital zoom
- WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus
- H.265+/H.265

DS-2DE4215/4220/4225IW-DE
2MP 15×/20×/25× Network Speed Dome



- 2MP 1/2.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 15×20×/25× optical zoom, 16× digital zoom
- WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus
- Up to 100 m IR distance
- H.265+/H.265

DS-2DE4225W-DE(3)
2 MP 25× Network Speed Dome



- 2MP 1/2.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 25× optical zoom, 16× digital zoom
- WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus
- H.265+/H.265

DS-2DE4215W-DE3
2 MP 15× Network Speed Dome



- 2MP 1/2.8" progressive scan CMOS
- DarkFighter ultra-low light technology
- 15× optical zoom, 16× digital zoom
- WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus
- H.265+/H.265

DS-2DE4220W-AE(3)
2 MP 25× Network Speed Dome



- 2MP 1/2.8" progressive scan CMOS
- 20X Zoom
- DWDR
- 3D Positioning
- Hik-Connect
- IP66

DS-2DE3204/3304W-DE
2MP/3MP Network Mini PTZ Dome Camera



- 2MP/3MP 1/2.8" progressive scan CMOS
- 4X Optical Zoom
- Digital WDR
- Support IP67/IK10
- PoE(802.3af)
- Support RS485
- Support plug & play

DS-2DE2204IW-DE3
2MP Network IR Mini PTZ Camera



- 2MP 1/2.8" progressive scan CMOS
- 4x Zoom
- Digital WDR
- 3D positioning
- Hik-Connect
- Up to 20m IR distance
- H.265+/H.265

DS-2PT3326IZ-DE3 (2.8-12mm)
PanoVu Mini Series Network PTZ Camera



- 3-ch panoramic images in different directions and 1-ch close-up image
- Panoramic Camera**
- 3× 2MP 1/2.8" progressive scan CMOS
- H.265
- Horizontal FOV: 128.5°×3
- PTZ Camera**
- 2MP 1/2.8" progressive scan CMOS
- H.265
- 4× optical zoom, 8× digital zoom

DS-2PT3122IZ-DE3 (2.8-12mm)
PanoVu Mini Series Network PTZ Camera



- 1-ch panoramic images in different directions and 1-ch close-up image
- Support PTZ linkage
- Panoramic Camera**
- 2MP 1/2.8" progressive scan CMOS
- H.265
- Horizontal FOV: 128.5°
- PTZ Camera**
- 2MP 1/2.8" progressive scan CMOS
- H.265
- 4× optical zoom, 8× digital zoom

NETWORK CAMERA

HIKVISION

PanoVu Camera

DS-2CD6A64F
24MP PanoVu Network Camera



- DarkFighter ultra-low light technology
- 24MP (4×6MP) resolution, 5.5mm fixed lens
- Panorama monitoring
- H.265+
- 50m wide-angle IR
- IP66
- 1+5 multi-window

DS-2CD6924F
8MP PanoVu Network Camera



- DarkFighter ultra-low light technology
- 180° horizontal panoramic monitoring
- DarkFighter lens
- 4/6mm lens optical
- 4mm lens (F1.8) H.265+ and 6mm H.265
- 0-90° tilt adjustment
- 8MP (4×2MP)
- IR 30m
- IP66, IK10

DS-2CD6986F
8MP PanoVu Network Camera



- DarkFighter ultra-low light technology
- 4×1/1.8" progressive CMOS
- 4×5mm fixed lens
- 180° horizontal view
- Digital WDR, 3D DNR, defog
- Audio/alarm ID
- ROI codec
- Up to 128GB on-board storage
- Full smart feature-set
- IP66

DS-2CD6D54FWD
20MP PanoVu Vari-Focal Network Camera



- 4×1/2.7" progressive scan CMOS
- 4×5MP @ 30fps
- FOV: horizontal 31° to 108°, vertical 22.5° to 74.4°
- H.265, H.264
- Fiber optic transmission
- 10 m to 30 m IR range
- 4×2.8-12mm flexible VF lens
- 6 behavior analyses, 4 exception detection, and face detection

DeepinView Camera

DS-2CD6D24FWD
8MP PanoVu Vari-Focal Network Camera



- 4×1/2.7" progressive scan CMOS
- 4×2MP @ 30fps
- FOV: horizontal 31° to 108°, vertical 22.5° to 74.4°
- H.265, H.264
- Fiber optic transmission
- 10 m to 30 m IR range
- 4×2.8-12mm flexible VF lens
- 6 behavior analyses, 4 exception detection, and face detection

iDS-2CD6810D
1.3MP Dual-Lens People Counting Camera



- Separate counts of people entering, exiting, and passing by
- Max. 640×960 @25fps
- Baseline Profile/Main Profile H.264 encoding complexity
- Micro SD/SDHC/SDXC card (128G)
- ANR
- Alarm I/O, triggered by disconnected network, IP address conflict, illegal login, HDD full, HDD error
- DC 12 ± 25%VSPoE

iDS-2CD6810F-IV
1.3MP Dual-Lens People Counting Camera



- Separate counting of people entering, exiting, and passing by
- Max. 640×960 @25fps
- Baseline Profile/Main Profile H.264 encoding complexity
- Micro SD/SDHC/SDXC card (128G)
- ANR
- Alarm I/O, triggered by disconnected network, IP address conflict, illegal login, HDD full, HDD error
- DC 12 ± 25%VSPoE
- IP67

DS-2CD702660
2MP DeepinView Box Network Camera



- 1/1.8" CMOS; 120db WDR
- Color:0.002Lux/F1.2,BW:0.0002Lux/F1.2
- Audio; 2 alarm in, 2 alarm out
- RS485
- DC 12V out
- 5 streams
- ABF/P-iris (optional)
- Improved perimeter detection
- Object target capture

DS-2CD712660
2MP DeepinView Dome Network Camera



- 1/1.8" CMOS
- 120db WDR
- Color: 0.002Lux/F1.2; BW: 0.0002Lux/F1.2
- Audio;1 Alarm I/O, RS485
- DC 12V out
- 5 streams
- Improved perimeter detection
- Object target capture
- Socket-style interfaces

DS-2CD712660/L
2MP DeepinView Dome Network Camera



- 1/1.8" CMOS; 120db WDR
- Color: 0.002Lux/F1.2; BW: 0.0002 Lux/F1.2
- Audio, 1 alarm/I/O, RS485
- DC 12V out
- 5 streams
- Queue manage (L model)

DS-2CD7A2660
2MP DeepinView Bullet Network Camera



- 1/1.8" CMOS; 120db WDR
- Color: 0.002Lux/F1.2; BW: 0.0002Lux/F1.2
- 2 alarm I/O
- Socket-style interfaces
- 10 streams
- Built-in heater (H model optional)
- Improved perimeter detection
- Object target capture

Smart IP 3.0 Series

iDS-2CD842660/B
2MP Dual-Lens Behavioral Analysis Network Camera



- 1/2.8" progressive scan CMOS
- 1920×1080 @ 30fps
- H.265+, H.265, H.264+, H.264
- 5 video streams
- 120dB WDR
- IR range up to 10 m
- Behavioral analysis

iDS-2CD862660/P
2MP ANPR Bullet Network Camera



- 1/1.8" progressive scan CMOS
- 1920×1080 @ 60fps
- H.265+, H.265, H.264+, H.264
- 120dB WDR
- IR range up to 120 m
- 5 video streams, 2 alarm I/O, 1 RS485
- Vehicle detection (Based on deep learning algorithm)
- NEMA 4X (P model)
- IP66

DS-2CD502860/E
DarkFighterX 2MP Outdoor Smart Camera



- DarkFighterX technology
- Dual sensor 1/2.8"CMOS progressive scan CMOS
- 1080P 25fps/30fps
- H.265+/H.265/ H.264+/H.264/MJPEG
- 100m IR
- 120dB WDR
- 3 streams
- Optimized VCA

DS-2CD502660
2MP Ultra-Low Light Smart Network Box Camera



- DarkFighter ultra-low light technology
- 1/1.8"CMOS, 1080P 25fps/30fps
- Up to 50fps/60fps
- H.265+/H.265/H.264+/H.264
- 120dB WDR
- Up to 256 GB on-board storage
- ABF/P-iris (optional)
- 2× alarm I/O
- RS485, 5 streams

NETWORK CAMERA

DS-2CD504660
4MP Ultra-Low Light Smart Network Box Camera



- DarkFighter ultra-low light technology, Color:0.009Lux/F1.2; BW:0.0009Lux/F1.2;
- 1/1.8"CMOS; 4MP
- H.265+/H.265/H.264+/H.264
- 120dB WDR
- Audio
- (-AP:ABF;P-IRIS;)
- 2× Alarm I/O;
- RS485

DS-2CD508560
8 MP Smart Network Box Camera



- Color:0.009Lux/F1.2;BW:0.0009Lux/F1.2
- 8MP
- 1/1.8"CMOS
- H.265+/H.265/H.264+/H.264,
- 120dB WDR
- Audio
- (-AP:ABF;P-IRIS;)
- 2× alarm I/O
- RS485
- 5 streams

DS-2CD512660
2MP Vari-Focal Dome Network Camera



- DarkFighter ultra-low light technology, H.265+/H.265/H.264+/H.264
- Color:0.002Lux/F1.2, BW:0.0002Lux/F1.2
- 1/1.8"CMOS
- 1080P 25fps/30fps, up to 50fps/60fps;
- 2.8-12mm Motorized VF lens
- 120dB WDR; Socket-style interfaces;
- Audio, 1 Alarm I/O
- RS485

DS-2CD514660
4MP Vari-Focal Dome Network Camera



- DarkFighter ultra-low light technology
- H.265+/H.265/H.264+/H.264
- Color:0.009Lux/F1.2, BW:0.0009Lux/F1.2
- 1/1.8"CMOS;
- 4MP 2.8-12mm Motorized VF lens,120dB WDR
- Socket-style interfaces;
- Audio, 1 alarm I/O
- RS485
- 5 streams

DS-2CD518560
8MP Vari-Focal Dome Network Camera



- H.265+/H.265/H.264+/H.264
- Color:0.009Lux/F1.2, BW:0.0009Lux/F1.2;
- 1/1.8"CMOS
- 8MP, 2.8-12mm Motorized VF lens
- 120dB WDR
- Audio
- Socket-style interfaces
- Audio, 1 alarm I/O
- RS485
- 5 streams

DS-2CD5A2660
2MP Vari-Focal Bullet Network Camera



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS
- ICR
- Color: 0.002Lux/F1.2, B/W:0.0002Lux/F1.2
- slow shutter, 1920 x 1080, up to 50fps/60fps: H.265+/H.265/H.264+/H.264
- 120dB WDR
- 2 alarm I/O
- Socket-style interfaces
- 5streams
- Built-in Heater (-H models)

DS-2CD5A4660
4MP Vari-Focal Bullet Network Camera



- DarkFighter ultra-low light technology, 1/1.8" progressive scan CMOS, ICR, Color:0.009Lux/F1.2× alarm I/O
- Socket-style interfaces; 5 streams;
- Built-in heater (-H models)

DS-2CD5A8560
8MP Vari-Focal Bullet Network Camera



- 1/1.8" progressive scan CMOS, ICR, Color:0.009Lux/F1.2× alarm I/O
- Socket-style interfaces; 5 streams;Built-in heater (-H models)

DS-2CD552660
2MP Vari-Focal Dome Network Camera



- DarkFighter ultra-low light technology
- 1/1.8" progressive scan CMOS, ICR, Color:0.002Lux/F1.2, B/W:0.0002Lux/F1.2
- slow shutter, 1920 x 1080, up to 50fps/60fps: H.265+/H.265/H.264+/H.264
- 120dB WDR
- 1× alarm I/O
- Socket-style interfaces
- 5 streams
- Built-in heater (-H models)

EasyIP 3.0

DS-2CD2085FWD-I
8MP EXIR Mini Bullet network camera



- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2055FWD-I
5MP EXIR Mini Bullet network camera



- SMP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2035FWD-I
3MP EXIR Mini Bullet network camera



- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2025F(H)WD
2MP EXIR Mini Bullet Network Camera



- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- DarkFighter technology
- 25fps/30fps(1920×1080)
- VCA functions
- 3 streams
- Up to 30m IR
- Built-in micro SD/SDHC/SDXC slot;
- Hik-Connect cloud service
- *FHW model: 50fps/60fps(1920×1080)

NETWORK CAMERA

HIKVISION

DS-2CD2185FWD-I(S)
8MP EXIR Dome network camera



- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67, IK10
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2155FWD-I(S)
5MP EXIR Dome network camera



- 5MP high resolution
- H.265+/H.265/H.264+/H.264
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67, IK10
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2135FWD-I(S)
3MP EXIR Dome network camera



- 3MP high resolution
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67, IK10
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2125F(H)WD
2MP EXIR Dome Network Camera



- 2MP high resolution
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR; IP67, IK10
- 3 streams
- *-S model: Audio/Alarm I/O
- *FHW model: 50fps/60fps(1920×1080)

DS-2CD2385FWD-I
8MP EXIR Turret network camera



- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2355FWD-I
5MP EXIR Turret network camera



- 5MP high resolution
- H.265+/H.265/H.264+/H.264
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2335FWD-I
3MP EXIR Turret network camera



- 3MP high resolution
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2325F(H)WD
2MP EXIR Turret Network Camera



- 2MP high resolution
- H.265+/H.265+/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR, 3 streams
- IP67
- Hik-Connect cloud service
- Up to 128GB on-board storage
- *FHW model: 50fps/60fps (1920×1080)

DS-2CD2T85FWD-I(S/8)
8MP EXIR Bullet network camera



- 4K Ultra-HD
- H.265+/H.265/H.264+/H.264
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams
- IS: up to 50 m; IS: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T55FWD-I(S/8)
5MP EXIR Bullet Network Camera



- 5MP high resolution
- H.265+/H.265/H.264+/H.264
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams
- IS: up to 50 m; IS: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T35FWD-I(S/8)
3MP EXIR Bullet Network Camera



- 3MP high resolution
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams
- IS: up to 50 m; IS: up to 80 m
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2T25F(H)WD
2MP EXIR Bullet Network Camera



- 2MP high resolution
- H.265+/H.265/H.264+/H.264
- DarkFighter ultra-low light technology
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR, IP67
- 3 streams
- Up to 128GB on-board storage
- *-IS/IS model: up to 50m/80m IR
- *FHW model: 50fps/60fps(1920×1080)

DS-2CD2455FWD
5MP EXIR Bullet Network Camera



- 5MP high resolution
- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG;
- Color: 0.01 lux@F1.2, AGC ON), 0 lux with IR
- VCA functions
- 3 streams
- Up to 30m IR
- Built-in micro SD/SDHC/SDXC slot;
- Hik-Connect cloud service
- Built-in Wi-Fi (-W model)

DS-2CD2435FWD
3MP EXIR Bullet Network Camera



- 3MP high resolution
- 1/2.8" progressive scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG;
- DarkFighter technology
- VCA functions
- 3 streams; 3D DNR; BLC; ICR
- EXIR 2.0, up to 10m
- Built-in mic & speaker
- Built-in micro SD/SDHC/SDXC slot
- Hik-Connect cloud service
- *Built-in Wi-Fi (-W model)

DS-2CD2425FWD
2MP EXIR Bullet Network Camera



- 2MP high resolution
- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- DarkFighter technology
- 25fps/30fps(1920×1080)
- VCA functions
- 3 streams
- EXIR 2.0, up to 10m
- Built-in mic & speaker
- Hik-Connect cloud service
- *Built-in Wi-Fi (-W model)

DS-2CD2555FWD
5MP EXIR Dome Network Camera



- SMP high resolution
- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- VCA functions
- 3 streams
- Up to 10m IR
- Hik-Connect cloud service
- Built-in mic, audio/alarm I/O (-S models)
- Built-in Wi-Fi (-W model)

NETWORK CAMERA

DS-2CD2535FWD

3MP EXIR Dome Network Camera



- 3MP high resolution
- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG;
- DarkFighter technology
- VCA functions
- 3 streams
- up to 10m IR
- Hik-Connect cloud service
- Built-in mic, Audio/Alarm I/O [-S models]
- Built-in Wi-Fi [-W model]

DS-2CD2635FWD-IZS

3MP Vari-focal EXIR Bullet Network Camera



- 3MP high resolution; H.265+/H.265/H.264+/H.2643 streams;
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67, IK10
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2735FWD-IZS

3MP Vari-focal EXIR Dome Network Camera



- 3MP high resolution; H.265+/H.265/H.264+/H.2643 streams
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67, IK10
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H35FWD-IZS

3MP Vari-focal EXIR Turret Network Camera



- 3MP high resolution; H.265+/H.265/H.264+/H.2643 streams;
- 2.8-12mm motorized VF lens
- DarkFighter ultra-low light technology
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2525F(H)WD

2MP EXIR Dome Network Camera



- 2MP high resolution
- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- DarkFighter technology
- VCA functions
- 3 streams
- up to 10m IR
- Built-in Hik-Connect cloud service
- Built-in mic, Audio/Alarm I/O [-S models]
- Built-in Wi-Fi [-W model]

DS-2CD2625F(H)WD

2MP Vari-focal EXIR Bullet Network Camera



- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG;
- DarkFighter technology
- VCA functions
- 3 streams
- Up to 50m infrared
- Built-in audio/alarm I/O
- Hik-Connect cloud service

DS-2CD2725F(H)WD

2MP Vari-focal EXIR Dome Network Camera



- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG;
- DarkFighter technology,Color: 0.005 lux @F1.2, AGC ON, 0 lux with IR
- 25fps/30fps[1920×1080]
- VCA functions
- 3 streams
- 3D DNR; BLC; ICR; EXIR 2.0, up to 30m
- Built-in Audio/Alarm I/O
- Hik-Connect cloud service
- *FHW model: 50fps/60fps[1920×1080]

DS-2CD2H25F(H)WD

2MP Vari-focal EXIR Turret Network Camera



- 1/2.8" progressive scan CMOS;
- H.265+/H.265/H.264+/H.264/MJPEG;
- DarkFighter technology,Color: 0.005 lux @F1.2, AGC ON, 0 lux with IR;
- Intrusion/line crossing/object removal/unattended baggage/face detection
- VCA functions
- 3 streams
- 3D DNR; BLC; ICR
- EXIR 2.0, up to 30m
- Built-in Audio/Alarm I/O
- Hik-Connect cloud service
- *FHW model: 50fps/60fps[1920×1080]

DS-2CD2685FWD-IZS

8MP Vari-focal EXIR Bullet Network Camera



- 4K HD;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67, IK10
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2785FWD-IZS

8MP Vari-focal EXIR Dome Network Camera



- 4K HD;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67, IK10
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H85FWD-IZS

8MP Vari-focal EXIR Turret Network Camera



- 4K HD
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2955FWD-I(S)

5MP EXIR Fisheye Network Camera



- 5MP high resolution
- H.265+/H.265/H.264+/H.264
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 1.05 mm @ F2.2, horizontal field of view: 180°, vertical field of view: 180°
- 120dB WDR
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2655FWD-IZS

5MP Vari-focal EXIR Bullet Network Camera



- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67, IK10
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2755FWD-IZS

5MP Vari-focal EXIR Dome Network Camera



- 5MP high resolution;
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67, IK10
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2H55FWD-IZS

5MP Vari-focal EXIR Turret Network Camera



- 5MP high resolution
- H.265+/H.265/H.264+/H.264
- 2.8-12mm motorized VF lens
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 120dB WDR
- IP67
- 3 streams;
- Hik-Connect Service
- Up to 128GB on-board storage

DS-2CD2935FWD-I(S)

3MP EXIR Fisheye Network Camera



- 3MP high resolution;
- H.265+/H.265/H.264+/H.264
- Intrusion/line crossing/object removal/unattended baggage/face detection
- 1.16 mm @ F2.2, horizontal field of view: 180°, vertical field of view: 180°
- 120dB WDR
- 3 streams
- Hik-Connect Service
- Up to 128GB on-board storage

NETWORK CAMERA

EasyIP 2.0 Plus Series

DS-2CD208360

8MP IR Fixed Bullet Network Camera



- 1/2.5" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- EXIR 2.0, up to 30m
- IP67
- Up to 128 GB built-in storage
- Hik-Connect cloud service

DS-2CD218360

8MP IR Fixed Dome Network Camera



- 1/2.5" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- EXIR 2.0, up to 30m
- IP67, IK10
- Hik-Connect cloud service
- *-S model: Audio/Alarm IO

DS-2CD238360

8MP IR Fixed Turret Network Camera



- 1/2.5" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- 3D DNR; ICR
- EXIR, up to 30m
- IP67
- Hik-Connect cloud service

DS-2CD2T8360

8MP IR Fixed Bullet Network Camera



- 1/2.5" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR, 3D DNR, ICR
- EXIR, up to 30m
- IP67
- Hik-Connect cloud service
- *-IS/I8 model: up to 50m/80m IR distance

DS-2CD206360

6MP IR Fixed Bullet Network Camera



- 1/2.9" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- EXIR 2.0, up to 30m
- IP67
- Up to 128 GB built-in storage
- Hik-Connect cloud service

DS-2CD216360

6MP IR Fixed Dome Network Camera



- 1/2.9" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- EXIR 2.0, up to 30m
- IP67, IK10
- Hik-Connect cloud service
- *-S model: Audio/Alarm IO

DS-2CD236360

6MP IR Fixed Turret Network Camera



- 1/2.9" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- 3D DNR; ICR
- EXIR, up to 30m
- IP67
- Hik-Connect cloud service

DS-2CD2T6360

6MP IR Fixed Bullet Network Camera



- 1/2.9" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR, 3D DNR, ICR
- EXIR, up to 30m
- IP67
- Hik-Connect cloud service
- *-IS/I8 model: up to 50m/80m IR distance

DS-2CD204360

4MP IR Fixed Bullet Network Camera



- 1/3" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- EXIR 2.0, up to 30m
- IP67
- Up to 128 GB built-in storage
- Hik-Connect cloud service

DS-2CD214360

4MP IR Fixed Dome Network Camera



- 1/3" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- EXIR 2.0, up to 30m
- IP67, IK10
- Hik-Connect cloud service
- *-S model: Audio/Alarm IO

DS-2CD234360

4MP IR Fixed Turret Network Camera



- 1/3" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- 3D DNR; ICR
- EXIR, up to 30m
- IP67
- Hik-Connect cloud service

DS-2CD2T4360

4MP IR Fixed Bullet Network Camera



- 1/3" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR, 3D DNR, ICR
- EXIR, up to 30m
- IP67
- Hik-Connect cloud service
- *-IS/I8 model: up to 50m/80m IR distance

DS-2CD202360

2MP IR Fixed Bullet Network Camera



- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- EXIR 2.0 up, to 30m
- IP67
- Up to 128 GB built-in storage
- Hik-Connect cloud service

DS-2CD212360

2MP IR Fixed Dome Network Camera



- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- EXIR 2.0, up to 30m
- IP67, IK10
- Hik-Connect cloud service
- *-S model: Audio/Alarm IO

DS-2CD232360

2MP IR Fixed Turret Network Camera



- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR
- 3D DNR; ICR
- EXIR, up to 30m
- IP67
- Hik-Connect cloud service

DS-2CD2T2360

2MP IR Fixed Bullet Network Camera



- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- Line crossing detection, intrusion detection, face detection
- 3 streams
- 120dB WDR, 3D DNR, ICR
- EXIR, up to 30m
- IP67
- Hik-Connect cloud service
- *-IS/I8 model: up to 50m/80m IR distance

NETWORK CAMERA

DS-2CD268360
8MP IR Vari-Focal Bullet Network Camera



- 1/2.5" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- 3 VCA functions
- 3 streams
- 3D DNR
- ICR
- EXIR, up to 30m
- Hik-Connect cloud service

DS-2CD266360
6MP IR Vari-Focal Bullet Network Camera



- 1/2.9" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- 3 VCA functions
- 3 streams
- 3D DNR; ICR
- EXIR, up to 50m
- Hik-Connect cloud service

DS-2CD264360
4MP IR Vari-Focal Bullet Network Camera



- 1/3" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- 3 VCA functions
- 3 streams
- 3D DNR; ICR
- EXIR, up to 50m
- Hik-Connect cloud service

DS-2CD262360
2MP IR Vari-Focal Bullet Network Camera



- 1/2.8" progressive scan CMOS;
- H.265+/H.265/H.264+/H.264/MJPEG;
- Visible: 384×288@50fps
- 3 VCA functions
- 3 streams
- up to 50m
- Hik-Connect cloud service

DS-2CD278360
8MP IR Vari-Focal Dome Network Camera



- 1/2.5" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- 3 VCA functions
- 3 streams
- 3D DNR
- ICR
- EXIR, up to 30m
- Hik-Connect cloud service

DS-2CD276360
6MP IR Vari-Focal Dome Network Camera



- 1/2.9" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- 3 VCA functions
- 3 streams
- IR up to 30m
- Hik-Connect cloud service

DS-2CD274360
4MP IR Vari-Focal Dome Network Camera



- 1/3" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- 3 VCA functions
- 3 streams
- IR up to 30m
- Hik-Connect cloud service

DS-2CD272360
2MP IR Vari-Focal Dome Network Camera



- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- 3 VCA functions
- 3 streams
- IR up to 10m
- Hik-Connect cloud service

DS-2CD2H8360
8MP IR Vari-Focal Turret Network Camera



- 1/2.5" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- 3 VCA functions
- 3 streams
- IR up to 30m
- Hik-Connect cloud service

DS-2CD2H6360
6MP IR Vari-Focal Turret Network Camera



- 1/2.9" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG;
- 3 VCA functions; 3 streams
- IR up to 30m
- Hik-Connect cloud service

DS-2CD2H4360
4MP IR Vari-Focal Turret Network Camera



- 1/3" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- 3 VCA functions
- 3 streams
- IR up to 30m
- Hik-Connect cloud service

DS-2CD2H2360
2MP IR Vari-Focal Turret Network Camera



- 1/2.8" progressive scan CMOS
- H.265+/H.265/H.264+/H.264/MJPEG
- 3 VCA functions
- 3 streams
- IR up to 30m
- Hik-Connect cloud service

THERMAL CAMERA

HIKVISION

DS-2TD2136-7/10/15/25/35
Thermal Network Bullet Camera



- Thermal: 384×288 17um
- 7mm/10mm/15mm/25mm/35mm
- Visible: 384×288@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~150°C, Temperature accuracy: ±8°C)
- Working temperature: -40 °C to 65 °C (-40 °F to 149 °F)
- IP66

DS-2TD2166-7/15/25/35
Thermal Network Bullet Camera



- Thermal: 640×512 17um;
- 7mm/15mm/25mm/35mm
- Visible: 640×512@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~150°C, temperature accuracy: ±8°C)
- Working temperature: -40 °C to 65 °C (-40 °F to 149 °F)
- IP66

DS-2TD2336-50/75/100
Thermal Network Bullet Camera



- Thermal: 384×288 17um
- 50mm/75mm/100mm
- Visible: 384×288@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~150°C, temperature accuracy: ±8°C)
- Working temperature: -40 °C to 65 °C (-40 °F to 149 °F)
- IP66

DS-2TD2366-50/75/100
Thermal Network Bullet Camera



- Thermal: 640×512 17um
- 50mm/75mm/100mm
- Visible: 640×512@50fps;
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~150°C, temperature accuracy: ±8°C)
- Working temperature: -40 °C to 65 °C (-40 °F to 149 °F)
- IP66

DS-2TD2136T-10/15/25
Thermal Network Bullet Camera



- Thermal: 384×288 17um
- 10mm/15mm/25mm
- Visible: 640×512@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~550°C, temperature accuracy: max (±2 °C, ±2%)
- Working temperature: -40 °C to 65 °C (-40 °F to 149 °F)
- IP66

DS-2TD2166T-15/25
Thermal Network Bullet Camera



- Thermal: 640×512 17um
- 15mm/25mm
- Visible: 640×512@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~550°C, temperature accuracy: max (±2 °C, ±2%)
- Working temperature: -40 °C to 65 °C (-40 °F to 149 °F)
- IP66

DS-2TD2466-25Y/50Y
Anti-corrosion Thermal Network Bullet Camera



- Thermal: 640×512 17um
- Thermal lens: 25mm/50mm
- Visible: 640×512@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~150°C, Temperature accuracy: ±8°C)
- Working temperature: -40 °C to 65 °C (-40 °F to 149 °F)
- IP66
- 316L stainless steel material for anti-corrosion environment

DS-2TD2466-9/25X
Explosion-Proof Thermal Network Bullet Camera



- Thermal: 640×512 17um
- Thermal lens: 9mm/25mm
- Visible: 640×512@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~150°C, Temperature accuracy: ±8°C)
- Working temperature: -40 °C to 65 °C (-40 °F to 149 °F)
- IP66
- 316L stainless steel material for explosion-proof environment

DS-2TD2615-7/10
Thermal Bi-spectrum Network Bullet Camera



- Thermal: 160×120 (output image: 320×240), 25um
- Visible: 1920×1080
- Thermal: 7mm/10mm, Visible: 6mm/8mm
- Visible: 320×240@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~150°C, Temperature accuracy: ±8°C)
- Bi-spectrum image fusion, picture in picture preview
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP67

DS-2TD2636-10/15
Thermal Bi-spectrum Network Bullet Camera



- Thermal: 384×288 17um, Visible: 1920×1080
- Thermal: 10mm/15mm, Visible: 6mm/8mm
- Visible: 384×288@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~150°C, Temperature accuracy: ±8°C)
- Bi-spectrum image fusion, picture in picture preview
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP67

DS-2TD2836-25/50
Thermal & Optical Bi-spectrum Network Bullet



- Thermal: 384×288, 17um, Visible: 1920×1080
- Thermal: 25mm/50mm, Visible: 13mm/25mm
- Visible: 384×288@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~150°C, Temperature accuracy: ±8°C)
- Bi-spectrum image fusion, picture in picture preview
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

DS-2TD2866-25/50
Thermal & Optical Bi-spectrum Network Bullet



- Thermal: 640×512, 17um, Visible: 1920×1080
- Thermal: 25mm/50mm, Visible: 13mm/25mm
- Visible: 640×512@50fps
- Line crossing, intrusion detection, region entrance, region exiting
- Fire detection
- Temperature exception (temperature measuring range: -20~150°C, Temperature accuracy: ±8°C)
- Bi-spectrum image fusion, picture in picture preview
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

THERMAL CAMERA

DS-2TD4136-25/50

Thermal Speed Dome



- Thermal: 384×288 17um, Visible: 1920×1080;
- Thermal: 25mm/50mm, Visible: 5.7-205.2mm
- 384×288@50fps;
- Fire detection
- Temperature exception (temperature measuring range: -20-150°C, Temperature accuracy: ±8°C)
- Line crossing/Intrusion detection/Region entrance/Region exiting/Smart tracking linkage (Thermal + Visible)
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

DS-2TD4136T-9/25

Thermal Speed Dome



- Thermal: 384×288 17um, Visible: 1920×1080;
- Thermal: 9mm/25mm, Visible: 5.7-205.2mm
- 384×288@50fps;
- Fire detection
- Temperature exception (temperature measuring range: -20-550°C, Temperature accuracy: Max (±2 °C, ±2%))
- Line crossing/Intrusion detection/Region entrance/Region exiting/Smart tracking linkage (Thermal + Visible)
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

DS-2TD4166-25/50

Thermal Speed Dome



- Thermal: 640×512 17um, Visible: 1920×1080
- Thermal: 25mm/50mm, Visible: 5.7-205.2mm
- 640×512@50fps
- Fire detection
- Temperature exception (temperature measuring range: -20-150°C, Temperature accuracy: ±8°C)
- Line crossing/Intrusion detection/Region entrance/Region exiting/Smart tracking linkage (Thermal + Visible)
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

DS-2TD4166T-9/25

Thermal Speed Dome



- Thermal: 640×512 17um, Visible: 1920×1080
- Thermal: 9mm/ 25mm, Visible: 5.7-205.2mm
- 640×512@50fps
- Fire detection
- Temperature exception (temperature measuring range: -20-550°C, Temperature accuracy: Max (±2 °C, ±2%))
- Line crossing/Intrusion detection/Region entrance/Region exiting/Smart tracking linkage (Thermal + Visible)
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

DS-2TX3636-15/25/35A(P)

Thermal smart linkage Tracking System



- Thermal: 384×288 17um, Visible: 1920×1080
- Thermal: 15mm/25mm/35mm, Visible: 5.7-205.2mm
- 384×288@50fps
- Line crossing/Intrusion detection/smart linkage Tracking System (Thermal + Visible)
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

DS-2TD6236-50H2L/75C2L

Thermometric Positioning System



- Thermal: 384×288 17um, Visible: 1920×1080
- Thermal: 50mm/75mm, Visible: H(5.6-208mm) /C(6.7-330mm)
- 384×288@50fps
- Line crossing/Intrusion detection/Region entrance/Region exiting/Smart tracking linkage (Thermal + Visible)
- Fire detection
- Temperature exception (temperature measuring range: -20-150°C, Temperature accuracy: ±8°C)
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

DS-2TD6236T-25H2L/50H2L

Thermometric Positioning System



- Thermal: 384×288 17um, Visible: 1920×1080
- Thermal: 25mm/50mm, Visible: H(5.6-208mm)
- 384×288@50fps
- Line crossing/Intrusion detection/Region entrance/Region exiting/Smart tracking linkage (Thermal + Visible)
- Fire detection
- Temperature exception (temperature measuring range: -20-550°C, Temperature accuracy: Max (±2 °C, ±2%))
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

DS-2TD6266-50H2L/75C2L/100C2L

Thermometric Positioning System



- Thermal: 640×512 17um, Visible: 1920×1080
- Thermal: 50mm/75mm/100mm, Visible: H(5.6-208mm) /C(6.7-330mm)
- 640×512@50fps
- Line crossing/Intrusion detection/Region entrance/Region exiting/Smart tracking linkage (Thermal + Visible)
- Fire detection
- Temperature exception (temperature measuring range: -20-150°C, Temperature accuracy: ±8°C)
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

DS-2TD6266T-25H2L/50H2L

Thermometric Positioning System



- Thermal: 640×512 17um, Visible: 1920×1080
- Thermal: 25mm/50mm, Visible: H(5.6-208mm)
- 640×512@50fps
- Line crossing/Intrusion detection/Region entrance/Region exiting/Smart tracking linkage (Thermal + Visible)
- Fire detection
- Temperature exception (temperature measuring range: -20-550°C, Temperature accuracy: Max (±2 °C, ±2%))
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F)
- IP66

DS-2TD8166-75/100C2F

DS-2TD8166-150/180ZE2F

Thermometric Stable PTZ Camera



- Thermal: 640×512 17um, Visible: 1920×1080
- Thermal: 75mm/100mm/30-150mm/45-180mm, Visible: C(6.7-330mm)/ E(12.5-775mm)
- 640×512@50fps
- Line crossing/Intrusion detection/Region entrance/Region exiting/Smart tracking linkage (Thermal + Visible)
- Fire detection
- Working temperature: -40 °C to 60 °C (-40 °F to 140 °F);
- IP66

DS-2TA03-15VI

Thermographic Automation Thermal Camera



- 384×288 17um
- 15mm
- 384×288@50fps
- Temperature measurement: -20 °C to 550 °C;Temperature accuracy: Max (±2°C, ±2%)
- Dimension Size: 120×60×60 mm
- Ethernet: Gigabit Ethernet
- Working temperature: -20 °C to 50 °C (-4 °F to 122°F)

DS-2TA13-6VI/H1

Thermographic Body Temperature Measurement Thermal Camera (with Black Body)



- Thermal: 384×288 17um, Visible: 1280*960
- Thermal: 6mm, Visible: 5mm
- 384×288@50fps
- Temperature measurement: 0 °C to 60 °C;Temperature accuracy: ±0.3°C
- Working temperature: -20 °C to 50 °C (-4 °F to 122°F)

THERMAL CAMERA

HIKVISION

DS-2TP03-15VM/W

Handheld Thermography Camera



- Resolution: 384×288 (thermal), 1080P (optical)
- Digital detail enhancement (DDE) technology
- 3D DNR, adaptive AGC (Automatic Gain Control)
- 3.6-inch LCD capacitive touch panel 320×240
- Temperature measurement: -20 °C to 650 °C
- Wi-Fi
- IP66
- Up to 5 hours continuous running

DS-2TS03-25UM/W

Handheld Observational Thermal Camera



- 384×288 resolution; 17um; 25mm
- Digital detail enhancement (DDE) technology
- Up to 16G built-in SD card
- 0.39-inch OLED display
- Working temperature:-20 °C to 55 °C (-4 °F to 131 °F)
- Hot track, Wi-Fi, Ranging, GPS
- IP67
- Up to 5 hours continuous running (GPS & WiFi off)

DS-2TS16-38VI

Handheld Thermal & Optical Bi-spectrum Binocular



- Therml: 640×512 17um, Visible: 800×600
- Thermal: 38mm, Visible: 40mm
- 0.39-inch OLED display, 32G
- Working temperature:-40 °C to 55 °C(-40 °F to 131 °F);
- Video recording, replay, picture snapshot and search;
- Image Fusion, Object Highlight
- IP67, Battery Operating Time ≥7h

DS-2TR03-35UM/W

Thermal Weapon Sight



- 384×288 thermal resolution; 17um
- Thermal: 35mm lens
- No-shutter thermal imaging technology
- 0.39-inch OLED display
- Distance measurement; Wi-Fi; GPS
- MIL-STD-810F; crosshair
- Working temperature:-40 °C to 50 °C(-40 °F to 122 °F);
- Video recording, picture snapshot, up to 16 GB built-in SD card storage
- IP67, battery operating time ≥8h

NVR

iDS-6716NXI-I/16S

False Alarm Filtering NVS



- 320 Mbps Bit Rate Input Max (up to 16-ch 4M IPC video stream
- Support the third party IPC)
- Alarm I/O: 16/4,
- False alarm filtering for up to 16-ch behavior detection(line crossing, intrusion,region entrance and region exiting)

iDS-7716NXI-I4/8S

Fale Alarm Filtering and Appearance analysis NVR



- 160 Mbps Bit Rate Input Max (up to 16-ch IP video)
- 4 SATA Interfaces
- Up to 10TB per HDD
- Alarm I/O: 16/4
- 1.5U case,19"
- Human detection & appearance analysis for up to 8 channels
- Behavior detection (line crossing, intrusion, region entrance and region exiting)

iDS-7716NXI-I4/16P/8S

Fale Alarm Filtering and Appearance analysis NVR



- 160 Mbps Bit Rate Input Max (up to 16-ch IP video), 4 SATA Interfaces
- Up to 10TB per HDD,16 independent PoE network interfaces
- Alarm I/O: 16/4
- 1.5U case,19"
- Human detection & appearance analysis for up to 8 channels
- Behavior detection (line crossing, intrusion, region entrance and region exiting)

iDS-7732NXI-I4/8S

Fale Alarm Filtering and Appearance analysis NVR



- 256 Mbps Bit Rate Input Max (up to 16-ch IP video), 4 SATA Interfaces
- Up to 10TB per HDD
- Alarm I/O: 16/4
- 1.5U case,19"
- Human detection & Appearance analysis for up to 8 channels
- Behavior detection (line crossing, intrusion, region entrance and region exiting)

iDS-7732NXI-I4/16P/8S

Fale Alarm Filtering and Appearance analysis NVR



- 256 Mbps Bit Rate Input Max (up to 16-ch IP video), 4 SATA Interfaces
- Up to 10TB per HDD,16 independent PoE network interfaces
- Alarm I/O: 16/4
- 1.5U case,19"
- Human detection & appearance analysis for up to 8 channels,
- Behavior detection (line crossing, intrusion, region entrance and region exiting)

iDS-9632NXI-I8/8S

Fale Alarm Filtering and Appearance analysis NVR



- 320Mbps Bit Rate Input Max (up to 32-ch IP video)
- 8 SATA Interfaces
- Up to 10TB per HDD
- Alarm I/O: 16/4 (16/8 optional)
- 2U case,19"
- RAID 0/1/5/6/10
- Human detection & appearance analysis for up to 8 channels
- Behavior detection (line crossing, intrusion, region entrance and region exiting)

iDS-9632NXI-I8/16S

Fale Alarm Filtering and Appearance analysis NVR



- 320Mbps Bit Rate Input Max (up to 32-ch IP video), 8 SATA Interfaces
- Up to 10TB per HDD
- Alarm I/O: 16/4 (16/8 optional)
- 2U case,19"
- RAID 0/1/5/6/10
- Human detection & appearance analysis for up to 16 channels
- Behavior detection (line crossing, intrusion, region entrance and region exiting)

iDS-9632NXI-I8/4F

Facial Recognition NVR



- 256Mbps Bit Rate Input Max (up to 32-ch IP video)
- 8 SATA Interfaces
- Up to 10TB per HDD
- Alarm I/O: 16/4 (16/8 optional)
- 2U case,19"
- RAID 0/1/5/6/10
- Facial recognition for up to 4 channels
- Supports 4 face libraries, up to 30,000 face pictures per library and support 50,000 pictures in total

iDS-96064NXI-I16

Facial recognition/False Alarm Filtering and Appearance analysis NVR



- 400Mbps Bit Rate Input Max (up to 64-ch IP video)
- 8 SATA Interfaces,Up to 10TB per HDD, LCD Default
- Alarm I/O: 16/8
- 3U case,19"
- RAID 0/1/5/6/10
- Redundant power supply
- Facial recognition for up to 16 channels
- Human detection & appearance analysis
- Supports 16 face libraries, up to 30,000 face pictures per library and support 100,000 pictures in total

iDS-96128NXI-I16

Facial Recognition/False Alarm Filtering and Appearance analysis NVR



- 512Mbps Bit Rate Input Max (up to 128-ch IP video), 8 SATA Interfaces
- Up to 10TB per HDD
- Alarm I/O: 16/8
- 3U case,19"
- LCD default
- RAID 0/1/5/6/10
- Redundant power supply
- Facial Recognition for up to 32 channels
- Human detection & appearance analysis
- Supports 16 face libraries, up to 30,000 face pictures per library and support 100,000 pictures in total

DS-96064NI-I16

Super Series NVR



- 512Mbps Bit Rate Input Max (up to 64-ch IP video)
- 16 SATA Interfaces
- Alarm I/O: 16/8
- RAID0,1,5,6,10 supported
- 3U case,19"

DS-8616NI-K8

8 HDD NVR



- 160Mbps Bit Rate Input Max (up to 16-ch IP video)
- 8 SATA interfaces
- Alarm I/O: 16/4
- 2U case,19"

NVR

HIKVISION

DS-8632NI-K8

8 HDD NVR



- 256Mbps Bit Rate Input Max (up to 32-ch IP video)
- 8 SATA interfaces
- Alarm I/O: 16/4
- 2U case,19"

DS-7604NI-K1(B)

4K NVR



- 40Mbps Bit Rate Input Max (up to 4-ch IP video)
- 1 SATA interface
- Standalone 1U case

DS-7604NI-K1/4P(B)

4K NVR



- 40Mbps Bit Rate Input Max (up to 4-ch IP video)
- 1 SATA interface
- 4 independent PoE network interfaces
- Standalone 1U case

DS-7608NI-K1(B)

4K NVR



- 80Mbps Bit Rate Input Max (up to 8-ch IP video)
- 1 SATA interface
- Standalone 1U case

DS-7616NI-K1(B)

4K NVR



- 160Mbps Bit Rate Input Max (up to 16-ch IP video)
- 1 SATA interface
- Standalone 1U case

DS-7604NI-K1/W

Wi-Fi NVR



- 50Mbps Bit Rate Input Max (up to 4-ch IP video)
- 1 SATA interface,
- Standalone 1U case
- H.265+/2.265/H.264+/H.264
- 2 external antennas,
- Transmission speed at up to 300Mbps
- Transmission distance at up to 150m

DS-7608NI-K1/W

Wi-Fi NVR



- 50Mbps Bit Rate Input Max (up to 8-ch IP video)
- 1 SATA interface,
- Standalone 1U case
- H.265+/2.265/H.264+/H.264
- 2 external antennas
- Transmission speed at up to 300Mbps
- Transmission distance at up to 150m



TURBO HD ANALOG CAMERA

Turbo HD 3MP WDR EXIR Camera

DS-2CE16F7T-IT
Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66

DS-2CE56F7T-ITM
Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66

DS-2CE56F7T-VPIT
Outdoor Vandalproof EXIR Dome



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66

DS-2CE16F7T-IT1/3/5
Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 20/40/80m IR distance
- IP66

DS-2CE56F7T-IT1/3
Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 20/40m IR distance
- IP66

DS-2CE16F7T-IT3Z
Outdoor EXIR Motorized Vari-focal Bullet



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance & IP66

DS-2CE16F7T-AIT3Z
Outdoor EXIR Motorized Vari-focal Bullet



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance & IP66
- Dual voltage: 12 VDC/ 24 VAC

DS-2CE56F7T-IT3Z
Outdoor EXIR Motorized Vari-focal Eyeball



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66

DS-2CE56F7T-ITZ
Indoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance

DS-2CE56F7T-AITZ
Indoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC

DS-2CE56F7T-VPIT3Z
Outdoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66

DS-2CE56F7T-AVPIT3Z
Outdoor EXIR Motorized Vari-focal Dome



- 18 fps at 3MP resolution
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66
- Dual voltage: 12 VDC/ 24 VAC

Turbo HD 3MP EXIR Camera

DS-2CE16F1T-IT
Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True day/night & Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66

DS-2CE56F1T-ITM
Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True day/night & Smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66

DS-2CE16F1T-IT1/3/5
Outdoor EXIR Bullet



- 18 fps at 3MP resolution
- True day/night & Smart IR
- Advanced EXIR technology
- 20/40/80m IR distance
- IP66

DS-2CE56F1T-IT1/3
Outdoor EXIR Eyeball



- 18 fps at 3MP resolution
- True day/night & Smart IR
- Advanced EXIR technology
- 20/40m IR distance
- IP66

TURBO HD ANALOG CAMERA

HIKVISION

Turbo HD 5MP EXIR Camera

DS-2CE16H0T-ITPF
4/5MP Bullet Analog camera



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- Advanced EXIR technology
- Up to 20m IR distance
- ICR, 0.01 Lux/F1.2, smart IR, DNR
- OSD menu (up the coax)
- IP67
- 2.8/3.6/6mm Lens
- TVI/AHD/CVI/CVBS video signal output

DS-2CE16H0T-ITF
4/5MP Eyeball Analog camera



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- Advanced EXIR technology
- Up to 20m IR distance
- ICR, 0.01 Lux/F1.2, smart IR, DNR
- OSD menu (up the coax)
- IP67
- 2.8/3.6/6mm Lens
- TVI/AHD/CVI/CVBS video signal output

DS-2CE16H0T-IT1F
4/5MP Eyeball Analog camera



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- Advanced EXIR technology
- Up to 20m IR distance
- ICR, 0.01 Lux/F1.2, smart IR, DNR
- OSD menu (up the coax)
- IP67
- 3.6/6/8/12/16mm Lens
- TVI/AHD/CVI/CVBS video signal output

DS-2CE16H0T-IT3F
4/5MP Eyeball Analog camera



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- Advanced EXIR technology
- Up to 40m IR distance
- ICR, 0.01 Lux/F1.2, smart IR, DNR
- OSD menu (up the coax)
- IP67
- 3.6/6/8/12/16mm Lens
- TVI/AHD/CVI/CVBS video signal output

DS-2CE16H0T-IT5F
4/5MP Eyeball Analog camera



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- Advanced EXIR technology
- Up to 80m IR distance
- ICR, 0.01 Lux/F1.2, smart IR, DNR, OSD menu (up the coax)
- IP67
- 3.6/6/8/12/16mm Lens
- TVI/AHD/CVI/CVBS video signal output

DS-2CE56H0T-VPITF
4/5MP Eyeball Analog camera



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- Advanced EXIR technology
- Up to 40m IR distance
- ICR, 0.01 Lux/F1.2, smart IR, DNR, OSD menu (up the coax)
- IP67
- 3.6/6/8/12/16mm Lens
- TVI/AHD/CVI/CVBS video signal output

DS-2CE56H0T-ITPF
4/5MP Eyeball Analog camera



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- Advanced EXIR technology
- Up to 20m IR distance
- ICR, 0.01 Lux/F1.2, smart IR, DNR, OSD menu (up the coax)
- 2.8/3.6/6mm Lens
- TVI/AHD/CVI/CVBS video signal output

DS-2CE56H0T-ITMF
4/5MP Eyeball Analog camera



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- Advanced EXIR technology
- Up to 20m IR distance
- ICR, 0.01 Lux/F1.2, smart IR, DNR, OSD menu (up the coax)
- IP66
- 2.8/3.6/6mm Lens
- TVI/AHD/CVI/CVBS video signal output

DS-2CE56H0T-IT1F
4/5MP Eyeball Analog camera



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- Advanced EXIR technology
- Up to 20m IR distance
- ICR, 0.01 Lux/F1.2, smart IR, DNR, OSD menu (up the coax)
- IP66
- 2.8/3.6/6mm Lens
- TVI/AHD/CVI/CVBS video signal output

DS-2CE56H0T-IT3F
4/5MP Eyeball Analog camera



- Up to 20 fps at 5MP resolution
- Switchable between 5MP and 4MP resolution
- Advanced EXIR technology
- Up to 40m IR distance
- ICR, 0.01 Lux/F1.2, smart IR, DNR, OSD menu (up the coax)
- IP66
- 3.6/6/8/12/16mm Lens
- TVI/AHD/CVI/CVBS video signal output

DS-2CE11D8T-PIRL
2 MP Ultra-Low Light PIR Bullet Camera



- 2 MP high performance CMOS
- Ultra-low light
- 1920 × 1080 resolution
- 2.8 mm, 3.6 mm fixed focal lens
- PIR detection, visual alarm
- 120 dB true WDR, 3D DNR
- EXIR 2.0, smart IR, up to 20 m IR distance
- IP67
- Up the coax (HIKVISION-C)

DS-2CE12D8T-PIRL
2 MP Ultra-Low Light PIR Bullet Camera



- 2 MP high performance CMOS
- Ultra-low light
- 1920 × 1080 resolution
- 2.8 mm, 3.6 mm fixed focal lens
- PIR detection, visual alarm
- 120 dB true WDR, 3D DNR
- EXIR 2.0, smart IR, up to 20 m IR distance
- IP67
- Up the coax (HIKVISION-C)

DS-2CE71D8T-PIRL
2 MP Ultra-Low Light PIR Turret Camera



- 2 MP high performance CMOS
- Ultra-low light
- 1920 × 1080 resolution
- 2.8 mm, 3.6 mm fixed focal lens
- PIR detection, visual alarm
- 120 dB true WDR, 3D DNR
- EXIR 2.0, smart IR, up to 20 m IR distance
- IP67
- Up the coax (HIKVISION-C)

DS-2CE38D8T-PIR
2 MP Ultra-Low Light PIR Cube Camera



- 2 MP high performance CMOS
- Ultra-low light
- 1920 × 1080 resolution
- 2.8 mm, 3.6 mm fixed focal lens
- PIR detection
- 120 dB true WDR, 3D DNR
- EXIR 2.0, smart IR, up to 20 m IR distance
- Built-in microphone
- Up the coax (HIKVISION-C)

DS-2CC12D9T-IT3
HD1080P Starlight+ POC Bullet



- Built-in POC(Power over Coax)
- True day/night,
- True WDR, smart IR
- Advanced EXIR technology
- Up to 40m IR distance
- IP66

DS-2CC52D9T-IT3
HD1080P Starlight+ POC Eyeball



- Built-in POC(Power over Coax)
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- Up to 40m IR distance
- IP66



TURBO HD ANALOG CAMERA

DS-2CC12D9T-AIT3ZE
HD1080P Starlight+ POC Vari-focal Bullet



- Built-in POC(Power over Coax)
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized auto focus Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC

DS-2CC52D9T-AVPIT3ZE
HD1080P Starlight+ POC Vari-focal Dome



- Built-in POC(Power over Coax)
- True day/night, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized auto focus Lens
- 40m IR distance
- Vandal proof & IP66
- Dual voltage: 12 VDC/ 24 VAC

DS-2CC52D9T-AITZE
HD1080P Starlight+ POC Vari-focal Dome



- Built-in POC(Power over Coax)
- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized auto focus Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC

Turbo HD1080P WDR EXIR Camera

DS-2CE16D7T-IT
Outdoor EXIR Eyeball



- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66

DS-2CE56D7T-ITM
Outdoor EXIR Eyeball



- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66

DS-2CE56D7T-VPIT
Outdoor Vandalproof EXIR Dome



- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- Up to 20m IR distance
- IP66

DS-2CE16D7T-IT1/3/5
Outdoor EXIR Bullet



- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 20/40/80m IR distance
- IP66

DS-2CE56D7T-IT1/3
Outdoor EXIR Eyeball



- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 20/40m IR distance
- IP66

DS-2CE16D7T-(A)IT3Z
Outdoor EXIR Motorized Vari-focal Bullet



- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56D7T-IT3Z
Outdoor EXIR Motorized Vari-focal Eyeball



- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- IP66

DS-2CE56D7T-(A)ITZ
Indoor EXIR Motorized Vari-focal Dome



- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 30m IR distance
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

DS-2CE56D7T-(A)VPIT3Z
Outdoor EXIR Motorized Vari-focal Dome



- True day/night
- True WDR, smart IR
- Advanced EXIR technology
- 2.8-12mm motorized Lens
- 40m IR distance
- Vandal proof & IP66
- Dual voltage: 12 VDC/ 24 VAC (-A model only)

Turbo HD1080P Camera

DS-2CE56D0T-IRMM
Indoor IR Dome



- 3-axis adjustment
- True day/night
- DNR, smart IR
- Up to 20m IR distance

DS-2CE56D0T-IRP
Indoor IR Eyeball



- 3-axis adjustment
- True day/night
- DNR, smart IR
- Up to 20m IR distance

DS-2CE16D0T-IR(P)
Outdoor IR Bullet



- 3-axis adjustment
- True day/night
- DNR, smart IR
- Up to 20m IR distance

TURBO HD ANALOG CAMERA



DS-2CE56D0T-IR
Outdoor IR Eyeball



- 3-axis adjustment
- True day/night
- DNR, smart IR
- Up to 20m IR distance

DS-2CE56D0T-IRM
Outdoor IR Eyeball



- 3-axis adjustment
- True day/night
- DNR, smart IR
- Up to 20m IR distance

DS-2CE16D0T-IT1/3/5
Outdoor EXIR Bullet



- 3-axis adjustment
- True day/night
- DNR, smart IR
- Up to 20/40/80m IR distance with EXIR
- IP66

DS-2CE56D0T-IT1/3
Outdoor EXIR Eyeball



- 3-axis adjustment
- True day/night
- DNR, smart IR
- Up to 20/40m IR distance with EXIR
- IP66

DS-2CE56D1T-IRMM
HD1080P Indoor IR Dome



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC
- 3-axis adjustment

DS-2CE56D1T-VP1R
HD1080P Vandal-proof IR Dome



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC
- Vandal proof

DS-2CE16D1T-IR
HD1080P IR Bullet Camera



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC
- IP66

DS-2CE56D1T-IRP
HD1080P Indoor IR Turret



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC

DS-2CE56D1T-IR
HD1080P Outdoor IR Turret



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC
- IP66

DS-2CE56D1T-IRM
HD1080P Outdoor IR Turret



- True day/night
- DNR, smart IR
- 20m IR distance
- OSD menu controlled via UTC
- IP66

DS-2CE16D1T-IT1/3/5
HD1080P EXIR Bullet Camera



- True day/night
- DNR, smart IR
- 20/40/80m IR distance
- OSD menu controlled via UTC
- IP66

DS-2CE56D1T-IT1/3
HD1080P EXIR Turret Camera



- True day/night
- DNR, smart IR
- 20/40m IR distance
- OSD menu controlled via UTC
- IP66

DS-2CE56D1T-AVF1R
HD1080P Indoor Vari-focal IR Dome



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 30m IR distance
- OSD menu controlled via UTC
- Dual voltage: 12 VDC / 24 VAC

DS-2CE56D1T-VF1R
HD1080P Indoor Vari-focal IR Dome



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 30m IR distance
- OSD menu controlled via UTC

DS-2CE56D1T-VP1R3
HD1080P Outdoor Vandal-proof IR Dome



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 40m IR distance
- OSD menu controlled via UTC
- Vandal proof, IP66

DS-2CE56D1T-AVPIR3
HD1080P Outdoor Vandal-proof IR Dome



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 40m IR distance
- OSD menu controlled via UTC
- Vandal proof, IP66
- Dual voltage: 12 VDC / 24 VAC

TURBO HD ANALOG CAMERA

DS-2CE56D1T-VFIR3

HD1080P Outdoor Vari-focal IR Turret



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 40m IR distance
- OSD menu controlled via UTC
- IP66

DS-2CE16D1T-VFIR3

HD1080P Outdoor Vari-focal IR Bullet



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 40m IR distance
- OSD menu controlled via UTC
- IP66

DS-2CE16D1T-AVFIR3

HD1080P Outdoor Vari-focal IR Bullet



- True day/night
- DNR, smart IR
- 2.8-12mm vari-focal lens
- 40m IR distance
- OSD menu controlled via UTC
- IP66
- Dual voltage: 12 VDC / 24 VAC

DS-2CC12D9T(-A)

HD1080P Box Camera



- True day/night
- 3D DNR, smart IR
- True WDR, up to 120dB
- OSD menu controlled via UTC
- Alarm input & output (DS-2CC12D9T-A)
- Dual voltage: 12 VDC / 24 VAC

DS-2CE16D9T-AIRAZH

HD1080P Outdoor Vari-focal Bullet Camera



- Turbo HD output, up to 1080P resolution
- 5 ~ 50mm motorized vari-focal lens
- True day/night
- Auto Focus, EXIR Technology
- OSD menu, 3D DNR, smart IR
- True WDR, up to 120dB
- Up to 120m IR distance
- Built-in heater, IP66
- UTC function, 24V AC/ 12V DC

DS-2CE16D5T-IR

HD1080P Turret Camera



- HD1080P video output
- Adopt HDTVI Technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 20m IR distance
- IP66
- True WDR
- Up the coax (via coaxial cable)

DS-2CE56D5T-IRM

HD1080P Turret Camera



- HD1080P video output
- Adopt HDTVI Technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 20m IR distance
- IP66
- True WDR
- Up the coax (via coaxial cable)

DS-2CE56D5T-IR

HD1080P Turret Camera



- HD1080P video output
- Adopt HDTVI Technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 20m IR distance
- IP66
- True WDR
- Up the coax (via coaxial cable)

DS-2CE16D5T-IT1

HD1080P EXIR Bullet Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 20m IR distance
- IP66
- True WDR
- Up the coax (via coaxial cable)

DS-2CE16D5T-IT3

HD1080P EXIR Bullet Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 40m IR distance
- IP66
- True WDR
- Up the coax (via coaxial cable)

DS-2CE16D5T-IT5

HD1080P EXIR Bullet Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 80m IR distance
- IP66
- True WDR
- Up the coax (via coaxial cable)

DS-2CE56D5T-IT1

HD1080P EXIR Turret Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 20m IR distance
- IP66
- True WDR
- Up the coax (via coaxial cable)

DS-2CE56D5T-IT3

HD1080P EXIR Turret Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 40m IR distance
- IP66
- True WDR
- Up the coax (via coaxial cable)

DS-2CE56D5T-VPIR3

HD1080P Outdoor Vandal Proof Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 40m IR distance
- IP66 & vandal proof
- True WDR
- Up the coax (via coaxial cable)

DS-2CE56D5T-AVPIR3

HD1080P Outdoor Vandal Proof Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 40m IR distance
- IP66 & vandal proof
- True WDR
- Up the coax (via coaxial cable)
- Dual Voltage (12 VDC/24 VAC)

DS-2CE56D5T-VFIR

HD1080P Indoor Vari-Focal IR Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 30m IR distance
- True WDR
- Up the coax (via coaxial cable)

TURBO HD ANALOG CAMERA

HIKVISION

DS-2CE56D5T-AVFIR

HD1080P Indoor Vari-Focal IR Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- 2 ~ 12mm Motorized vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 30m IR distance
- True WDR
- Up the coax (via coaxial cable)
- Dual Voltage (12 VDC/24 VAC)

DS-2CE56D5T-VFIT3

HD1080P Outdoor Vari-Focal EXIR Turret Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 50m IR distance
- IP66
- True WDR
- Up the coax (via coaxial cable)

DS-2CE16D5T-VFIT3

HD1080P Outdoor Vari-Focal EXIR Bullet Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 50m IR distance
- IP66
- True WDR
- Up the coax (via coaxial cable)

DS-2CE16D5T-AVFIT3

HD1080P Outdoor Vari-Focal EXIR Bullet Camera



- HD1080P video output
- Supports HDTVI technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 50m IR distance & IP66
- True WDR
- Up the coax (via coaxial cable)
- Dual voltage (12 VDC/24 VAC)

DS-2CE16D1T-(A)IR3Z

Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True day/night
- DNR, smart IR
- OSD menu controlled via UTC
- 2.8-12mm motorized vari-focal lens
- Up to 40m IR distance
- IP66
- Dual voltage: 12 VDC/ 24 VAC

DS-2CE56D1T-IR3Z

Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True day/night
- DNR, smart IR
- OSD menu controlled via UTC
- 2.8-12mm motorized vari-focal lens
- Up to 40m IR distance
- IP66

DS-2CE56D1T-(A)IRZ

Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True day/night
- DNR, smart IR
- OSD menu controlled via UTC
- 2.8-12mm motorized vari-focal lens
- Up to 40m IR distance
- IP66

DS-2CE56D1T-(A)VP1R3Z

Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True day/night
- DNR, smart IR
- OSD menu controlled via UTC
- 2.8-12mm motorized vari-focal lens
- Up to 40m IR distance
- IP66 & vandal proof
- Dual voltage: 12 VDC/ 24 VAC

DS-2CE16D5T-AIR3ZH

Motorized Lens Camera



- 2.0MP high-performance CMOS
- Turbo HD output, up to 1080P resolution
- True day/night
- True WDR, 3D DNR, smart IR
- OSD menu
- 2.8-12mm motorized vari-focal lens
- Up to 40m IR distance
- IP66
- Built-in heater

Turbo HD720P Low Light

DS-2CE16C5T-IT1/3

HD720P EXIR Low Light Bullet Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 40m IR distance
- IP66
- Low illumination
- Up the coax (via coaxial cable)

DS-2CE16C5T-IT5

HD720P EXIR Low Light Bullet Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 80m IR distance
- IP66
- Low illumination
- Up the coax (via coaxial cable)

DS-2CE56C5T-IT1

HD720P EXIR Low Light Turret Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 20m IR distance
- IP66
- Low illumination
- Up the coax (via coaxial cable)

DS-2CE56C5T-IT3

HD720P EXIR Low Light Turret Camera



- HD720P video output
- Supports HDTVI technology
- True day/night
- OSD menu, 3D DNR, smart IR
- 40m IR distance
- IP66
- Low illumination
- Up the coax (via coaxial cable)

TURBO HD ANALOG CAMERA

DS-2CE56C5T-VPIR3
HD720P Outdoor Vandal-proof Camera



- HD720P video output
- Supports HDTV technology
- True day/night
- 8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 40m IR distance
- IP66 S vandal proof
- Low illumination
- Up the coax (via coaxial cable)

DS-2CE56C5T-AVPIR3
HD720P Outdoor Vandal-proof Camera



- HD720P video output
- Supports HDTV technology
- True day/night
- 8 - 12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 40m IR distance
- IP66 S vandal proof
- Low illumination, Up the coax (via coaxial cable)
- Dual voltage(12 VDC/24 VAC)

DS-2CE56C5T-VFIR
HD720P Indoor Vari-focal IR Dome Camera



- HD720P video output
- Supports HDTV technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 30m IR distance
- Low illumination
- Up the coax (via coaxial cable)

DS-2CE56C5T-AVFIR
HD720P Indoor Vari-focal IR Dome Camera



- HD720P video output
- Supports HDTV technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 30m IR distance
- Low illumination, Up the coax (via coaxial cable)
- Dual voltage(12 VDC/24 VAC)

DS-2CE56C5T-VFIT3
HD720P Outdoor Vari-focal EXIR Turret Camera



- HD720P video output
- Supports HDTV technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 50m IR distance
- Low illumination
- Up the coax (via coaxial cable)

Turbo HD720P

DS-2CE16C2T-IRP
HD720P Bullet Camera



- HD720P video output
- Supports HDTV technology
- True day/night
- DNR, smart IR
- 20m IR distance
- IP66

DS-2CE16C5T-VFIR3
HD720P Outdoor Vari-focal IR Bullet Camera



- HD720P video output
- Supports HDTV technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 40m IR distance
- Low illumination
- Up the coax (via coaxial cable)

DS-2CE16C5T-AVFIR3
HD720P Outdoor Vari-focal IR Bullet Camera



- HD720P video output
- Supports HDTV technology
- True day/night
- 2.8-12mm vari-focal lens
- OSD menu, 3D DNR, smart IR
- Up to 40m IR distance
- Low illumination, Up the coax (via coaxial cable)
- Dual voltage(12 VDC/24 VAC)

DS-2CE16C2T-IR
HD720P Bullet Camera



- HD720P video output
- Supports HDTV technology
- True day/night
- DNR, smart IR
- 20m IR distance
- IP66

DS-2CE56C2T-IRM
HD720P Turret Camera



- HD720P video output
- Supports HDTV technology
- True day/night
- DNR, smart IR
- 20m IR distance
- IP66

DS-2CE16C2T-IT1/3
HD720P EXIR Bullet Camera



- HD720P video output
- Supports HDTV technology
- True day/night,smart IR
- 20/40m IR distance
- IP66

DS-2CE16C2T-IT5
HD720P EXIR Bullet Camera



- HD720P video output
- Supports HDTV technology
- True day/night,smart IR
- 80m IR distance
- IP66

DS-2CE56C2T-IT1/3
HD720P EXIR Turret Camera



- HD720P video output
- Supports HDTV technology
- True day/night,smart IR
- 20/40m IR distance
- IP66

DS-2CE56C0T-IRMM
Indoor IR Dome



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True day/night
- DNR, smart IR
- Up to 20m IR distance

DS-2CE56C0T-IRP
Indoor IR Eyeball



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True day/night
- DNR, smart IR
- Up to 20m IR distance

TURBO HD ANALOG CAMERA



DS-2CE16C0T-IR(P)
Outdoor IR Bullet



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True day/night
- DNR, smart IR
- Up to 20m IR distance
- IP66

DS-2CE56C0T-IR(M)
Outdoor IR Eyeball



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True day/night
- DNR, smart IR
- Up to 20m IR distance
- IP66

DS-2CE16C0T-IT1/3/5
Outdoor EXIR Bullet



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True day/night
- DNR, smart IR
- Up to 20/40/80m IR distance with EXIR
- IP66

DS-2CE56C0T-IT1/3
Outdoor EXIR Eyeball



- 1.0 MP high-performance CMOS
- Turbo HD output, up to 720P resolution
- True day/night
- DNR, smart IR
- Up to 20/40m IR distance with EXIR
- IP66

TURBO HD DVR

DS-7204/08HUHI-F1/S

5MP 1U Turbo HD DVR



- 4/8-ch video & 4-ch audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- 12fps recording at 5MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7204HUHI-F1/S), support CVBS output
- 4K UHD output (DS-7208HUHI-F1/S)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208HUHI-F1/S)

DS-7204/08/16HUHI-F2/S

5MP 1U Turbo HD DVR



- 4/8/16-ch video & 4-ch audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- 12fps recording at 5MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7204HUHI-F2/S), support CVBS output
- 4K UHD output (DS-7208/16HUHI-F2/S)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208/16HUHI-F2/S)

DS-7104/08/16HGHI-F1

720P Mini 1U Turbo HD DVR



- 4/8/16-ch HD TVI/AHD/analog cameras video&audio input
- HD-TVI/AHD/analog hybrid
- HD-TV and analog cameras self-adaptive access
- Up to full channel@720P resolution real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- 1SATA, 2 USB2.0

DS-7104/08/16HQHI-F1/N

1080P Mini 1U Turbo HD DVR



- 4/8/16-ch HD TVI/analog/AHD cameras video&audio input
- HD-TVI/analog/AHD/IP camera hybrid
- H.264+ video compression
- Full channel@720P resolution real-time and 1080P non real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- 1 SATA, 2 USB 2.0

DS-7204/08/16HGHI-F1

DS-7208/16HGHI-F2

720P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/AHD/analog cameras video&audio input
- HD-TVI/analog/AHD/IP camera quadruple hybrid
- HD-TV and analog cameras self-adaptive access
- Up to full channel@720P resolution real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1SATA(DS-7204/08/16HGHI-E1)/2 SATA(DS-7208/16HGHI-E2), 2 USB2.0

DS-7204/08/16HQHI-F1/N

1080P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/analog/AHD cameras video&audio input
- HD-TVI/analog/AHD/IP camera hybrid
- H.264+ video compression
- Full channel@720P resolution real-time and 1080P non real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 2 USB 2.0

DS-7208/16HQHI-F2/N

1080P 1U Turbo HD DVR



- 8/16-ch HD TVI/analog/AHD cameras video&audio input
- HD-TVI/analog/AHD/IP camera hybrid
- H.264+ video compression
- Full channel@720P resolution real-time and 1080P non real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA, 2 USB 2.0

DS-7204/08HUHI-F1/N

3MP 1U Turbo HD DVR



- 4/8-ch video & 1-ch audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- 15fps recording at 3MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7204HUHI-F1/N), support CVBS output
- 4K UHD output (DS-7208HUHI-F1/N)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208HUHI-F1/N)

DS-7204/08HUHI-F2/N

3MP 1U Turbo HD DVR



- 4/8/16-ch video & 1-ch audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- 15fps recording at 3MP
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7204HUHI-F2/N), support CVBS output
- 4K UHD output (DS-7208/16HUHI-F2/N)
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA, 1 USB 2.0 & 2 USB 3.0(DS-7208HUHI-F2/N)

DS-7204/08/16HGHI-SH

1080P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/analog cameras video&audio input
- HD-TVI/analog/IP camera triple hybrid
- HD-TV and analog cameras self-adaptive access
- Full channel@720P resolution real-time and 1080P no-real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA(DS-7216HGHI-SH)/1 SATA(7204/08HGHI-SH), 2 USB2.0

DS-7204/08/16HQHI-SH

Full 1080P 1U Turbo HD DVR



- 4/8/16-ch HD TVI/analog cameras video&audio input
- HD-TVI/analog/IP camera triple hybrid
- HD-TV and analog cameras self-adaptive access
- Full channel@1080P resolution real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 2 SATA(DS-7208/16HQHI-SH)/1 SATA(7204HQHI-SH), 2 USB2.0

DS-7324/7332HQHI-K4

Multiple-channel 1.5U Turbo HD DVR



- 24/32-ch video & 4-ch audio input
- H265+/H265/H264+/H264 video compression
- Self-adaptive HDTVI/HDCVI/AHD/CVBS signal input
- Full channel recording at 4MP lite resolution
- 8-ch(Up to 32/40-ch) 6MP IP Video Input
- Support POS triggered recording and POS information overlay
- 4K (3840×2160) UHD output
- 16/4 alarm I/O
- 4 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

TURBO HD DVR

DS-7304/08/16HQHI-F4/N


1080P 1.5U Turbo HD DVR



- 4/8/16-ch video & 4-ch audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-7304/08HQHI-F4/N), support CVBS output
- 4K UHD output (DS-7316HQHI-F4/N)
- Long transmission distance over coax cable
- 4 SATA, 1 eSATA, 3 USB2.0, gigabit NIC

DS-7324/7332HUHI-K4

Multiple-channel 1.5U Turbo HD DVR



- 24/32-ch video & 4-ch audio input
- H265+/H265/H264+/H264 video compression
- Self-adaptive HDTVI/HDCVI/AHD/CVBS signal input
- Full channel recording at 5MP resolution
- 8-ch(Up to 32/40-ch) 8MP IP Video Input
- Support POS triggered recording and POS information overlay
- Supports people counting and heat map functions
- 4K (3840×2160) UHD output
- 16/4 alarm I/O
- 4 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-8104/08/16HUHI-F8/N

3MP 2U Turbo HD DVR



- 4/8/16-ch HD-TVI/analog cameras video & audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 6/10/18-ch 8MP ONVIF conformant IP cameras input
- 4K (3840×2160) UHD output
- Long transmission distance over coax cable
- Supports POS triggered recording and POS information overlay
- Dual Gigabit network interfaces
- 8 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

Hybrid DVR

DS-9024/32HUHI-K8

Multiple-channel 2U Turbo HD DVR



- 24/32-ch video & 16-ch audio input
- H265+/H265/H264+/H264 video compression
- Self-adaptive HDTVI/HDCVI/AHD/CVBS signal input
- Full channel recording at 5MP resolution
- 24/32-ch(Up to 48/64-ch) 12MP IP Video Input
- Support POS triggered recording and POS information overlay
- Supports people counting and heat map functions
- 4K (3840×2160) UHD output
- 16/8 alarm I/O
- 8 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-7304/08/16/24/32HGHI-SH

1080P 1.5U Turbo HD DVR



- 4/8/16/24/32-ch HD TVI/analog cameras video&audio input
- HD-TVI/analog/IP camera triple hybrid
- HD-TV and analog cameras self-adaptive access
- Full channel@720P resolution real-time and 1080P no-real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Gigabit network interfaces
- 4 SATA, 1 eSATA, 3 USB2.0

DS-8104/08/16HQHI-F8/N

1080P 2U Turbo HD DVR



- 4/8/16-ch video & audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel recording at 1080P resolution
- HDMI output at up to 1920×1080P resolution(DS-8104/08HQHI-F8/N), support CVBS output
- 4K UHD output (DS-8116HQHI-F8/N)
- Long transmission distance over coax cable
- 8 SATA, 1 eSATA, 3 USB2.0, gigabit NIC

DS-8124/32HQHI-K8

Multiple-channel 2U Turbo HD DVR



- 24/32-ch video & 16-ch audio input
- H265+/H265/H264+/H264 video compression
- Self-adaptive HDTVI/HDCVI/AHD/CVBS signal input
- Full channel recording at 4MP lite resolution
- 16-ch(Up to 40/48-ch) 6MP IP Video Input
- Support POS triggered recording and POS information overlay
- 4K (3840×2160) UHD output
- 16/8 alarm I/O
- 8 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-9004/08/16HUHI-F8/N

3MP 2U Turbo HD DVR



- 4/8/16-ch HD-TVI/analog cameras video & audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 10/18/32-ch 8MP ONVIF conformant IP cameras input
- 4K (3840×2160) UHD output
- Long transmission distance over coax cable
- Supports POS triggered recording and POS information overlay
- Dual Gigabit network interfaces
- 8 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-7304/08/16HUHI-F4/N

3MP 1.5U Turbo HD DVR



- 4/8/16-ch HD-TVI/analog cameras video & audio input
- HDTVI/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 6/10/18-ch 8MP ONVIF conformant IP cameras input
- 4K (3840×2160) UHD output
- Long transmission distance over coax cable
- Supports POS triggered recording and POS information overlay
- Dual Gigabit network interfaces
- 4 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-8104/08/16/24/32HGHI-SH

1080P 2U Turbo HD DVR



- 4/8/16/24/32-ch HD TVI/analog cameras video&audio input
- HD-TVI/analog/IP camera triple hybrid
- HD-TV and analog cameras self-adaptive access
- Full channel@720P resolution real-time and 1080P no-real-time recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Dual Gigabit network interfaces
- 8 SATA, 1 eSATA, 3 USB2.0

DS-8124/32HUHI-K8

Multiple-channel 2U Turbo HD DVR



- 24/32-ch video & 16-ch audio input
- H265+/H265/H264+/H264 video compression
- Self-adaptive HDTVI/HDCVI/AHD/CVBS signal input
- Full channel recording at 5MP resolution
- 16-ch(Up to 40/48-ch) 8MP IP Video Input
- Support POS triggered recording and POS information overlay
- Supports people counting and heat map functions
- 4K (3840×2160) UHD output
- 16/8 alarm I/O
- 8 SATA, 1 eSATA, 1 USB 3.0 & 2 USB 2.0

DS-9004/08/16HFI-STI-(RT)

Full 4CIF 2U Hybrid DVR



- Up to 8/16/32-ch (Analog video + IP video) input
- H.264 & dual-stream video compression
- Full channel@4CIF real-time analog video recording
- Up to 5MP resolution IP video recording
- Third-party network cameras supported
- HDMI and VGA output at up to 1920×1080P resolution
- 8 SATA, 1 eSATA, 3 USB2.0
- *-RT series support RAID0, 1, 5, 10

TURBO HD DVR & NETWORK STORAGE

DS-7604HUHI-F1/N & DS-7608/16HUHI-F2/N
3MP 1U Turbo HD DVR



- Up to 8/16/32-ch (Analog video + IP video) input
- HDTV/analog/AHD/IP camera quadruple hybrid
- Full channel 3MP resolution recording at 15 fps
- Up to 8MP resolution IP video recording
- HDMI and VGA output at up to 1920×1080P resolution
- Long transmission distance over coax cable
- Front panel and alarm I/O optional
- 1 SATA, 2 USB 2.0(DS-7604HUHI-F1/N)
- 2 SATA, 1 USB 2.0 & 1 USB 3.0(DS-7608/16HUHI-F2/N)

DS-7604/08/16HI-ST
Full 4CIF 1U Hybrid DVR



- Up to 8/16/32-ch (Analog video + IP video) input
- H.264 & dual-stream video compression
- Full channel@4CIF real-time analog video recording
- Up to 5MP resolution IP video recording
- Third-party network cameras supported
- HDMI output at up to 1920×1080P resolution
- 1 SATA(DS-7604HI-ST)/2 SATA(DS-7608/16HI-ST), 2 USB2.0

DS-8104/08/16HFHI-ST(-SL)
Full 1080P/720P 2U HD-SDI DVR



- 4/8/16-ch HD-SDI video&audio input
- H.264 & dual-stream video compression
- Full channel@1920×1080P resolution real-time recording(-ST series)
- Full channel@1280×720P resolution real-time recording(-SL series)
- HDMI and VGA output at up to 1920×1080P resolution
- Dual Gigabit network interfaces
- HDD quota and group management
- 8 SATA, 1 eSATA, 3 USB2.0

NETWORK STORAGE

DS-7304/08/16HFHI-ST(-SL)
Full 1080P/720P 1.5U HD-SDI DVR



- 4/8/16-ch HD-SDI video&audio input
- H.264 & dual-stream video compression
- Full channel@1920×1080P resolution real-time recording(-ST series)
- Full channel@1280×720P resolution real-time recording(-SL series)
- HDMI and VGA output at up to 1920×1080P resolution
- Gigabit network interfaces
- HDD quota and group management
- 4 SATA, 1 eSATA, 3 USB2.0

DS-A81024D
Network Storage System



- High-performance & easily-extensible hardware platform
- Highly reliable system design, double controller
- Support 180 –Ch(2M) record and play in IP-SAN mode,296 –Ch(2M) record and play in CVR mode
- Disk detection, repair and RAID optimization
- Low power design
- Massive storage space, 4U chassis with 14 HDs and cascade extension support

DS-A82024D
Network Storage System



- High-performance & easily-extensible hardware platform
- Highly reliable system design, double controller
- Support 256 –Ch(2M) record and play in IP-SAN mode,448 –Ch(2M) record and play in CVR mode
- Disk detection, repair and RAID optimization
- Low power design
- Massive storage space, 4U chassis with 14 HDs and cascade extension support

DS-A81016S
Network Storage System



- High performance with 64-bit RISC processor
- Up to 16 HDD, each disk up to 4TB capacity and cascade extension support
- Support 180 –Ch(2M) record and play in IP-SAN mode,296 –Ch(2M) record and play in CVR mode
- iSCSI/NFS/CIFS/FTP/HTTP/AFP protocols
- RAID 0, 1, 3, 5, 10, 50 and HDD hot swap supported
- Modularization and redundant power design for highest reliability

DS-A80624S
Network Storage System



- High performance with 64-bit RISC processor
- Up to 24 HDD, each disk up to 4TB capacity and cascade extension support
- Support 120 –Ch(2M) record and play in IP-SAN mode,192 –Ch(2M) record and play in CVR mode
- iSCSI/NFS/CIFS/FTP/HTTP/AFP protocols
- RAID 0, 1, 3, 5, 10, 50 and HDD hot swap supported
- Modularization and redundant power design for highest reliability

MONITOR

Monitor

DS-D5019QE
19" LCD Monitor



- 19" backlit LED at 1366×768 resolution
- View angle: 90°(H)/65°(V)
- Inputs: VGA
- 3D comb filter, 3D de-interlace, 3D noise reduction
- High reliable components for 7×24 working

DS-D5019QE-B
19" LCD Monitor



- 19" backlit LED at 1366×768 resolution
- View angle: 90°(H)/65°(V)
- Inputs: VGA, HDMI
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5022FC
22" LCD Monitor



- 22" backlit LED at full HD 1920×1080
- Wide view angle: 170°(H)/160°(V)
- Multiply inputs: HDMI, VGA, BNC, audio in
- 3D comb filter, 3D de-interlace, 3D noise reduction
- High reliable components for 7×24 working

DS-D5022QE-B
22"LCD Monitor



- 22" backlit LED at full HD 1920×1080
- Wide view angle: 170°(H)/160°(V)
- Inputs: VGA, HDMI
- 3D comb filter, 3D de-interlace, 3D noise reduction
- High reliable components for 7×24 working

DS-D5024FC
Monitor



- 32" backlit LED at 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, CVBS(BNC×1), audio in
- Built-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5032FL-B
Monitor



- 32", Backlit LED at 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA CVBS(BNC×1), USB, audio in
- Built-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5032FC
32" LCD Monitor



- 32" backlit LED at 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, S-Video, CVBS(BNC×1), audio in
- Built-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5032FL
32" LCD Monitor



- 32" backlit LED at 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, BNC, USB, audio in
- Built-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- Image freeze
- High reliable components for 7×24 working

DS-D5042FL
42" LCD Monitor



- 42" backlit LED at 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, BNC, USB, audio in
- Built-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- Image freeze
- High reliable components for 7×24 working

DS-D5043FC
43" LCD Monitor



- 43" backlit LED at 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, CVBS(BNC×1), audio in
- Built-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5049FL
Monitor



- 49" backlit LED at 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, CVBS(BNC×1), USB, audio in
- Built-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

DS-D5055UL-B
55" LCD Monitor



- 55" backlit LED at 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA,DVI, CVBS(BNC×1), USB, audio in
- Built-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

MONITOR & NETWORK SWITCH

DS-D5055FL
55" LCD Monitor



- Backlit LED at 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, DVI, BNC, USB, YPbPr, S-Video, audio in
- Built-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- Image freeze
- High reliable components for 7×24 working

DS-D5084UL
84" LCD Monitor



- 84", Backlit LED at 1920×1080 HD resolution
- View angle: 178°(H)/178°(V)
- Inputs: HDMI, VGA, AV, UHD, YPbPr, DVI, CVBS(BNC×1), USB, audio in
- Built-in speaker
- 3D comb filter, 3D de-interlace, 3D noise reduction
- Selectable signal source
- High reliable components for 7×24 working

Network Switch

DS-3E0109P-E/M
PoE switch



- 8×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 1×10/100Mbps uplink port
- 58Watts PoE budget
- 250m transmission
- 6 kV surge protection
- Plug-and-play installation

DS-3E0318P-E/M
PoE switch



- 16×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 1×1000Mbps uplink port
- 135Watts PoE budget
- 250m transmission
- 6 kV surge protection
- Plug-and-play installation

DS-3E0326P-E/M
PoE switch



- 24×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 1×1000Mbps uplink port
- 225Watts PoE budget
- 250m transmission
- 6 kV surge protection
- Plug-and-play installation

DS-3E0508-E
PoE switch



- 8×1000Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 100m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E0516-E
PoE switch



- 16×1000Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 100m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E0524-E
PoE switch



- 24×1000Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 100m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E2310P
PoE Switch



- 8×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 2×1000Mbps uplink port
- 125Watts PoE budget
- 100m transmission
- 4 kV surge protection
- Full managed:VLAN,STP,Console, Telnet, SSH2.0, Web,SNMP v1/v2/v3,TFTP,RMON,etc

DS-3E2318P
PoE switch



- 16×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 2×1000Mbps uplink port
- 300Watts PoE budget
- 100m transmission
- 4 kV surge protection
- Full managed:VLAN,STP,Console, Telnet, SSH2.0, Web,SNMP v1/v2/v3,TFTP,RMON,etc

DS-3E2326P
PoE Switch



- 24×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 2×1000Mbps uplink port
- 380Watts PoE budget
- 100m transmission
- 4 kV surge protection
- Full managed:VLAN,STP,Console, Telnet, SSH2.0, Web,SNMP v1/v2/v3,TFTP,RMON,etc

DS-3E0105P-E
Unmanaged L2 PoE Switch



- 4×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 1×10/100Mbps uplink port
- 58Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

NETWORK SWITCH



DS-3E0109P-E
Unmanaged L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 1×10/100Mbps uplink port
- 123Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E0318P-E
Unmanaged L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 1×10/100Mbps uplink port
- 123Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E0326P-E
Unmanaged L2 PoE Switch



- 24×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 2×1000M combo port
- 370Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug-and-play installation

DS-3E1310P-E
Managed L2 PoE Switch



- 8×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 2×1000Mbps combo uplink port
- 123Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Plug & play installation
- Web-managed: VLAN, Port Mirroring, SNMP, etc.

DS-3E1318P-E
Managed L2 PoE Switch



- 16×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 2×1000M combo uplink port
- 230Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Web-managed: VLAN, Port Mirroring, SNMP, etc.

DS-3E1326P-E
Managed L2 PoE Switch



- 24×10/100Mbps PoE ports, each port support
- 802.3af/802.3at self-adaption
- 2×1000M combo port
- 370Watts PoE budget
- 250m transmission
- 4 kV surge protection
- Web-managed: VLAN, Port Mirroring, SNMP, etc.

DS-1LN5E-S
Network Cable



- UTP CAT 5E, 305 meters
- Conductor Nom.O.D.(mm): 0.500±0.005
- HDPE,PVC,CM,Grey

DS-1LN6-UU
Network Cable



- UTP, CAT6, 305 meters,
- ,Conductor Nom.O.D.(mm): 0.565±0.005,HDPE
- ,PVC,CM,orange

DS-3WF01C-2N
Wireless bridge



- IEEE802.11 a/n, 2.412 to 2.472 GHz
- 500m transmission, 300Mbps bandwidth
- Point-to-point, point-to-multipoint connection
- Web-based configuration, easy to use
- 4 operating mode: Access Point, Client, Access Point (WDS), Client (WDS)

DS-3WF03C-D
Wireless bridge



- IEEE802.11 a/n, 5745 to 5825MHz:
- 3km transmission , 300Mbps bandwidth ;
- Point-to-point, point-to-multipoint connection;
- Web-based configuration, easy to use;
- 5 operation mode: Access Point, Station, WDS Access Point, WDS Station, WDS Repeater

DS-1H34-0101P
PoE repeater



- 1-ch 10/100BaseT(X) and IEEE 802.3at standard of PD connection.
- 1-ch 10/100BaseT(X) and IEEE 802.3af/at standard of PSE output.
- 4-stage cascade support;
- Max transmission distance 500 meters

DS-1H34-0102P
PoE repeater



- 1-ch 10/100BaseT(X) and IEEE 802.3at standard of PD connection.
- 2-ch 10/100BaseT(X) and IEEE 802.3af standard of PSE outputs
- 4-stage cascade support;
- Max transmission distance 500 meters

ENCODER, MOBILE RECORDER & VMS

ENCODERS

DS-6708/16HQHI-SATA

HD1080P Encoder



- 8/16-ch video input, 4-ch audio input
- HD-TVI and analog cameras self-adaptive access
- H.264 & dual-stream video compression
- Full channel@1920x1080P resolution real-time recording
- Multiple network protocols
- 2 SATA interfaces, up to 6 TB for each disk
- 8/16-ch alarm in, 4-ch alarm output

DS-6701/04/08/16HFI/HWI(-SATA)

Full 4CIF/960H Encoder



- 1/4/8/16-ch video&audio input
- H.264/MPEG4/MPEG2/MJPEG & dual-stream video encoding
- Full channel@ 4CIF resolution for DS-6700HFI (-SATA) and full channel@WD1(PAL:960×576,NTSC:960×480) resolution for DS-6700HWI (-SATA)
- Multiple network protocols
- One independent PoE network interfaces for DS-6701/6704HFI/HWI models
- Multiple PTZ protocols
- 1 SATA [DS-6701/04/08/16HFI/HWI-SATA]

DS-6600HFI-JX

ATCA Standard Encoder



- Up to 64-ch video&audio input
- H.264/MPEG4/MPEG2/MJPEG & dual-stream video encoding
- 16 slots available for audio/video output modules (DS-6604HFI-B)
- Each DS-6604HFI-B module provides 4-ch audio/video inputs
- Full channel@4CIF resolution real-time recording
- Standard rack-mounted chassis structure (6U 19")
- Pluggable modular design provides high flexibility

MOBILE RECORDERS

DS-MP3516-RS/GW

On-board Network Recorder



- 16 channels video/audio input
- Support up to 6 x 2.5-inch HDDs/SSDs
- 1-ch CVBS output, 1-ch VGA output
- Support Wi-Fi connection
- Support 3G connection *only for GW model
- 2 x Ethernet ports with M12 plug
- Built-in G-sensor
- Wide power range protection
- Super capacitor for power-off protection
- Patented anti-vibration design

DS-M5504HNI

4-Channel Mobile NVR



- Supports 4 channels of 1080P IP video input
- 4-channel POE interface
- Pluggable disk box with vibration damping technology
- 2x pluggable 2.5-inch HDDs / SSDs
- 1x SD/SDHC card slot
- Pluggable 3G/4G/Wi-Fi module (optional)
- Standard 1DIN dimensions
- EN50155 certification

DS-M5504HMI-SD

4-Channel Mobile DVR



- Supports 4 channels of WD1 video input
- 2× SD / SDHC / SDXC card slot
- Pluggable 3G/4G/Wi-Fi module (optional)
- Standard 1DIN dimensions
- EN50155 certification

DS-M5504HMI

4-Channel Mobile DVR



- Supports 4 channels of WD1 video input
- Pluggable disk box with vibration damping technology
- 1x 2.5-inch HDD/SSD
- Pluggable 3G/4G/Wi-Fi module (optional)
- Standard 1DIN dimensions
- EN50155 certification

DS-MP7504

HD-TVI Mobile DVR



- Supports 4 channels of 720P video input
- 4-ch POE interface
- Pluggable disk box with vibration damping technology
- 2x pluggable 2.5-inch HDDs / SSDs
- Pluggable 3G/4G model (optional)
- Built-in Wi-Fi/GPS (optional)
- Built-in G-sensor
- EN50155 certification

Blazer Pro 128/256/16H

VMS All-in-One Server



- Ready to use, preinstalled with Hikvision Professional VMS software and Windows 8.1;
- Up to 128/256 channels access and recording, recording band width up to 512/718 Mbps;
- 16HDD,HDD hot swap with RAID0, RAID1, RAID5, RAID10 support;
- Active directory integration for user management;
- 100 client user support;
- 3 years of Hardware warranty and software technical support with SSP.

Blazer Express

A Simple iVMS Station With Enormous Potential



- Easy and user friendly UI design for easy basic operation and daily monitoring operation
- Alarm information, real-time video, and the physical location are all displayed on one screen
- Interactive Live View E-map for system awareness and easy visual identification of events
- ANPR function makes entrance/exit management and identification of VIP or black list vehicles quick and convenient
- Point-of-sale integration displays transaction data and video on the same screen for effective customer

OTHER

Keyboard

DS-1600KI

Network Keyboard



- 10.1" capacitive touchscreen with 1024×600 resolution
- Touchscreen and joystick detachable
- Live view
- Wi-Fi connection
- PoE power supply
- External video play via USB interface
- HDMI, DVI output
- Emergency event recording and picture capturing
- Video wall control: window division, screen splicing, cross-window video roaming

DS-1200KI

Network Keyboard



- 128x64 LED dot matrix screen
- PTZ and TV wall control
- 4-axis joystick
- System upgrade and import / export of configuration files by USB-flash disk
- Network access and configuration by Web browser support

DS-1100KI

Network Keyboard



- 7" TFT touch screen with 800×480 resolution
- Live view and video playback
- Video wall control
- 4-axis joystick
- Macro command operation
- Up to 255 analog domes by RS-485 connection
- Compatible with Hikvision IP cameras, DVR/NVR, decoder, matrix

DS-1006KI

RS-485 Keyboard



- 128x64 LED dot matrix screen
- PTZ and TV wall control
- 4-axis joystick
- System upgrade and import / export of configuration files by USB-flash disk
- RS-485 serial port

DS-1005KI

USB Keyboard



- USB HID protocol
- Power supply and communication by USB port directly;
- PTZ control: set and call the preset, patrol and pattern
- DVR/NVR menu control
- Compatible with client software and platform software;

Portable Camera

DS-MH6171

Portable PTZ Dome



- 2 MP Full HD1080p high resolution
- 30X optical zoom, 12X digital zoom
- H.264+ optimized codec to reduce storage
- Dual SD card slots, up to 128 GB for each card
- Supports Wi-Fi, 3G, 4G wireless connection
- Interchangeable Lithium battery, up to 6-hour operating time
- Alarm I/O, RS232, RS485 interfaces
- Supports Bluetooth connection
- IP66 weather-proof protection
- Up to 195 feet (60m) IR range
- Powerful magnetic base for vehicle-roof mounting
- iVMS-4500 client for remote operation

Compression Card

DS-4304HFHI-E


HD1080P Compression Card



- 4-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@1920×1080P resolution real-time recording
- HDMI output at up to 1920×1080P resolution
- PCI-Ex1 2.0 standard
- OSD, LOGO and mask area settings

DS-4308/16HWI-E


Full 960H Compression Card



- 8/16-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@WD1(PAL:960×576,NTSC:960×480) resolution
- real-time recording
- PCI-Ex1 2.0 standard
- OSD,LOGO and MASK overlay

DS-4304/08/16HFVI-E

Full 4CIF Compression Card



- 4/8/16-ch video&audio input
- H.264 & Dual-stream video compression
- Full channel@4CIF resolution real-time recording
- PCI-Ex1 2.0 standard
- OSD,LOGO and MASK overlay

ACCESS CONTROL

DS-K2601/02/04
K2600 Series Access Controller



- Single/double/four door access controller
- Max. storage 100,000 cards and 300,000 access control events
- Uplink: TCP/IP and RS-485
- Accessible card reader: 2/4/4 Wiegand readers or 2/4/8 RS485 readers
- Input interface: 4 alarm input, door sensor×1/2/4, door switch×1/2/4, case Input×2/4/8, fire alarm linkage×1, tamper-proof×1
- Output interface: door switch relay×1/2/4, alarm relay×1/2/4

DS-K2210
Master Elevator Controller



- Max. storage of 20,000 cards and 50,000 events
- Up to 128 floor permissions
- Uplink: TCP/IP and RS-485
- Accessible card reader: 2 Wiegand readers or 2 RS485 readers
- Input interface: emergency button×1, 1 fire alarm button×1, 1 maintenance button×1, case input×2
- Output interface: door switch relay×4, alarm relay×4

DS-K1103M/MK
K1100 Series Card Reader



- Reads Mifare 1 card
- Supports RS485 and Wiegand (W26/W34) protocol
- Tamper-proof alarm
- Dust-proof, IP 64
- Applies to 120 gang box only

DS-K1108M/MK/E/EK
K1100 Series Card Reader



- Reads Mifare 1 card/ EM card
- Supports RS485 and Wiegand (W26/W34) protocol
- Tamper-proof alarm
- Dust-proof, IP 65
- Apply to 86 & 120 gang box

DS-K2801/02/04
K2800 Series Access Controller



- Single/double/four door access controller
- Max. storage 100,000 cards and 500,000 access control events
- Uplink communication: TCP/IP;
- Accessible card reader: 2/4/4 Wiegand readers
- Input interface: door sensor×1/2/4, door switch×1/2/4, case Input×1/2/4
- Output interface: Door Switch, relay×1/2/4, alarm relay×1/2/4

DS-K2M0016A
Distributed Elevator Controller



- Up to 16 floor permissions
- Uplink communication: RS-485
- Input interface: alarm input×1, tamper alarm×1
- Output interface: relay output×16

DS-K1104M/MK
K1100 Series Card Reader



- Reads Mifare 1 card
- Supports RS485 and Wiegand (W26/W34) protocol
- Tamper-proof alarm
- Dust-proof, IP 65; vandal proof, IK10
- Applies to 86 & 120 gang boxes

DS-K1801M/MK/E/EK
K1800 Series Card Reader



- Reads Mifare 1 card/ EM card
- Supports Wiegand (W26/W34) protocol
- Dust-proof, IP 65

DS-K2700
K2700 Series Master Access Controller



- Master Access Controller, Storage with 200,000 cards and 600,000 access control events.
- Uplink Communication: TCP/IP×2 and RS-485; Downlink Communication: RS-485×8(4 RS-485 Loops), TCP/IP.
- Max. 64 Distributed Access Controller, Max. 128 Doors.
- Input interface: Alarm Input×16, Fire Alarm Linkage×1, Tamper-proof×1;
- Output interface: Alarm Output×8.
- USB interface×1, IP54

DS-K1101M/MK
K1100 Series Card Reader



- Reads Mifare 1 card
- Supports RS485 and Wiegand (W26/W34) protocol
- Tamper-proof alarm
- Dust-proof, IP 64
- Applies to 120 gang box only

DS-K1106M
K1100 Series Card Reader



- Reads Mifare 1 card
- Supports RS485 and Wiegand (W26/W34) protocol
- Tamper-proof alarm
- indoor installation
- Applies to 86 gang box
- Mainly for connecting to elevator controller

DS-K1802M/MK/E/EK
K1800 Series Card Reader



- Reads Mifare 1 card/ EM card
- Supports Wiegand (W26/W34) protocol
- Dust-proof, IP 65

DS-K27M01/02/04
K2700 Series Distributed Access Controller



- Distributed Access Controller, Storage with 20,000 cards and 60,000 access control events.
- Uplink Communication: TCP/IP and RS-485×2;
- Accessible Card Reader: 2/4/4 Wiegand readers or 2/4/8 RS485 readers;
- Input interface: Alarm Input×6, Door Sensor×1/2/4, Door Switch×1/2/4, Fire Alarm Linkage×1, Tamper-proof×1;
- Output interface: Door Switch Relay×1/2/4, Alarm Relay×6.

DS-K1102M/MK/E/EK
K1100 Series Card Reader



- Reads Mifare 1 card/EM Card
- Supports RS485 and Wiegand (W26/W34) protocol
- Tamper-proof alarm
- Dust-proof, IP 64
- Applies to 86 & 120 gang boxes

DS-K1107M/MK/E/EK
K1100 Series Card Reader



- Reads Mifare 1 card/ EM Card
- Supports RS485 and Wiegand(W26/W34) protocol
- Tamper-proof alarm
- Dust-proof, IP 65
- Applies for 86 & 120 gang boxes.

DS-K1201MF/EF
Fingerprint Reader



- Reads Mifare 1 card/ EM card
- Fingerprint (capacity: 5000)
- Supports RS485 (HiK private)
- IP65
- Wall mounting with screws
- Gang box not supported

ACCESS CONTROL

HIKVISION

DS-K1T105M/E(-C)
Access Control Terminal



- 2.8 inch LCD-TFT Screen Standalone Access Control Terminal, Built-in Mifare/ EM card reading module
- Storage with 100,000 cards and 300,000 access control events
- Uplink Communication: TCP/IP, RS-485, Wi-Fi; Downlink Communication: RS-485, Wiegand(W26/W34)
- 17 Keys keyboard and doorbell, DC 12V/1A
- -C with 2 Mega pixels camera

DS-K1T804F/MF/EF(-1)
Fingerprint Access Control Terminal



- Integrated management of access control & time attendance
- 2.4" LCD screen
- Max. 3,000 users, 3,000 fingerprints, and 100,000 event records
- Uplink communication: TCP-IP, Wi-Fi (not available for -1 model); downlink communication: RS485 (connect to secure module)
- Wiegand out (W26/W34) and Wiegand in (W26/W34) (not available for -1 model)

DS-K1T605M/E/MF/EF(-B)
Face Recognition Terminal



- 5-inch LCD touch screen, 300,000 pixel wide-angle lens
- Built-in Mifare/ EM card reading module (not available for M/E modules)
- Face recognition distance: 0.3m to 1m; live face detection, max. 2000 face pictures
- Supports TCP/IP,Wi-Fi communication, DC 12V/2A
- *-B module equipped with lithium battery

DS-K4T100
Lock



- Electric bolt, polished and brushed stainless steel
- Supports thrust of 800kg
- Working current: 900mA (startup current), 100mA (standby)
- DC12V

DS-K1T201MF/EF(-C)
Access Control Terminal



- 2.8 inch LCD-TFT Screen IP-based Fingerprint Access Control Terminal, Built-in Mifare/ EM card reading module
- Storage with 5000 fingerprints, 100,000 cards and 300,000 access control events
- Uplink Communication: TCP/IP, RS-485, Wi-Fi; Downlink Communication: RS-485, Wiegand(W26/W34)
- 17 Keys keyboard and doorbell, DC 12V/1A
- -C with 2 Mega pixels camera

DS-K1A802F/MF/EF(-B)(-1)
Time Attendance Terminal



- LCD Display fingerprint time attendance terminal
- Built-in Mifare/EM card reading module (not available for F module)
- Max. 3,000 fingerprints and 100,000 access control events
- Supports time attendance function, automatic report generation, optical fingerprint module
- Uplink communication: TCP-IP, Wi-Fi (Not available for -1 model)
- *-B model supports lithium battery

DS-K1F100-D8E
Card Issuer



- Plug-and-play USB with no-driver technology
- Supports various card types (Mifare card and EM card)

DS-K4T100-U1
Lock



- Lower U-bracket of electric bolt, for usage with DS-K4T100.

DS-K1T801M/E
Access Control Terminal



- Standalone Access Control Terminal, Built-in Mifare/ EM card reading module,
- Storage with 3,000 cards
- 12 Keys keyboard and doorbell, DC 12V/1A

DS-K1T500S
Video Access Control Terminal




- Built-in 2 MP camera
- Max. 50,000 cards and 200,000 access control events
- Two-way audio intercom, remote live view, video recording through NVR, optical fingerprint module
- Uplink communication: TCP/IP, RS-485, Wi-Fi; downlink communication: RS-485, Wiegand(W26/W34)
- Supports SD card, IP65, DC 12V/1A

DS-K1F180-D8E
Card Issuer



- Plug-and-play USB with no-driver technology
- Supports various card types (Mifare card and EM card)

DS-K4T100-U2
Lock



- Upper and lower U-bracket of electric bolt, for usage with DS-K4T100

DS-K1T802M/E
Access Control Terminal



- Standalone Access Control Terminal, Built-in Mifare/ EM card reading module,
- Storage with 3,000 cards and 10,000 access control events
- Uplink Communication: TCP/IP
- 12 Keys keyboard and doorbell, DC 12V/1A

DS-K1T501SF
Video Access Control Terminal



- Built-in Mifare card reading module, 2 MP camera
- Max. 50,000 cards, 3,000 fingerprints, and 200,000 access control events
- Two-way audio intercom, remote live view, video recording through NVR, optical fingerprint module
- Uplink communication: TCP/IP, RS-485, Wi-Fi; downlink communication: RS-485, Wiegand(W26/W34)
- Supports SD card, IP65, DC 12V/1A

DS-K1F820-F
Fingerprint Enrollment Scanner



- Plug-and-play USB with no-driver technology, USB 2.0
- Fingerprint enrollment for DS-K1T201, DS-K1201, DS-K1T804, DS-K1A802 and DS-K1T501


ACCESS CONTROL

DS-K4H250D Lock



- Double-door magnetic lock
- 2x300 kg static linear thrust
- Working current: 12V/500mA×2 24V/250mA×2

DS-K4H250-LZ Lock



- LZ-bracket of magnetic lock for DS-K4H250S/D

DS-K4H250-U Lock




- U-bracket of magnetic lock for DS-K4H250S/D

DS-K4H450D Lock



- Double-door magnetic lock
- 2x450kg static linear thrust
- Working current: 12V/500mA×2, 24V/250mA×2

DS-K4H450-LZ Lock



- LZ-bracket of magnetic lock for DS-K4H450D

DS-K4T108 Lock




- Electric bolt
- Dimensions: 205×34×42mm (8.1×1.3×1.7")
- 12VDC, ≤1.2A (startup current), 0.2A (Standby)

DS-K4T108-U1 Lock



- U-bracket of electric bolt for usage with DS-K4T108

DS-K4H258S Lock



- Single-door magnetic lock
- 280kg (550Lbs) linear thrust
- 12 VDC, 340mA

DS-K4H258D Lock



- Double-door magnetic lock
- 280kg (550Lbs)×2 linear thrust
- 12 VDC, 340mA×2

DS-K4H258-LZ Lock



- LZ-Bracket of magnetic lock for DS-K4H258S/D

DS-K4H258-U Lock



- U-Bracket of magnetic lock for DS-K4H258S/D

DS-K2M060 Secure Module



- Accessible card reader: 1 Wiegand reader, uplink RS-485 Interface
- Input interface: door magnetic×1, door switch×1, tamper-proof×1
- Output interface: door switch relay×1, alarm relay×1
- DC 12V

DS-K7P01 Button



- Aluminum alloy panel, metal button
- Dimension (L×W×H): 86×86×20mm (3.39×3.39×0.79")

DS-K7P02 Button



- Aluminum alloy panel, metal button
- Dimension (L×W×H): 90×35×28.9mm (3.54×1.38×1.14")

DS-K7P03 Button



- Aluminum panel, led Indicator
- Dimension (L×W×H): 86×86×25mm (3.39×3.39×0.98")

DS-K7P04 Button



- Aluminum panel
- Dimension (L×W×H): 86×50×34 mm (3.39×1.97×1.34")

ACCESS CONTROL



DS-K7P05 Button



- Structure: stainless steel panel, metal button, metal bottom case
- Dimension (L×W×H): 90×35×54 mm (3.54×1.38×2.13")

DS-K7P06 Button



- Structure: stainless steel panel, metal button, metal bottom case
- Dimension (L×W×H): 88×88×54 mm (3.46×3.46×2.13")

DS-K7PEB Button




- Emergency Break glass, green/red color

MF-Y3 Card




- 13.56MHz response frequency
- Dimension: 41×32×3.5mm
- Working temperature: -10° C to +50° C
- IP67
- Blue/red/orange

DS-KEM125 Card




- EM contactless smart card
- Frequency: 125KHz

S50+TK4100 Card




- Mifare1+EM dual frequency card

IC S50 Card



- Mifare 1 contactless smart card
- Frequency: 13.56vMHz

FM11RF08-M1 Card



- Mifare 1 Contactless Smart card
- Frequency: 13.56vMHz

VIDEO INTERCOM

DS-KD8102-V
Plastic Apartment
Door Station



- 3.5" colorful TFT LCD capacitive touch key
- 1.3 MP door station, plastic
- Display resolution: 480×320
- Camera resolution: HD720P, 25fps(P)/30fps(N),
- Visible light supplement
- 10M/100M/1000M self-adaptive Ethernet, Wiegand & RS-485
- 8-ch alarm input, 4-ch alarm output
- IP65, USB 2.0, 12 VDC

DS-KD8002-VM
Metal Apartment
Door Station



- 1.3 MP aluminum alloy door station with 3.5" colorful TFT LCD and physical touch key
- Display resolution: 480×320
- Camera resolution: HD720P, 25fps(P)/30fps(N)
- Visible light supplement
- 10M/100M/1000M self-adaptive Ethernet, Wiegand & RS-485
- 8-ch alarm input, 4-ch alarm output
- IP65, USB 2.0, 12 VDC

DS-KD3002-VM
Metal Apartment
Door Station



- 1.3 MP aluminum alloy door station with 3.5" colorful TFT LCD and physical touch key
- Display resolution: 480×320
- Camera resolution: HD720P, 25fps(P)/30fps(N)
- Visible light supplement
- 10M/100M/1000M self-adaptive Ethernet, Wiegand & RS-485
- 8-ch alarm input, 4-ch alarm output
- IP65, USB 2.0, 12 VDC

DS-KV 81/82/84 02-IM
Metal Villa Door Station



- 1.3 MP villa door station, aluminum alloy
- 1/2/4-ch indoor station access
- Camera resolution: HD720P, 25fps(P)
- IR supplement
- 10M/100M self-adaptive Ethernet, RS-485
- 4-ch alarm input, 1-ch alarm output
- IP65
- 12 VDC

DS-KV8102-IP/VP
Plastic Villa Door Station



- 1.3 MP villa door station, plastic
- 1-ch indoor station access,
- Camera resolution: HD720P, 25fps(P), IR/visible light supplement
- 10M/100M self-adaptive Ethernet, RS-485
- 4-ch alarm input, 1-ch alarm output
- IP65
- 12 VDC

DS-KH8300-T
IP Indoor Station



- 7" colorful TFT LCD touch screen indoor station
- Display resolution: 1024×600
- 10/100Mbps Ethernet
- 8-ch alarm input
- PoE Cable/12 VDC

DS-KH8301-WT
IP Indoor Station



- 7" colorful TFT LCD touch screen indoor station with mechanical switch
- Display resolution: 1024×600
- 0.3MP camera resolution: 640×480
- 10/100Mbps Ethernet, Wi-Fi 802.11b/g/n
- 8-ch alarm input
- Supports SD card
- PoE cable
- 12 VDC

DS-KH6310(-W/-WL)
IP Indoor Station



- 7" colorful TFT LCD touch screen indoor station
- Display resolution: 800×480
- 10/100Mbps Ethernet
- 2/8-ch alarm input, Power Over Network Cable/ 12 VDC
- *-W/WL model supports Wi-Fi 802.11b/g/n

DS-KH6210-L
IP Indoor Station



- 7" colorful TFT LCD screen indoor station with physical push button
- Display resolution: 800×480
- 10/100Mbps Ethernet
- 2-ch alarm input
- PoE cable/12 VDC

DS-KM8301
Master Solution



- CMOS 0.3 MP, 7" colorful TFT LCD capacitive touch screen
- Display resolution 1024×600
- Touch key, physical button
- 1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
- 2 RS-485 half-duplex ports
- 1 USB interface, 2 on-off outputs, 2 relay outputs, 4 on-off inputs
- 12 VDC

DS-KIS601
IP Intercom Kit



- DS-KV8102-IM x1
- DS-KH6310-WL x1
- 12VDC x2
- One-touch call indoor station

DS-KB2411-IM
Analog Door Station



- Pinhole camera with 720×576 @ 25 fps, video intercom
- Supports 2 door stations cascading in intercom system
- Unlock control, self-adaptive IR supplement

DS-KH2220
Analog Indoor Station



- 7" LCD screen indoor station, video intercom
- Supports three indoor stations cascading in intercom system
- Remote unlocking, monitoring of door stations and external analog cameras

DS-KIS202
Analog Intercom Kit



- Kit includes DS-KB2411-IM and DS-KH2220

DS-KB2421-IM
Analog Door Station



- Pinhole camera with 720×576 @ 25 fps, video intercom
- Supports 2 door stations cascading in intercom system
- Unlock control
- Self-adaptive IR supplement
- Anti-oxidant zinc alloy
- IK7, IP65

DS-KIS203
Analog Intercom Kit



- Kit includes DS-KB2421-IM and DS-KH2220

VIDEO INTERCOM

HIKVISION

DS-KAD606
Distributor



- Pinhole camera with 720×576 @+E25 25 fps, video intercom communication
- Supports two door station cascading in intercom system;
- Unlocking controlling
- self-adaptive IR supplement

DS-KAD612
Distributor



- Built-in voltage-stabilized power
- 16 x 100Mbps ports (12-ch supporting network cable powering and 4-chcascading LAN interfaces)
- Suitable for indoor station and villa door station

DS-KAD606-N(-P)
Distributor



- 8 RJ-45 interfaces, including 6 adaptive 10/100 Mbps LAN interfaces supporting network cable powering and 2 adaptive 10/100 Mbps cascading LAN interfaces, adaptive 10/100 Mbps LAN interfaces supports providing 24 VDC for video
- Suitable for indoor station and villa door station
- *-P Model with power supply

DS-KAW50-1
Power Supply



- Power supply for door station and villa door station
- Output: 12 VDC, 4.2A, with box

DS-KAW50-1N/2N
Power Supply



- Power supply for door station and villa door station
- Output: 12 VDC, 4.2A, 50/150W, without box

DS-KB8112-IM
Doorbell



- 1.3 MP IP vandal-resistant door station
- FOV: 80° (Horizontal) and 44° (Vertical)
- FOV adjustment -50° to 50°
- 10/100 Mbps self-adaptive Ethernet
- PoE (Power over Ethernet),
- IR supplement, IR distance: 5 m
- IK 9, IP66

DS-KB60/6403-WIP
Doorbell



- 2MP HD colorful camera
- FOV: 160° (Horizontal)
- 1 call button, 1 reset button, 1 wireless interface (wireless network card), 2.4 GHz
- IR supplement, IR distance: 5 m
- Power: 16VAC-24VAC/12VDC

DS-KV8103-IME2
2-Wire Door Station



- 1080P two-wire door station
- Fisheye camera
- Low illumination
- IP65, vandal-resistant metal
- IR supplement
- One-touch call indoor station
- Two-wire interface, lock control, RS-485
- Powered by DS-KAD709

DS-KH8340-TCE2
2-Wire Indoor Station



- 7-inch colorful TFT LCD, capacitive touch screen with touch button
- Display resolution: 1024x600
- Two-wire interface
- Wall mounting
- Supports monitoring of door station and external IP cameras
- Powered by DS-KAD709

DS-KAD709
2-Wire Controller



- 1 RJ-45 Interface
- 9 two-wire interface
- Reset button
- Wall mounting
- Power: 24VDC, 60W

DS-KIS701
2-Wire Intercom Kit



- DS-KV8103-IME2 x1
- DS-KH8340-TCE2 x1
- DS-KAD709 x1
- One-touch call indoor station
- Includes power supply (EU standard) for DS-KAD709

SECURITY ALARM

Wireless Kits



- Wireless Security Control Panel: DS-PW32
- Wireless Magnetic Contact: DS-PD1-MC-WWS
- Wireless Panic Button: DS-PD1-EB-WR
- Wireless PIR: DS-PD1-P12-W
- Wireless Keyfob: DS-PK00-Y

DS-PMA-WR

Wireless Repeater



- Communication frequency: 433MHz
- Two-way communication: 800 meters (open area)
- AES-128 data encryption
- 3000 mAh backup battery

DS-19A08-01BN(G)

MBUS Security Control Panel



- 8 inputs onboard, expandable to 256
- 4 outputs onboard, expandable to 256
- 2 buses, up to 2.4km each (SWG17/AWG15)
- Transmission modes: IP, PSTN, (GPRS)
- Non-polarity MBUS

DS-19A08/16-BN(G)

Security Control Panel



- 8/16 inputs onboard, expandable to 48
- 4 outputs onboard, expandable to 48
- Transmission modes: IP, PSTN, (GPRS)

DS-PV4808N-PL(S)

Video Security Control Panel



- 8 Inputs onboard, expandable to 48
- 4 Outputs onboard, expandable to 48
- Transmission modes: IP, PSTN, (4G)
- 8-CH IPC

DS-PD1-MC-MS

Magnetic Contact



- Metal plating shell
- Connection type: NC
- Designed for doors or windows
- Dimension(L x W x H): 50mm x 18mm x 10mm

DS-PD1-SKM

Vibration Detector



- Adjusts a wide range of sensitivity
- Ceramic sensor design
- Tamper alarm
- Dual color LED indicator

DS-PD1-BG9

Break-Glass Detector



- Dual color LED indicator
- High/Low sensitivity optional
- Anti-electromagnetic interference
- Anti-RF interference

DS-PD1-EB-86

Board-mounted Panic Button



- Flame retardant ABS shell
- Capacity: ≤250 V ≤300 mA
- Connection mode: NO/NC

DS-PD1-EB

Panic Button



- Flame retardant ABS shell
- Capacity: ≤250 V ≤300 mA
- Connection mode: NO/NC

DS-PK00(M)-LCD Series

DS-PK00M-LCD/DS-PK00-LCD

LCD Keypad



- Arm/disarm by swiping cards, up to 32 cards ([DS-PK00(M)-LCD])
- Remote arm/disarm via keyfob, up to 32 wireless keyfobs
- One push to arm, disarm by password
- Displaying the signal strength of GPRS
- Displaying real-time status of zones

DS-19K00-Y

Wireless Keyfob



- Button: arm/disarm, stay armed, panic alarm, alarm elimination
- Frequency: 433MHz
- Distance: 100m (open area)
- Battery: 3V/210 mAh
- Dimensions (L x W x H): 63mm x 49mm x 16mm

DS-PM-RS18

8 Inputs Expander



- 8 inputs
- Tamper alarm
- EOL: 2.2K, 3.3K, 5.6K, 8.2K

DS-PM-RS04 (RI)



- Power supply: DC 12V
- Operating temperature: -10°C ~ +55°C
- Relay: DC 30V/1A

DS-PM-RS04 (RI)-H



- Power supply: DC 12V
- Operating temperature: -10°C ~ +55°C
- Relay: AC 220V/10A

DS-PM-M11



- Non-polarity MBUS
- 1 input

SECURITY ALARM

HIKVISION

DS-PM-M12

Dual Inputs Expander



- Non-polarity MBUS
- 2 inputs

DS-PM-M18

8 Inputs Expander



- Non-polarity MBUS
- 8 inputs

DS-PM-MR

MBUS Repeater



- Non-polarity MBUS
- Voltage: 12 VDC
- Current: maximum 1.5 A
- Working temperature: -25°C~+55°C
- Dimensions (L x W x H): 74mm x 135mm x 28mm

DS-PM-M04-H

MBUS 4 Outputs Expander



- 4 outputs
- AC 220V/10A
- Dimensions (L x W x H): 114mm x 187mm x 31mm

DS-PM-M032

32 Outputs Expander



- 32 outputs
- Non-polarity MBUS
- Dimensions (L x W x H): 184mm x 387mm x 31mm

DS-PI-XX

Active Infrared



- Beam number: two/three/four
- Detection range: 100m, 150m, 200m, 250m
- Operating voltage: DC10.5~28V (Non-polarity)
- Working temperature:-25°C~+55°C, RH 95%

DS-PI-XX/FM

Selectable Frequency Active Infrared



- Frequency: CH1-CH4
- Beam Number: Two/Three/Four
- Detection Range: 100m, 150m, 200m, 250m
- Operating Voltage: DC10.5~28V(Non-polarity)
- Operation Temperature:-25°C~+55°C, RH 95%

DS-PEA1-N

One button panic alarm station



- Wired IP
- Emergency call, Voice Intercom
- Support Micro SD/SDHC/SDXC
- Siren and audio expandable

DS-PEA1-N2

Two buttons panic alarm station



- Wired IP
- Emergency call, Consultant call, Voice Intercom
- Support MicroSD/SDHC/SDXC
- Siren and audio expandable

DS-PEA1

Panic alarm station with camera



- SNMP+RTSP+SIP+SDK
- Built-in 1.3MP camera, 24 hours monitoring
- Emergency call, Voice Intercom
- Support MicroSD/SDHC/SDXC, TCP/IP, dual net ports
- Siren and audio expandable

DS-PEA2

Box panic alarm station



- TCP/IP+SNMP+RTSP+SIP+SDK
- Built-in 1.30w camera
- Emergency call, Voice Intercom
- Support MicroSD/SDHC/SDXC
- Siren expandable

DS-PEA3M

Pole panic alarm station



- SNMP+RTSP+SIP+SDK
- Remote lock
- Video, Voice Intercom, Alarm linkage with camera
- Support MicroSD/SDHC/SDXC
- TCP/IP

DS-PEA3M-H

Pole panic alarm station without camera



- SNMP+RTSP+SIP+SDK
- Integrated with weak electric box, Remote lock
- Video Linkage, Voice Intercom,
- Support Micro SD/SDHC/SDXC
- TCP/IP

DS-PEA4L-7

Master station



- Capable to manage 255 public alarm devices
- Hand free or receiver pick up
- Real time alarm information display
- Voice intercom, monitoring, speed dial
- 7 inches touch screen