


## March Networks SDA Outdoor IR Dome standard definition outdoor analogue dome with IR, WDR

### Technical Specification

<b>Make</b>	March Networks	
<b>Company</b>	March Networks Corporation	
<b>Model code</b>	SDA Outdoor IR Dome	
<b>Previously known as</b>	1	
<b>Chip Inch Size</b>	1/3	
<b>Colour Type</b>	Colour / Monochrome	
<b>Resolution TVL</b>	1.3MP	
<b>Sensitivity lux</b>	0 ~ 0.2	
<b>Digital (DSP)</b>	Yes	
<b>Electrical Specifications</b>	Voltage: 12 V DC Power Consumption: 1.7 ~ 3.5 W	
<b>Focal length</b>	2.8 ~ 12mm	

<b>Back Light Compensation</b>	Yes
<b>Auto Gain Control</b>	Yes
<b>White Balance</b>	Yes
<b>Electronic Shutter range</b>	50 (60) ~ 60,000s
<b>S/ N (Signal/ Noise) Ratio dB</b>	> 55
<b>Synchronisation</b>	Internal
<b>Signal Mode</b>	PAL, NTSC
<b>Built-in IR LED</b>	Yes
<b>Video Output</b>	1.0Vp-p, 75? Composite
<b>Physical Specifications</b>	Dimensions mm: 109 x 145 Weight g: 748
<b>Environmental Specifications</b>	Operating Temp °C: -20 ~ +50 C (-4 ~ +122 F) Operating Humidity %: 0 ~ 90

**Additional info**

- Get your preferred field of view
- Mounts to brick and concrete without additional accessories
- Ideal for outdoor applications
- See colour in low-light environments
- Integrated IR
- Icon-driven on-screen display